

```
# In case you want to add a .htpasswd authentication
# you'll have to add the host of the shop as an allowed entity,
# so that calls from the host skip the authentication
# Example:
# Order Deny,Allow
# Deny from All
# AuthType Basic
# AuthName "Access not allowed"
# AuthUserFile path_to_htpasswd_file/.htpasswd
# Require valid-user
# Allow from localhost
# Satisfy Any

<IfModule mod_rewrite.c>
    Options +FollowSymLinks
    RewriteEngine On
    RewriteBase /

    RewriteCond %{REQUEST_URI} config\.inc\.php [NC]
    RewriteRule ^config\.inc\.php index\.php [R=301,L]

    RewriteCond %{QUERY_STRING} fnc=(getShopVersion|getShopEdition|getRevision) [NC]
    RewriteRule ^(.*)$ $1? [R=301,L]

    RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
    RewriteRule . * - [F]

    RewriteCond %{REQUEST_URI} oxseo\.php$
    RewriteCond %{QUERY_STRING} mod_rewrite_module_is=off
    RewriteRule oxseo\.php$ oxseo.php?mod_rewrite_module_is=on [L]

    RewriteCond %{REQUEST_URI} !^(/admin|/core|/application|/export|/modules|/out|/setup|/tmp|/views)
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule !(\.html|\.jpg|\.css|\.pdf|\.doc|\.gif|\.png|\.js|\.htm|\.svg)$ %{REQUEST_URI} [R=301,L]

    RewriteCond %{REQUEST_URI} !^(/admin|/core|/application|/export|/modules|/out|/setup|/tmp|/views)
    RewriteCond %{REQUEST_FILENAME} !-
```

```
RewriteCond %{REQUEST_FILENAME} !-t
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (\.html|\/)$ oxseo.php

RewriteCond %{REQUEST_URI} (/out/pictures/generated/)
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (\.jpe?g|\.gif|\.png|\.svg)$ getimg.php

</IfModule>

# disabling log file access from outside
<FilesMatch "(EXCEPTION_LOG|txt|log|tp1|pkg|revl|ini|pkg|info|pem)$">
    order allow,deny
    deny from all
</FilesMatch>

# Prevent .ht* files from being sended to outside requests
<Files ".ht">
    Order allow,deny
    Deny from all
</Files>

Options -Indexes
DirectoryIndex index.php index.html
```