

```
RewriteEngine On
```

```
RewriteCond %{HTTP: Authorization} ^(.*)
```

```
RewriteRule .* - [e=HTTP_AUTHORIZATION:%1]
```

```
# The following rule tells Apache that if the requested filename  
# exists, simply serve it.
```

```
RewriteCond %{REQUEST_FILENAME} -s [OR]
```

```
RewriteCond %{REQUEST_FILENAME} -l [OR]
```

```
RewriteCond %{REQUEST_FILENAME} -d
```

```
RewriteRule ^.*$ - [NC,L]
```

```
RewriteCond %{REQUEST_URI} ^/api.+
```

```
RewriteRule ^(.*)$ api.php [NC,L]
```

```
# The following rewrites all other queries to index.php. The  
# condition ensures that if you are using Apache aliases to do  
# mass virtual hosting, the base path will be prepended to  
# allow proper resolution of the index.php file; it will work  
# in non-aliased environments as well, providing a safe, one-size  
# fits all solution.
```

```
RewriteCond %{REQUEST_URI}::$1 ^(/.+)(.+)::\2$
```

```
RewriteRule ^(.*) - [E=BASE:%1]
```

```
RewriteRule ^(.*)$ %{ENV:BASE}index.html [NC,L]
```