

```

# Apache Server Configs v2.13.0 | MIT License
# https://github.com/h5bp/server-configs-apache

# (!) Using `.htaccess` files slows down Apache, therefore, if you have
# access to the main server configuration file (which is usually called
# `httpd.conf`), you should add this logic there.
#
# https://httpd.apache.org/docs/current/howto/htaccess.html.

#####
# # CROSS-ORIGIN #
#####

# -----
# | Cross-origin requests |
# -----

# Allow cross-origin requests.
#
# https://developer.mozilla.org/en-US/docs/Web/HTTP/Access_control_CORS
# http://enable-cors.org/
# http://www.w3.org/TR/cors/

# <IfModule mod_headers.c>
#     Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# | Cross-origin images |
# -----

# Send the CORS header for images when browsers request it.
#
# https://developer.mozilla.org/en-US/docs/Web/HTML/CORS_enabled_image
# https://blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html

<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        <FilesMatch "\.(bmp|curl gif|ico|jpe?g|png|svgz?|webp)$">
            SetEnvIf Origin ":" IS_CORS
            Header set Access-Control-Allow-Origin "*" env=IS_CORS

```

```

        Header set Access-Control-Allow-Origin * env=IS_LUKS
    </FilesMatch>
</IfModule>
</IfModule>

# -----
# | Cross-origin web fonts |
# -----

# Allow cross-origin access to web fonts.

<IfModule mod_headers.c>
    <FilesMatch "\.(eot|otf|tt[cf]|woff2?)$">
        Header set Access-Control-Allow-Origin "*"
    </FilesMatch>
</IfModule>

# -----
# | Cross-origin resource timing |
# -----

# Allow cross-origin access to the timing information for all resources.
#
# If a resource isn't served with a `Timing-Allow-Origin` header that
# would allow its timing information to be shared with the document,
# some of the attributes of the `PerformanceResourceTiming` object will
# be set to zero.
#
# http://www.w3.org/TR/resource-timing/
# http://www.stevesouders.com/blog/2014/08/21/resource-timing-practical-tips/

# <IfModule mod_headers.c>
#     Header set Timing-Allow-Origin: "*"
# </IfModule>

# #####
# # ERRORS #
# #####

# -----
# | Custom error messages/pages |
# ..

```

```
# -----  
  
# Customize what Apache returns to the client in case of an error.  
# https://httpd.apache.org/docs/current/mod/core.html#errordocument
```

```
ErrorDocument 404 /404.html
```

```
# -----  
# | Error prevention |  
# -----
```

```
# Disable the pattern matching based on filenames.  
#  
# This setting prevents Apache from returning a 404 error as the result  
# of a rewrite when the directory with the same name does not exist.  
#  
# https://httpd.apache.org/docs/current/content-negotiation.html#multiviews
```

```
Options -MultiViews
```

```
# #####  
# # INTERNET EXPLORER #  
# #####
```

```
# -----  
# | Document modes |  
# -----
```

```
# Force Internet Explorer 8/9/10 to render pages in the highest mode  
# available in the various cases when it may not.  
#  
# https://hsivonen.fi/doctype/#ie8  
#  
# (!) Starting with Internet Explorer 11, document modes are deprecated.  
# If your business still relies on older web apps and services that were  
# designed for older versions of Internet Explorer, you might want to  
# consider enabling `Enterprise Mode` throughout your company.  
#  
# https://msdn.microsoft.com/en-us/library/ie/bg182625.aspx#docmode  
# http://blogs.msdn.com/b/ie/archive/2014/04/02/stay-up-to-date-with-enterprise-mode-for-internet-explorer-11.aspx
```

```

<IfModule mod_headers.c>

    Header set X-UA-Compatible "IE=edge"

    # `mod_headers` cannot match based on the content-type, however,
    # the `X-UA-Compatible` response header should be send only for
    # HTML documents and not for the other resources.

    <FilesMatch "\.
    (appcache|atom|bbaw|bmp|crx|css|curl|eot|f4[abpv]|flv|geojson|gif|htcl|icol|jpe?
    |j|j|json|ld)?
    |m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
    |swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|woff2?|xlcl|x|l|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>

</IfModule>

# -----
# | Iframes cookies |
# -----

# Allow cookies to be set from iframes in Internet Explorer.
#
# https://msdn.microsoft.com/en-us/library/ms537343.aspx
# http://www.w3.org/TR/2000/CR-P3P-20001215/

# <IfModule mod_headers.c>
#     Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD
# IVAi IVDi CONi HIS OUR IND CNT\""
# </IfModule>

# #####
# # MEDIA TYPES AND CHARACTER ENCODINGS #
# #####

# -----
# | Media types |
# -----

```

```
# Serve resources with the proper media types (f.k.a. MIME types),
#
# https://www.iana.org/assignments/media-types/media-types.xhtml
# https://httpd.apache.org/docs/current/mod/mod\_mime.html#addtype

<IfModule mod_mime.c>

    # Data interchange

    AddType application/atom+xml          atom
    AddType application/json              json map topojson
    AddType application/ld+json           jsonld
    AddType application/rss+xml           rss
    AddType application/vnd.geo+json      geojson
    AddType application/xml               rdf xml

    # JavaScript

    # Normalize to standard type.
    # https://tools.ietf.org/html/rfc4329#section-7.2

    AddType application/javascript        js

    # Manifest files

    # If you are providing a web application manifest file (see
    # the specification: https://w3c.github.io/manifest/), it is
    # recommended that you serve it with the `application/manifest+json`
    # media type.
    #
    # Because the web application manifest file doesn't have its
    # own unique file extension, you can set its media type either
    # by matching:
    #
    # 1) the exact location of the file (this can be done using a
    #    directive such as ``, but it will NOT work in
    #    the `.htaccess` file, so you will have to do it in the main
    #    server configuration file or inside of a ``
    #    container)
    #
    #    e.g.:
```

```
#
#   <Location "/.well-known/manifest.json">
#       AddType application/manifest+json          .json
#   </Location>
#
# 2) the filename (this can be problematic as you will need to
# ensure that you don't have any other file with the same name
# as the one you gave to your web application manifest file)
#
# e.g.:
#
#   <Files "manifest.json">
#       AddType application/manifest+json          .json
#   </Files>
```

```
AddType application/x-web-app-manifest+json      webapp
AddType text/cache-manifest                       appcache
```

Media files

```
AddType audio/mp4                               f4a f4b m4a
AddType audio/ogg                                oga ogg opus
AddType image/bmp                                bmp
AddType image/svg+xml                            svg svgz
AddType image/webp                                webp
AddType video/mp4                                 f4v f4p m4v mp4
AddType video/ogg                                 ogv
AddType video/webm                                webm
AddType video/x-flv                               flv
```

```
# Serving `.ico` image files with a different media type
# prevents Internet Explorer from displaying them as images:
# https://github.com/h5bp/html5-
```

boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8ee

```
AddType image/x-icon                             cur ico
```

Web fonts

```
AddType application/font-woff                    woff
AddType application/font-woff2                   woff2
```

```
AddType application/vnd.ms-fontobject          eot
```

```
# Browsers usually ignore the font media types and simply sniff  
# the bytes to figure out the font type.  
# https://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern  
#  
# However, Blink and WebKit based browsers will show a warning  
# in the console if the following font types are served with any  
# other media types.
```

```
AddType application/x-font-ttf                 ttc ttf
```

```
AddType font/opentype                          otf
```

```
# Other
```

```
AddType application/octet-stream              safariextz
```

```
AddType application/x-bb-appworld            bbaw
```

```
AddType application/x-chrome-extension       crx
```

```
AddType application/x-opera-extension        oex
```

```
AddType application/x-xpinstall              xpi
```

```
AddType text/vcard                           vcard vcf
```

```
AddType text/vnd.rim.location.xloc           xloc
```

```
AddType text/vtt                             vtt
```

```
AddType text/x-component                     htc
```

```
</IfModule>
```

```
# -----  
# | Character encodings |  
# -----
```

```
# Serve all resources labeled as `text/html` or `text/plain`  
# with the media type `charset` parameter set to `UTF-8`.  
#  
# https://httpd.apache.org/docs/current/mod/core.html#adddefaultcharset
```

```
AddDefaultCharset utf-8
```

```
# -----
```

```
# Serve the following file types with the media type `charset`
```

```
# parameter set to `UTF-8`,
#
# https://httpd.apache.org/docs/current/mod/mod\_mime.html#addcharset

<IfModule mod_mime.c>
    AddCharset utf-8 .atom \
                .bbaw \
                .css \
                .geojson \
                .js \
                .json \
                .jsonld \
                .rdf \
                .rss \
                .topojson \
                .vtt \
                .webapp \
                .xloc \
                .xml
</IfModule>

# #####
# # REWRITES #
# #####

# -----
# | Rewrite engine |
# -----

# (1) Turn on the rewrite engine (this is necessary in order for
#     the `RewriteRule` directives to work).
#
#     https://httpd.apache.org/docs/current/mod/mod\_rewrite.html#RewriteEngine
#
# (2) Enable the `FollowSymLinks` option if it isn't already.
#
#     https://httpd.apache.org/docs/current/mod/core.html#options
#
# (3) If your web host doesn't allow the `FollowSymLinks` option,
#     you need to comment it out or remove it, and then uncomment
#     the `Options +SymLinksIfOwnerMatch` line (4). but be aware
```



```
.. -----  
# of the performance impact.  
#  
# https://httpd.apache.org/docs/current/misc/perf-tuning.html#symlinks  
#  
# (4) Some cloud hosting services will require you set `RewriteBase`.  
#  
# https://www.rackspace.com/knowledge\_center/frequently-asked-question/why-is-modrewrite-not-working-on-my-site  
# https://httpd.apache.org/docs/current/mod/mod\_rewrite.html#rewritebase  
#  
# (5) Depending on how your server is set up, you may also need to  
# use the `RewriteOptions` directive to enable some options for  
# the rewrite engine.  
#  
# https://httpd.apache.org/docs/current/mod/mod\_rewrite.html#rewriteoptions  
#  
# (6) Set %{ENV:PROTO} variable, to allow rewrites to redirect with the  
# appropriate schema automatically (http or https).
```

```
<IfModule mod_rewrite.c>
```

```
    # (1)  
    RewriteEngine On  
  
    # (2)  
    Options +FollowSymlinks  
  
    # (3)  
    # Options +SymLinksIfOwnerMatch  
  
    # (4)  
    RewriteBase /  
  
    # (5)  
    # RewriteOptions <options>  
  
    # (6)  
    RewriteCond %{HTTPS} =on  
    RewriteRule ^ - [env=proto:https]  
    RewriteCond %{HTTPS} !=on  
    RewriteRule ^ - [env=proto:http]
```

```
RewriteRule ^(.*)$ http://www.$1 [R=301,L]
```

```
RewriteCond %{THE_REQUEST} ^GET \(. \).html \ HTTP
```

```
RewriteRule (. \).html$ $1 [R=301]
```

```
RewriteRule (. *)/html$ $1/ [R=301]
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} /$
```

```
RewriteRule (. *)/ $1 [R=301]
```

```
RewriteCond %{REQUEST_FILENAME}.html -f
```

```
RewriteCond %{REQUEST_URI} !/$
```

```
RewriteRule (. *) $1.html [L]
```

```
</IfModule>
```

```
# -----  
# | Forcing `https://` |  
# -----
```

```
# Redirect from the `http://` to the `https://` version of the URL.  
# https://wiki.apache.org/httpd/RewriteHTTPToHTTPS
```

```
# <IfModule mod_rewrite.c>  
#     RewriteEngine On  
#     RewriteCond %{HTTPS} !=on  
#     RewriteRule ^(.*)$ https://%{HTTP_HOST}/$1 [R=301,L]  
# </IfModule>
```

```
# -----  
# | Suppressing / Forcing the `www.` at the beginning of URLs |  
# -----
```

```
# The same content should never be available under two different  
# URLs, especially not with and without `www.` at the beginning.  
# This can cause SEO problems (duplicate content), and therefore,  
# you should choose one of the alternatives and redirect the other  
# one.
```

```
#
```

```
# By default `Option 1` (no `www.`) is activated.
```

```
# http://no-www.org/faq.php?q=class_b
```

```
“
```

```

#
# If you would prefer to use `Option 2`, just comment out all the
# lines from `Option 1` and uncomment the ones from `Option 2`.
#
# (!) NEVER USE BOTH RULES AT THE SAME TIME!

# -----

# Option 1: rewrite www.example.com + example.com

<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+)$ [NC]
    RewriteRule ^ %{ENV:PROTO}://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2: rewrite example.com + www.example.com
#
# Be aware that the following might not be a good idea if you use "real"
# subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#     RewriteEngine On
#     RewriteCond %{HTTPS} !=on
#     RewriteCond %{HTTP_HOST} !^www\. [NC]
#     RewriteCond %{SERVER_ADDR} !=127.0.0.1
#     RewriteCond %{SERVER_ADDR} !=::1
#     RewriteRule ^ %{ENV:PROTO}://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# #####
# # SECURITY #
# #####

# -----
# | Clickjacking |
# -----

..

```

```
# Protect website against clickjacking.
#
# The example below sends the `X-Frame-Options` response header with
# the value `DENY`, informing browsers not to display the content of
# the web page in any frame.
#
# This might not be the best setting for everyone. You should read
# about the other two possible values the `X-Frame-Options` header
# field can have: `SAMEORIGIN` and `ALLOW-FROM`.
# https://tools.ietf.org/html/rfc7034#section-2.1.
#
# Keep in mind that while you could send the `X-Frame-Options` header
# for all of your website's pages, this has the potential downside that
# it forbids even non-malicious framing of your content (e.g.: when
# users visit your website using a Google Image Search results page).
#
# Nonetheless, you should ensure that you send the `X-Frame-Options`
# header for all pages that allow a user to make a state changing
# operation (e.g: pages that contain one-click purchase links, checkout
# or bank-transfer confirmation pages, pages that make permanent
# configuration changes, etc.).
#
# Sending the `X-Frame-Options` header can also protect your website
# against more than just clickjacking attacks:
# https://cure53.de/xfo-clickjacking.pdf.
#
# https://tools.ietf.org/html/rfc7034
# http://blogs.msdn.com/b/ieinternals/archive/2010/03/30/combating-clickjacking-with-x-
frame-options.aspx
# https://www.owasp.org/index.php/Clickjacking

# <IfModule mod_headers.c>

#     Header set X-Frame-Options "DENY"

#     # `mod_headers` cannot match based on the content-type, however,
#     # the `X-Frame-Options` response header should be send only for
#     # HTML documents and not for the other resources.

#     <FilesMatch "\.
(appache|atom|bbaw|bml|crl|css|curl|eot|f4[abpv]|flv|geojson|gif|htcl|icol|jpe?
```

```

gl jsl json(1d)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssl|safariextz|svgz?
|swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webappl|web[mp]|woff2?|x|oc|x|xml|xpi)$">
#           Header unset X-Frame-Options
#   </FilesMatch>

# </IfModule>

# -----
# | Content Security Policy (CSP) |
# -----

# Mitigate the risk of cross-site scripting and other content-injection
# attacks.
#
# This can be done by setting a `Content Security Policy` which
# whitelists trusted sources of content for your website.
#
# The example header below allows ONLY scripts that are loaded from
# the current website's origin (no inline scripts, no CDN, etc).
# That almost certainly won't work as-is for your website!
#
# To make things easier, you can use an online CSP header generator
# such as: http://cspisawesome.com/,
#
# http://content-security-policy.com/
# http://www.html5rocks.com/en/tutorials/security/content-security-policy/
# http://www.w3.org/TR/CSP11/.

# <IfModule mod_headers.c>

#           Header set Content-Security-Policy "script-src 'self'; object-src 'self'"

#           # `mod_headers` cannot match based on the content-type, however,
#           # the `Content-Security-Policy` response header should be send
#           # only for HTML documents and not for the other resources.

#   <FilesMatch "\.
<appache|atom|bbaw|bml|crl|css|curl|eot|f4[abpw]|flv|geojson|gif|htcl|icol|jpe?
gl jsl json(1d)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssl|safariextz|svgz?

```

```

| swf| top|json| tt[cf]| txt| vcard| vcf| vtt| webappl| web[mp]| woff2?| x|ocl| xml| xpi)"$">
#       Header unset Content-Security-Policy
#     </FilesMatch>

# </IfModule>

# -----
# | File access |
# -----

# Block access to directories without a default document.
#
# You should leave the following uncommented, as you shouldn't allow
# anyone to surf through every directory on your server (which may
# includes rather private places such as the CMS' s directories).

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# -----

# Block access to all hidden files and directories with the exception of
# the visible content from within the `/.well-known/` hidden directory.
#
# These types of files usually contain user preferences or the preserved
# state of an utility, and can include rather private places like, for
# example, the `.git` or `.svn` directories.
#
# The `/.well-known/` directory represents the standard (RFC 5785) path
# prefix for "well-known locations" (e.g.: `/.well-known/manifest.json`,
# `/.well-known/keybase.txt`), and therefore, access to its visible
# content should not be blocked.
#
# https://www.mnot.net/blog/2010/04/07/well-known
# https://tools.ietf.org/html/rfc5785

<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{REQUEST_URI} "!(^/)\.well-known/([^\./]+./?)+$" [NC]
    RewriteCond %{SCRIPT_FILENAME} -d [OR]

```

```
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
</IfModule>

# -----

# Block access to files that can expose sensitive information.
#
# By default, block access to backup and source files that may be
# left by some text editors and can pose a security risk when anyone
# has access to them.
#
# http://feross.org/cmsploit/
#
# (!) Update the `<FilesMatch>` regular expression from below to
# include any files that might end up on your production server and
# can expose sensitive information about your website. These files may
# include: configuration files, files that contain metadata about the
# project (e.g.: project dependencies), build scripts, etc..

<FilesMatch "(^#. *#| \.(bak|conf|dist|fla|in[ci]|log|psd|sh|sql|sw[op])|")$">

    # Apache < 2.3
    <IfModule !mod_authz_core.c>
        Order allow,deny
        Deny from all
        Satisfy All
    </IfModule>

    # Apache ≥ 2.3
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>

</FilesMatch>

# -----
# | HTTP Strict Transport Security (HSTS) |
# -----

# Force client-side SSL redirection.
```

```
#
# If a user types `example.com` in their browser, even if the server
# redirects them to the secure version of the website, that still leaves
# a window of opportunity (the initial HTTP connection) for an attacker
# to downgrade or redirect the request.
#
# The following header ensures that browser will ONLY connect to your
# server via HTTPS, regardless of what the users type in the browser's
# address bar.
#
# (!) Remove the `includeSubDomains` optional directive if the website's
# subdomains are not using HTTPS.
#
# http://www.html5rocks.com/en/tutorials/security/transport-layer-security/
# https://tools.ietf.org/html/draft-ietf-websec-strict-transport-sec-14#section-6.1
# http://blogs.msdn.com/b/ieinternals/archive/2014/08/18/hsts-strict-transport-security-
attacks-mitigations-deployment-https.aspx

# <IfModule mod_headers.c>
#     Header always set Strict-Transport-Security "max-age=16070400; includeSubDomains"
# </IfModule>

# -----
# | Reducing MIME type security risks |
# -----

# Prevent some browsers from MIME-sniffing the response.
#
# This reduces exposure to drive-by download attacks and cross-origin
# data leaks, and should be left uncommented, especially if the server
# is serving user-uploaded content or content that could potentially be
# treated as executable by the browser.
#
# http://www.slideshare.net/hasegawayosuke/owasp-hasegawa
# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-v-comprehensive-
protection.aspx
# https://msdn.microsoft.com/en-us/library/ie/gg622941.aspx
# https://mimesniff.spec.whatwg.org/

<IfModule mod_headers.c>
    Header set X-Content-Type-Options "nosniff"
```


</IfModule>

```
# -----  
# | Reflected Cross-Site Scripting (XSS) attacks |  
# -----  
  
# (1) Try to re-enable the cross-site scripting (XSS) filter built  
# into most web browsers.  
#  
# The filter is usually enabled by default, but in some cases it  
# may be disabled by the user. However, in Internet Explorer for  
# example, it can be re-enabled just by sending the  
# `X-XSS-Protection` header with the value of `1`.  
#  
# (2) Prevent web browsers from rendering the web page if a potential  
# reflected (a.k. a non-persistent) XSS attack is detected by the  
# filter.  
#  
# By default, if the filter is enabled and browsers detect a  
# reflected XSS attack, they will attempt to block the attack  
# by making the smallest possible modifications to the returned  
# web page.  
#  
# Unfortunately, in some browsers (e.g.: Internet Explorer),  
# this default behavior may allow the XSS filter to be exploited,  
# thereby, it's better to inform browsers to prevent the rendering  
# of the page altogether, instead of attempting to modify it.  
#  
# https://hackademix.net/2009/11/21/ies-xss-filter-creates-xss-vulnerabilities  
#  
# (!) Do not rely on the XSS filter to prevent XSS attacks! Ensure that  
# you are taking all possible measures to prevent XSS attacks, the  
# most obvious being: validating and sanitizing your website's inputs.  
#  
# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-iv-the-xss-filter.aspx  
# http://blogs.msdn.com/b/ieinternals/archive/2011/01/31/controlling-the-internet-explorer-xss-filter-with-the-x-xss-protection-http-header.aspx  
# https://www.owasp.org/index.php/Cross-site\_Scripting\_%28XSS%29  
  
# <IfModule mod_headers.c>
```

```

# # (1) (2)
# Header set X-XSS-Protection "1; mode=block"

# # `mod_headers` cannot match based on the content-type, however,
# # the `X-XSS-Protection` response header should be send only for
# # HTML documents and not for the other resources.

# <FilesMatch "\.
(appache|atom|bbaw|bml|crl|css|curl|eot|f4[abpv]|flv|geo.json|gif|htc|ico|jpe?
|js|json(1d)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssl|safari-extend|svgz?
|swf|topo.json|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|woff2?|x1o|xll|xpi)$">
# Header unset X-XSS-Protection
# </FilesMatch>

# </IfModule>

# -----
# | Server-side technology information |
# -----

# Remove the `X-Powered-By` response header that:
#
# * is set by some frameworks and server-side languages
# (e.g.: ASP.NET, PHP), and its value contains information
# about them (e.g.: their name, version number)
#
# * doesn't provide any value as far as users are concern,
# and in some cases, the information provided by it can
# be used by attackers
#
# (!) If you can, you should disable the `X-Powered-By` header from the
# language / framework level (e.g.: for PHP, you can do that by setting
# `expose_php = off` in `php.ini`)
#
# https://php.net/manual/en/ini.core.php#ini.expose-php

<IfModule mod_headers.c>
    Header unset X-Powered-By
</IfModule>

```

```
# -----  
# | Server software information |  
# -----
```

```
# Prevent Apache from adding a trailing footer line containing  
# information about the server to the server-generated documents  
# (e.g.: error messages, directory listings, etc.)  
#  
# https://httpd.apache.org/docs/current/mod/core.html#serversignature
```

ServerSignature Off

```
# -----  
  
# Prevent Apache from sending in the `Server` response header its  
# exact version number, the description of the generic OS-type or  
# information about its compiled-in modules.  
#  
# (!) The `ServerTokens` directive will only work in the main server  
# configuration file, so don't try to enable it in the `.htaccess` file!  
#  
# https://httpd.apache.org/docs/current/mod/core.html#servertokens
```

#ServerTokens Prod

```
# #####  
# # WEB PERFORMANCE #  
# #####
```

```
# -----  
# | Compression |  
# -----
```

<IfModule mod_deflate.c>

```
# Force compression for mangled `Accept-Encoding` request headers  
# https://developer.yahoo.com/blogs/ymn/pushing-beyond-gzipping-25601.html
```

<IfModule mod_setenvif.c>

<IfModule mod_headers.c>

[SetEnvIfNoCase ^\(\s|\.|@|\\\$|:|_|\/|\" data-bbox="171 953 846 966">SetEnvIfNoCase ^\(\s|\.|@|\\\$|:|_|\/|\"](#)

```

        SetEnvIfNoCase ^(\Accept-encoding|X-cept-encoding|X-15|15|15-15)$
^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
        RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
</IfModule>

# -----

# Compress all output labeled with one of the following media types.
#
# (!) For Apache versions below version 2.3.7 you don't need to
# enable `mod_filter` and can remove the `<IfModule mod_filter.c>`
# and `</IfModule>` lines as `AddOutputFilterByType` is still in
# the core directives.
#
# https://httpd.apache.org/docs/current/mod/mod_filter.html#addoutputfilterbytype

<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE "application/atom+xml" \
        "application/javascript" \
        "application/json" \
        "application/ld+json" \
        "application/manifest+json" \
        "application/rdf+xml" \
        "application/rss+xml" \
        "application/schema+json" \
        "application/vnd.geo+json" \
        "application/vnd.ms-fontobject" \
        "application/x-font-ttf" \
        "application/x-javascript" \
        "application/x-web-app-manifest+json" \
        "application/xhtml+xml" \
        "application/xml" \
        "font/eot" \
        "font/opentype" \
        "image/bmp" \
        "image/svg+xml" \
        "image/vnd.microsoft.icon" \
        "image/x-icon" \
        "text/cache-manifest" \
        "text/css" \
        ..

```

```
"text/html" \  
"text/javascript" \  
"text/plain" \  
"text/vcard" \  
"text/vnd.rim.location.xloc" \  
"text/vtt" \  
"text/x-component" \  
"text/x-cross-domain-policy" \  
"text/xml"
```

```
</IfModule>
```

```
# -----
```

```
# Map the following filename extensions to the specified  
# encoding type in order to make Apache serve the file types  
# with the appropriate `Content-Encoding` response header  
# (do note that this will NOT make Apache compress them!).  
#  
# If these files types would be served without an appropriate  
# `Content-Enable` response header, client applications (e.g.:  
# browsers) wouldn't know that they first need to uncompress  
# the response, and thus, wouldn't be able to understand the  
# content.  
#  
# https://httpd.apache.org/docs/current/mod/mod\_mime.html#addencoding
```

```
<IfModule mod_mime.c>
```

```
    AddEncoding gzip          svgz
```

```
</IfModule>
```

```
</IfModule>
```

```
# -----  
# | Content transformation |  
# -----
```

```
# Prevent intermediate caches or proxies (e.g.: such as the ones  
# used by mobile network providers) from modifying the website's  
# content.  
#
```

```
# https://tools.ietf.org/html/rfc2616#section-14.9.5
#
# (!) If you are using `mod_pagespeed`, please note that setting
# the `Cache-Control: no-transform` response header will prevent
# `PageSpeed` from rewriting `HTML` files, and, if the
# `ModPagespeedDisableRewriteOnNoTransform` directive isn't set
# to `off`, also from rewriting other resources.
#
# https://developers.google.com/speed/pagespeed/module/configuration#notransform
```

```
# <IfModule mod_headers.c>
#     Header merge Cache-Control "no-transform"
# </IfModule>
```

```
# -----
# | ETags |
# -----
```

```
# Remove `ETags` as resources are sent with far-future expires headers.
#
# https://developer.yahoo.com/performance/rules.html#etags
# https://tools.ietf.org/html/rfc7232#section-2.3
```

```
# `FileETag None` doesn't work in all cases.
```

```
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
```

FileETag None

```
# -----
# | Expires headers |
# -----
```

```
# Serve resources with far-future expires headers.
#
# (!) If you don't control versioning with filename-based
# cache busting, you should consider lowering the cache times
# to something like one week.
#
# https://httpd.apache.org/docs/current/mod/mod\_expires.html
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
ExpiresByType text/css "access plus 1 year"
```

```
# Data interchange
```

```
ExpiresByType application/atom+xml "access plus 1 hour"
```

```
ExpiresByType application/rdf+xml "access plus 1 hour"
```

```
ExpiresByType application/rss+xml "access plus 1 hour"
```

```
ExpiresByType application/json "access plus 0 seconds"
```

```
ExpiresByType application/ld+json "access plus 0 seconds"
```

```
ExpiresByType application/schema+json "access plus 0 seconds"
```

```
ExpiresByType application/vnd.geo+json "access plus 0 seconds"
```

```
ExpiresByType application/xml "access plus 0 seconds"
```

```
ExpiresByType text/xml "access plus 0 seconds"
```

```
# Favicon (cannot be renamed!) and cursor images
```

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

```
# HTML
```

```
ExpiresByType text/html "access plus 0 seconds"
```

```
# JavaScript
```

```
ExpiresByType application/javascript "access plus 1 year"
```

```
ExpiresByType application/x-javascript "access plus 1 year"
```

```
ExpiresByType text/javascript "access plus 1 year"
```

```
# Manifest files
```

```
ExpiresByType application/manifest+json "access plus 1 year"
```

```
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
```

```
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

```
# Media files
```

```
ExpiresByType audio/ogg "access plus 1 month"
```

```
ExpiresByType image/bmp "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType image/webp "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

Web fonts

Embedded OpenType (EOT)

```
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType font/eot "access plus 1 month"
```

OpenType

```
ExpiresByType font/opentype "access plus 1 month"
```

TrueType

```
ExpiresByType application/x-font-ttf "access plus 1 month"
```

Web Open Font Format (WOFF) 1.0

```
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType font/woff "access plus 1 month"
```

Web Open Font Format (WOFF) 2.0

```
ExpiresByType application/font-woff2 "access plus 1 month"
```

Other

```
ExpiresByType text/x-cross-domain-policy "access plus 1 week"
```

</IfModule>

```
# -----
# | File concatenation |
# -----
```

Allow concatenation from within specific files.

#


```
# e.g.:
#
# If you have the following lines in a file called, for
# example, `main.combined.js`:
#
#     <!--#include file="js/jquery.js" -->
#     <!--#include file="js/jquery.timer.js" -->
#
# Apache will replace those lines with the content of the
# specified files.

# <IfModule mod_include.c>
#     <FilesMatch "\.combined\.js$">
#         Options +Includes
#         AddOutputFilterByType INCLUDES application/javascript \
#             application/x-javascript \
#             text/javascript
#         SetOutputFilter INCLUDES
#     </FilesMatch>
#     <FilesMatch "\.combined\.css$">
#         Options +Includes
#         AddOutputFilterByType INCLUDES text/css
#         SetOutputFilter INCLUDES
#     </FilesMatch>
# </IfModule>

# -----
# | Filename-based cache busting |
# -----

# If you're not using a build process to manage your filename version
# revving, you might want to consider enabling the following directives
# to route all requests such as `/style.12345.css` to `/style.css`.
#
# To understand why this is important and even a better solution than
# using something like `*.css?v231`, please see:
# http://www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# <IfModule mod_rewrite.c>
#     RewriteEngine On
#     RewriteCond %{REQUEST_FILENAME} !-f
```

```
# RewriteRule ^(.+)\.(\d+)\.(bmp|css|curl|gif|ico|jpe?g|js|png|svgz?|webp)$ $1.$3 [L]
# </IfModule>
```