

```
# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
</IfModule>

# END WordPress
#Charset
AddCharset utf-8 .html .css .php
AddType application/rss+xml; charset=utf-8 .rss

#DIR index
DirectoryIndex index.php

# Redirect www urls to non-www
RewriteEngine on
RewriteCond %{HTTP_HOST} !^YOURDOMAIN\.COM
RewriteRule (.*) http://YOURDOMAIN.COM/$1 [R=301,L]

# Block the include-only files.
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteRule ^wp-admin/includes/ - [F,L]
RewriteRule !^wp-includes/ - [S=3]
RewriteRule ^wp-includes/[^/]+\.php$ - [F,L]
RewriteRule ^wp-includes/js/tinymce/langs/.+\.php - [F,L]
RewriteRule ^wp-includes/theme-compat/ - [F,L]
</IfModule>

##To protect against script injections and attempts to modify PHP's global and request vari.
<IfModule mod_rewrite.c>
  RewriteCond %{QUERY_STRING} (<|>|&gt;|&lt;) .*script.*(<|>|&gt;) [NC,OR]
  RewriteCond %{QUERY_STRING} GLOBALS(=|\[|\]|\%[0-9A-Z]{0,2}) [OR]
  RewriteCond %{QUERY_STRING} _REQUEST(=|\[|\]|\%[0-9A-Z]{0,2})
  RewriteRule .* index.php [F,L]
</IfModule>
```

```
</IMODULE>

# Securing any HTACCESS file
<files ".^.*\.(Hh)(Tt)(Aa)">
order allow,deny
deny from all
satisfy all
</files>

# Deny Access to WPconfig
<files wp-config.php>
order allow,deny
deny from all
</files>

# Deny Access to XMLRPC
<Files xmlrpc.php>
    Order Allow,Deny
    Deny from all
</Files>

## deny directory browsing
Options All -Indexes

## deny folder listing
IndexIgnore *

## prevent mime based attacks
Header set X-Content-Type-Options "nosniff"
## Don't allow any pages to be framed - Defends against CSRF - CLICKJACKING
Header set X-Frame-Options DENY

RewriteBase /
# Against Nasty site rippers/bots/etc
# useragents starting with
RewriteCond %{HTTP_USER_AGENT} ^atraxbot [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^Azureus [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^geohasher [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^PyCURL [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^Python-urllib [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^research-scan-bot [NC,OR]
- - - - -
```

```
RewriteCond %{HTTP_USER_AGENT} ^Sosospider [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^Wget [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^xenu [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^.*casper [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^.*goblox [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ^.*sun4u [NC]
RewriteCond %{HTTP_USER_AGENT} BlackWidow [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Bot\ mailto: craftbot@yahoo.com [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ChinaClaw [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Custo [NC,OR]
RewriteCond %{HTTP_USER_AGENT} DISCo [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Download\ Demon [NC,OR]
RewriteCond %{HTTP_USER_AGENT} EirGrabber [NC,OR]
RewriteCond %{HTTP_USER_AGENT} EmailSiphon [NC,OR]
RewriteCond %{HTTP_USER_AGENT} EmailWolf [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Express\ WebPictures [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ExtractorPro [NC,OR]
RewriteCond %{HTTP_USER_AGENT} EyeNetIE [NC,OR]
RewriteCond %{HTTP_USER_AGENT} FlashGet [NC,OR]
RewriteCond %{HTTP_USER_AGENT} GetRight [NC,OR]
RewriteCond %{HTTP_USER_AGENT} GetWeb! [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Go! Zilla [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Go-Ahead-Got-It [NC,OR]
RewriteCond %{HTTP_USER_AGENT} GrabNet [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Grafula [NC,OR]
RewriteCond %{HTTP_USER_AGENT} HMView [NC,OR]
RewriteCond %{HTTP_USER_AGENT} HTTrack [NC,OR]
RewriteCond %{HTTP_USER_AGENT} HTTrack [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Image\ Stripper [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Image\ Sucker [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Indy\ Library [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Indy\ Library [NC,OR]
RewriteCond %{HTTP_USER_AGENT} InterGET [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Internet\ Ninja [NC,OR]
RewriteCond %{HTTP_USER_AGENT} JOC\ Web\ Spider [NC,OR]
RewriteCond %{HTTP_USER_AGENT} JetCar [NC,OR]
RewriteCond %{HTTP_USER_AGENT} LeechFTP [NC,OR]
RewriteCond %{HTTP_USER_AGENT} MIDown\ tool [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Mass\ Downloader [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Mister\ PiX [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Navroad [NC,OR]
```

```
RewriteCond %{HTTP_USER_AGENT} NearSite [NC,OR]
RewriteCond %{HTTP_USER_AGENT} NetAnts [NC,OR]
RewriteCond %{HTTP_USER_AGENT} NetSpider [NC,OR]
RewriteCond %{HTTP_USER_AGENT} NetZIP [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Net\ Vampire [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Octopus [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Offline\ Explorer [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Offline\ Navigator [NC,OR]
RewriteCond %{HTTP_USER_AGENT} PageGrabber [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Papa\ Foto [NC,OR]
RewriteCond %{HTTP_USER_AGENT} ReGet [NC,OR]
RewriteCond %{HTTP_USER_AGENT} RealDownload [NC,OR]
RewriteCond %{HTTP_USER_AGENT} SiteSnagger [NC,OR]
RewriteCond %{HTTP_USER_AGENT} SmartDownload [NC,OR]
RewriteCond %{HTTP_USER_AGENT} SuperBot [NC,OR]
RewriteCond %{HTTP_USER_AGENT} SuperHTTP [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Surfbot [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Teleport\ Pro [NC,OR]
RewriteCond %{HTTP_USER_AGENT} TurnitinBot [NC,OR]
RewriteCond %{HTTP_USER_AGENT} VoidEYE [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WWWOFFLE [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebAuto [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebCopier [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebFetch [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebGo\ IS [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebLeacher [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebReaper [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebSauger [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebStripper [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebWhacker [NC,OR]
RewriteCond %{HTTP_USER_AGENT} WebZIP [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Web\ Image\ Collector [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Web\ Sucker [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Website\ Quester [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Website\ eXtractor [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Widow [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Xaldon\ WebSpider [NC,OR]
RewriteCond %{HTTP_USER_AGENT} Zeus [NC,OR]
RewriteCond %{HTTP_USER_AGENT} archiverloader [NC,OR]
RewriteCond %{HTTP_USER_AGENT} casper [NC,OR]
RewriteCond %{HTTP_USER_AGENT} clshttp [NC,OR]
```

```

RewriteCond %{HTTP_USER_AGENT} cmsworldmap [NC,OR]
RewriteCond %{HTTP_USER_AGENT} curl [NC,OR]
RewriteCond %{HTTP_USER_AGENT} diavol [NC,OR]
RewriteCond %{HTTP_USER_AGENT} dotbot [NC,OR]
RewriteCond %{HTTP_USER_AGENT} eCatch [NC,OR]
RewriteCond %{HTTP_USER_AGENT} email [NC,OR]
RewriteCond %{HTTP_USER_AGENT} extract [NC,OR]
RewriteCond %{HTTP_USER_AGENT} flicky [NC,OR]
RewriteCond %{HTTP_USER_AGENT} grab [NC,OR]
RewriteCond %{HTTP_USER_AGENT} harvest [NC,OR]
RewriteCond %{HTTP_USER_AGENT} jakarta [NC,OR]
RewriteCond %{HTTP_USER_AGENT} java [NC,OR]
RewriteCond %{HTTP_USER_AGENT} kmccrew [NC,OR]
RewriteCond %{HTTP_USER_AGENT} larbin [NC,OR]
RewriteCond %{HTTP_USER_AGENT} libwww [NC,OR]
RewriteCond %{HTTP_USER_AGENT} miner [NC,OR]
RewriteCond %{HTTP_USER_AGENT} nikto [NC,OR]
RewriteCond %{HTTP_USER_AGENT} pavuk [NC,OR]
RewriteCond %{HTTP_USER_AGENT} pcBrowser [NC,OR]
RewriteCond %{HTTP_USER_AGENT} planetwork [NC,OR]
RewriteCond %{HTTP_USER_AGENT} pycurl [NC,OR]
RewriteCond %{HTTP_USER_AGENT} python [NC,OR]
RewriteCond %{HTTP_USER_AGENT} scan [NC,OR]
RewriteCond %{HTTP_USER_AGENT} skygrid [NC,OR]
RewriteCond %{HTTP_USER_AGENT} tAkeOut [NC,OR]
RewriteCond %{HTTP_USER_AGENT} wget [NC,OR]
RewriteCond %{HTTP_USER_AGENT} winhttp [NC]
## Note: The final RewriteCond must NOT use the [OR] flag.
## Return 403 Forbidden error.
RewriteRule .* - [F]

## Disallow PHP Easter Eggs (can be used in fingerprinting attacks to determine
## your PHP version). See http://www.0php.com/php_easter_egg.php and
## http://osvdb.org/12184 for more information
RewriteCond %{QUERY_STRING} \=PHP[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}
RewriteRule .* - [F,L]

## Deny POST requests sent through proxies
RewriteCond %{REQUEST_URI} !^/(search|site-search|wp-login.php|wp-admin|wp-access|plugins|
RewriteCond %{REQUEST_METHOD} =POST
RewriteCond %{HTTP:VIA} %{HTTP:FORWARDED} %{HTTP:USERAGENT_VIA} %{HTTP:X_FORWARDED_FOR} %{HTTP:F

```

```

RewriteCond %{HTTP:XPROXY_CONNECTION} 0 %{HTTP:HTTP_PC_REMOTE_ADDR} %{HTTP:HTTP_CLIENT_IP} !^$ 
RewriteRule .* - [F,NS,L]

## Deny bogus graphic exploits
RewriteCond %{HTTP:Content-Disposition} \.php [NC]
RewriteCond %{HTTP:Content-Type} image/.+ [NC]
RewriteRule .* - [F,NS,L]

# Anti SQL injections, RFI, base64 etc etc
RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=http:// [OR]
RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=(\.\.\.//?)+ [OR]
RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=(/[a-zA-Z0-9_.]+//?)+ [NC,OR]
RewriteCond %{QUERY_STRING} \=PHP[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}
RewriteCond %{QUERY_STRING} (\.\.\./\.\.\.) [OR]
RewriteCond %{QUERY_STRING} ftp\:\: [NC,OR]
RewriteCond %{QUERY_STRING} http\:\: [NC,OR]
RewriteCond %{QUERY_STRING} https\:\: [NC,OR]
RewriteCond %{QUERY_STRING} \=\w\W [NC,OR]
RewriteCond %{QUERY_STRING} ^(.*)/self/(.*)$ [NC,OR]
RewriteCond %{QUERY_STRING} ^(.*)cPath=http://(.*)$ [NC,OR]
RewriteCond %{QUERY_STRING} (<|<%3C).+script.+(>|>%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|<%3C)([^s]*s)+cript.+(>|>%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|<%3C).+iframe.+(>|>%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|<%3C)([^i]*i)+frame.+(>|>%3E) [NC,OR]
RewriteCond %{QUERY_STRING} base64_encode.+(\.+\.) [NC,OR]
RewriteCond %{QUERY_STRING} base64_(enl de)code[^()]*\([^\)]*\) [NC,OR]
RewriteCond %{QUERY_STRING} GLOBALS(=|=|\.\.\.|\.|\.\.\.|\<|\>).+ [NC,OR]
RewriteCond %{QUERY_STRING} _REQUEST(=|=|\.\.\.|\.|\.\.\.|\<|\>).+ [NC,OR]
RewriteCond %{QUERY_STRING} ^.*(\|\|\|\|\|\|\|\<|\>).+ [NC,OR]
RewriteCond %{QUERY_STRING} (NULL|OUTFILE|LOAD_FILE) [OR]
RewriteCond %{QUERY_STRING} (\.\./\.\.\./\.\.\.)/+(mofd|etc|bin) [NC,OR]
RewriteCond %{QUERY_STRING} (localhost|loopback|127\.\.0\.\.1) [NC,OR]
RewriteCond %{QUERY_STRING} (<|>|\''%0A|\%0D|\%27|\%3C|\%3E|\%00) [NC,OR]
RewriteCond %{QUERY_STRING} concat[^\\]*\\ [NC,OR]
RewriteCond %{QUERY_STRING} union([^\s]*s)+elect [NC,OR]
RewriteCond %{QUERY_STRING} union([^\a]*a)+11([^\s]*s)+elect [NC,OR]
RewriteCond %{QUERY_STRING} (;|<|>|\''|\\"|\%0A|\%0D|\%22|\%27|\%3C|\%3E|\%00).+*
(/|\*|union|select|insert|drop|delete|update|cast|create|char|convert|alter|declare|order|scr
[NC,OR]
RewriteCond %{QUERY_STRING} (sp_executesql) [NC]
RewriteRule ^(.*)$ - [F,L]

```

```
# BEGIN Expire headers
<ifModule mod_expires.c>
    ExpiresActive On
    ExpiresDefault "access plus 5 seconds"
    ExpiresByType image/x-icon "access plus 2592000 seconds"
    ExpiresByType image/jpeg "access plus 2592000 seconds"
    ExpiresByType image/png "access plus 2592000 seconds"
    ExpiresByType image/gif "access plus 2592000 seconds"
    ExpiresByType application/x-shockwave-flash "access plus 2592000 seconds"
    ExpiresByType text/css "access plus 604800 seconds"
    ExpiresByType text/javascript "access plus 216000 seconds"
    ExpiresByType application/javascript "access plus 216000 seconds"
    ExpiresByType application/x-javascript "access plus 216000 seconds"
    ExpiresByType text/html "access plus 600 seconds"
    ExpiresByType application/xhtml+xml "access plus 600 seconds"
</ifModule>
# END Expire headers
```

```
# BEGIN Cache-Control Headers
<ifModule mod_headers.c>
    <filesMatch "\.(ico|jpe?g|png|gif|swf)$">
        Header set Cache-Control "public"
    </filesMatch>
    <filesMatch "\.(css)$">
        Header set Cache-Control "public"
    </filesMatch>
    <filesMatch "\.(js)$">
        Header set Cache-Control "private"
    </filesMatch>
    <filesMatch "\.(x?html?|php)$">
        Header set Cache-Control "private, must-revalidate"
    </filesMatch>
</ifModule>
# END Cache-Control Headers
```

```
<IfModule mod_deflate.c>
    AddOutputFilterByType DEFLATE application/javascript
    AddOutputFilterByType DEFLATE application/rss+xml
    AddOutputFilterByType DEFLATE application/vnd.ms-fontobject
    AddOutputFilterByType DEFLATE application/x-font
```

```
AddOutputFilterByType DEFLATE application/x-font-opentype
AddOutputFilterByType DEFLATE application/x-font-otf
AddOutputFilterByType DEFLATE application/x-font-truetype
AddOutputFilterByType DEFLATE application/x-font-ttf
AddOutputFilterByType DEFLATE application/x-javascript
AddOutputFilterByType DEFLATE application/xhtml+xml
AddOutputFilterByType DEFLATE application/xml
AddOutputFilterByType DEFLATE font/opentype
AddOutputFilterByType DEFLATE font/otf
AddOutputFilterByType DEFLATE font/ttf
AddOutputFilterByType DEFLATE image/svg+xml
AddOutputFilterByType DEFLATE image/x-icon
AddOutputFilterByType DEFLATE text/css
AddOutputFilterByType DEFLATE text/html
AddOutputFilterByType DEFLATE text/javascript
AddOutputFilterByType DEFLATE text/plain
</IfModule>
```

## **# GZIP ENABLED**

```
<ifModule mod_gzip.c>
mod_gzip_on Yes
mod_gzip_dechunk Yes
mod_gzip_item_include file .(html?|txt|css|js|php|pl)$
mod_gzip_item_include handler ^cgi-script$*
mod_gzip_item_include mime ^text/.*
mod_gzip_item_include mime ^application/x-javascript.**
mod_gzip_item_exclude mime ^image/.*
mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.**
</ifModule>
```