

```

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *ever!
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|oggl|m4al|ogvl|mp4l|m4vl|webml|svgl|svgz|eotl|ttfl|otfl|woffl|icol|webpl|appcache|manifest|
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    # mod_headers, y u no match by Content-Type?!
    <FilesMatch "\.(gif|png|jpe?gl|svgl|svgz|icol|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

<IfModule mod_headers.c>
  <FilesMatch "\.(ttf|ttcl|otf|eot|woff|font.css)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js

# Audio
AddType audio/ogg                    oga ogg
AddType audio/mp4                    m4a

# Video
AddType video/ogg                    ogv

```

```
AddType video/ogg                ogv
AddType video/mp4                 mp4 m4v
AddType video/webm                webm
```

```
# SVG
```

```
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml           svg svgz
AddEncoding gzip                 svgz
```

```
# Webfonts
```

```
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf         ttf ttc
AddType font/opentype                 otf
AddType application/x-font-woff        woff
```

```
# Assorted types
```

```
AddType image/x-icon              ico
AddType image/webp                 webp
AddType text/cache-manifest         appcache manifest
AddType text/x-component            htc
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall     xpi
AddType application/octet-stream    safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard                vcf
```

```
<IfModule mod_deflate.c>
```

```
# Force deflate for mangled headers developer.yahoo.com/blogs/ym/2010/12/pushing-bu
```

```
<IfModule mod_setenvif.c>
```

```
<IfModule mod_headers.c>
```

```
SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\
```

```
HAVE_Accept-Encoding
```

```
RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
```

```
</IfModule>
```

```
</IfModule>
```

```
# HTML, TXT, CSS, JavaScript, JSON, XML, HTC:
```

```
<IfModule filter_module>
```

```
FilterChain
```

```

FilterDeclare    COMPRESS
FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/html
FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/css
FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/plain
FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/xml
FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/x-component
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/javascript
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/json
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/xml
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/xhtml+xml
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/rss+xml
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/atom+xml
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/vnd.ms-fontobject
FilterProvider   COMPRESS DEFLATE resp=Content-Type $image/svg+xml
FilterProvider   COMPRESS DEFLATE resp=Content-Type $image/x-icon
FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/x-font-ttf
FilterProvider   COMPRESS DEFLATE resp=Content-Type $font/opentype
FilterChain      COMPRESS
FilterProtocol   COMPRESS DEFLATE change=yes;byteranges=no

```

```
</IfModule>
```

```
<IfModule !mod_filter.c>
```

```
# Legacy versions of Apache
```

```
AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
```

```
AddOutputFilterByType DEFLATE application/javascript
```

```
AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
```

```
AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml application/atom
```

```
AddOutputFilterByType DEFLATE image/x-icon image/svg+xml application/vnd.ms-fontobject :
```

```
font/opentype
```

```
</IfModule>
```

```
</IfModule>
```

```

# -----
# Expires headers (for better cache control)
# -----

```

```
# These are pretty far-future expires headers.
```

```
# They assume you control versioning with cachebusting query params like
```

```
# <script src="application.js?20100608">
```

```
# Additionally, consider that outdated proxies may miscache
```

```
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week" or so.

<IfModule mod_expires.c>
    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault                                     "access plus 1 month"

    # cache, apcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
    ExpiresByType text/cache-manifest                 "access plus 0 seconds"

    # Your document html
    ExpiresByType text/html                           "access plus 0 seconds"

    # Data
    ExpiresByType text/xml                             "access plus 0 seconds"
    ExpiresByType application/xml                     "access plus 0 seconds"
    ExpiresByType application/json                    "access plus 0 seconds"

    # Feed
    ExpiresByType application/rss+xml                 "access plus 1 hour"
    ExpiresByType application/atom+xml                "access plus 1 hour"

    # Favicon (cannot be renamed)
    ExpiresByType image/x-icon                        "access plus 1 week"

    # Media: images, video, audio
    ExpiresByType image/gif                           "access plus 1 month"
    ExpiresByType image/png                           "access plus 1 month"
    ExpiresByType image/jpg                           "access plus 1 month"
    ExpiresByType image/jpeg                         "access plus 1 month"
    ExpiresByType video/ogg                           "access plus 1 month"
    ExpiresByType audio/ogg                           "access plus 1 month"
    ExpiresByType video/mp4                           "access plus 1 month"
    ExpiresByType video/webm                          "access plus 1 month"

    # HTC files (css3pie)
    ExpiresByType text/x-component                    "access plus 1 month"
```

```
# Webfonts
ExpiresByType application/x-font-ttf      "access plus 1 month"
ExpiresByType font/opentype              "access plus 1 month"
ExpiresByType application/x-font-woff    "access plus 1 month"
ExpiresByType image/svg+xml              "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css                    "access plus 1 year"
ExpiresByType application/javascript      "access plus 1 year"

</IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above). If
# needed, un-comment the following rules.

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary
```

```
# -----  
# Cookie setting from iframes  
# -----  
  
# Allow cookies to be set from iframes (for IE only)  
# If needed, uncomment and specify a path or regex in the Location directive  
  
# <IfModule mod_headers.c>  
#   <Location />  
#     Header set P3P "policyref=\"/w3c/p3p.xml\"", CP="IDC DSP COR ADM DEVI TAIi PSA PSD IVA  
#   </Location>  
# </IfModule>  
  
# -----  
# Start rewrite engine  
# -----  
  
# Turning on the rewrite engine is necessary for the following rules and features.  
# FollowSymLinks must be enabled for this to work.  
  
<IfModule mod_rewrite.c>  
  Options +FollowSymLinks  
  RewriteEngine On  
</IfModule>  
  
# -----  
# Suppress or force the "www." at the beginning of URLs  
# -----  
  
# The same content should never be available under two different URLs - especially not with  
# without "www." at the beginning, since this can cause SEO problems (duplicate content).  
# That's why you should choose one of the alternatives and redirect the other one.  
  
# By default option 1 (no "www.") is activated. Remember: Shorter URLs are sexier.  
# no-www.org/faq.php?q=class_b  
  
# If you rather want to use option 2, just comment out all option 1 lines  
# and uncomment option 2.  
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!  
  
# -----
```

```
# Option 1:
# Rewrite "www.example.com -> example.com"

<IfModule mod_rewrite.c>
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2:
# To rewrite "example.com -> www.example.com" uncomment the following lines.
# Be aware that the following rule might not be a good idea if you
# use "real" subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\..+$ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----

# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version revving,
# you might want to consider enabling this, which will route requests for
# /css/style.20110203.css to /css/style.css

# To understand why this is important and a better idea than all.css?v1231,
# read: github.com/h5bp/html5-boilerplate/wiki/Version-Control-with-Cachebusting

# Uncomment to enable.
# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(.+)\.(.+)\.(js|css|png|jpg|gif)$ $1.$3 [L]
# </IfModule>
```

```
# -----  
# Prevent SSL cert warnings  
# -----  
  
# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent  
# https://www.example.com when your cert only allows https://secure.example.com  
# Uncomment the following lines to use this feature.  
  
# <IfModule mod_rewrite.c>  
#   RewriteCond %{SERVER_PORT} !^443  
#   RewriteRule ^ https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]  
# </IfModule>  
  
# -----  
# Prevent 404 errors for non-existing redirected folders  
# -----  
  
# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name do  
# e.g. /blog/hello : webmasterworld.com/apache/3808792.htm
```

## Options -MultiViews

```
# -----  
# Custom 404 page  
# -----  
  
# You can add custom pages to handle 500 or 403 pretty easily, if you like.  
ErrorDocument 404 /404.html  
  
# -----  
# UTF-8 encoding  
# -----  
  
# Use UTF-8 encoding for anything served text/plain or text/html  
AddDefaultCharset utf-8  
  
# Force UTF-8 for a number of file formats  
AddCharset utf-8 .css .js .xml .json .rss .atom  
  
# -----  
# A little more security
```



```
.. -----
# -----

# Do we want to advertise the exact version number of Apache we're running?
# Probably not.
## This can only be enabled if used in httpd.conf - It will not work in .htaccess
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a default document
# Usually you should leave this activated, because you shouldn't allow everybody to surf th
# every folder on your server (which includes rather private places like CMS system folders.
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories whose names begin with a period. This
# includes directories used by version control systems such as Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
</IfModule>

# Block access to backup and source files
# This files may be left by some text/html editors and
# pose a great security danger, when someone can access them
<FilesMatch "(\\. (bak|config|sql|fla|psd|ini|log|sh|incl|swp|dist)|")$" >
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS :
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
```

```
# Using a commercial web host, contact the administrator for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Rename session cookie to something else, than PHPSESSID
# php_value session.name sid

# Do not show you are using PHP
# Note: Move this line to php.ini since it won't work in .htaccess
# php_flag expose_php Off

# Level of log detail - log all errors
# php_value error_reporting -1

# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "
```

```
# php_value error_prepend_string
```

```
# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
```

```
# php_value error_append_string " "
```

```
# Increase cookie security
```

```
<IfModule php5_module>
```

```
    php_value session.cookie_httponly true
```

```
</IfModule>
```