

```
# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /flashpoint/
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /flashpoint/index.php [L]
</IfModule>

# END WordPress

# BEGIN HTML5 Boilerplate

###
### This contains the HTML5 Boilerplate .htaccess that can be found at:
### github.com/h5bp/html5-boilerplate/blob/master/.htaccess
###
### Added:
### Block access to access to WordPress files that reveal version information.
###
### Commented out by default:
### Expires headers:      Use WP Super Cache or W3 Total Cache (unless using the H5BP build)
### ETag removal:        Use WP Super Cache or W3 Total Cache (unless using the H5BP build)
### Start rewrite engine: Handled by WordPress
### Suppress/force www:   Handled by WordPress
### Options -MultiViews:  Causes a server 500 error on most shared hosts
### Custom 404 page:      Handled by WordPress
###
### Anytime you update this file the .htaccess file in the root of your
### WordPress install is automatically updated with the changes whenever
### the permalinks are flushed or set
###

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use Chrome Frame if it's installed for a better experience for the next IE fall
```

```

# use Unromerrame if it's installed for a better experience for the poor IC talk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *every*
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|oggl|m4al|ogvl|mp4l|m4vl|webml|svgl|svgz|eotl|ttfl|otfl|woffl|icol|webpl|appcachel|manifestl
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# CORS-enabled images (@crossorigin)
# -----

# Send CORS headers if browsers request them; enabled by default for images.
# developer.mozilla.org/en/CORS_Enabled_Image
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    # mod_headers, y u no match by Content-Type?!
    <FilesMatch "\.(gif|png|jpe?gl|svgl|svgz|icol|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>

```

```
</IfModule>
</IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

<IfModule mod_headers.c>
  <FilesMatch "\.(ttf|ttd|otf|eot|woff|font. css)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js jsonp
AddType application/json            json

# Audio
AddType audio/ogg                   oga ogg
AddType audio/mp4                   m4a f4a f4b

# Video
AddType video/ogg                   ogv
AddType video/mp4                   mp4 m4v f4v f4p
AddType video/webm                   webm
AddType video/x-flv                  flv

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml               svg svgz
```



```

#<FilesMatch "\.combined\.css$"
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
#</FilesMatch>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

    # Force deflate for mangled headers developer, yahoo.com/blogs/ymn/posts/2010/12/pushing-b
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\
HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # HTML, TXT, CSS, JavaScript, JSON, XML, HTC:
    <IfModule filter_module>
        FilterDeclare    COMPRESS
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/html
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/css
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/plain
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/xml
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/x-component
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/javascript
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/json
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/xml
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/xhtml+xml
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/rss+xml
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/atom+xml
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/vnd.ms-fontobject
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $image/svg+xml
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $image/x-icon
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/x-font-ttf
        FilterProvider   COMPRESS DEFLATE resp=Content-Type $font/opentype
        FilterChain      COMPRESS

```

```
    FilterProtocol COMPRESS DEFLATE change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
    # Legacy versions of Apache
    AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
    AddOutputFilterByType DEFLATE application/javascript
    AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
    AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml application/atom
    AddOutputFilterByType DEFLATE image/x-icon image/svg+xml application/vnd.ms-fontobject :
font/opentype
</IfModule>

</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/
# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week" or so.

# <IfModule mod_expires.c>
# ExpiresActive on

# Perhaps better to whitelist expires rules? Perhaps.
# ExpiresDefault "access plus 1 month"

# cache.appcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
# ExpiresByType text/cache-manifest "access plus 0 seconds"

# Your document html
# ExpiresByType text/html "access plus 0 seconds"

# Data
# ExpiresByType text/xml "access plus 0 seconds"
```

```
# ExpiresByType application/xml "access plus 0 seconds"
# ExpiresByType application/json "access plus 0 seconds"
```

Feed

```
# ExpiresByType application/rss+xml "access plus 1 hour"
# ExpiresByType application/atom+xml "access plus 1 hour"
```

Favicon (cannot be renamed)

```
# ExpiresByType image/x-icon "access plus 1 week"
```

Media: images, video, audio

```
# ExpiresByType image/gif "access plus 1 month"
# ExpiresByType image/png "access plus 1 month"
# ExpiresByType image/jpg "access plus 1 month"
# ExpiresByType image/jpeg "access plus 1 month"
# ExpiresByType video/ogg "access plus 1 month"
# ExpiresByType audio/ogg "access plus 1 month"
# ExpiresByType video/mp4 "access plus 1 month"
# ExpiresByType video/webm "access plus 1 month"
```

HTC files (css3pie)

```
# ExpiresByType text/x-component "access plus 1 month"
```

Webfonts

```
# ExpiresByType application/x-font-ttf "access plus 1 month"
# ExpiresByType font/opentype "access plus 1 month"
# ExpiresByType application/x-font-woff "access plus 1 month"
# ExpiresByType image/svg+xml "access plus 1 month"
# ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
```

CSS and JavaScript

```
# ExpiresByType text/css "access plus 1 year"
# ExpiresByType application/javascript "access plus 1 year"
```

```
# </IfModule>
```

```
# -----
# Prevent mobile network providers from modifying your site
# -----
```

The following header prevents modification of your code over 3G on some European provider:

```
# This is the official 'bypass' suggested by O2 in the UK

# <IfModule mod_headers.c>
# Header set Cache-Control "no-transform"
# </IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
# <IfModule mod_headers.c>
#   Header unset ETag
# </IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
#   developer.yahoo.com/performance/rules.html#etags
# FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above). If
# needed, un-comment the following rules.

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
# Set Keep-Alive Header
# -----

# Keep-Alive allows the server to send multiple requests through one TCP-connection.
# Be aware of possible disadvantages of this setting. Turn on if you serve a lot of
# static content.
```

```
# <IfModule mod_headers.c>
#   Header set Connection Keep-Alive
# </IfModule>

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, uncomment and specify a path or regex in the Location directive

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\"", CP="IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
# </IfModule>

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and features.
# FollowSymLinks must be enabled for this to work.
#
# Some cloud hosting services require RewriteBase to be set: goo.gl/H0cPM
# If using the h5bp in a subdirectory, use `RewriteBase /foo` instead where 'foo' is your d

# <IfModule mod_rewrite.c>
#   Options +FollowSymlinks
#   RewriteEngine On
# # RewriteBase /
# </IfModule>

# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs - especially not with
# without "www." at the beginning, since this can cause SEO problems (duplicate content).
# That's why you should choose one of the alternatives and redirect the other one.

# By default option 1 (no "www.") is activated. Remember: Shorter URLs are sexier.
# no-www.org/faq.php?noclass=1
```

```
# http://www.ietf.org/rfc/rfc2845.txt
```

```
# If you rather want to use option 2, just comment out all option 1 lines  
# and uncomment option 2.  
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!
```

```
# -----
```

```
# Option 1:  
# Rewrite "www.example.com -> example.com"
```

```
# <IfModule mod_rewrite.c>  
#   RewriteCond %{HTTPS} !=on  
#   RewriteCond %{HTTP_HOST} ^www/(.+$) [NC]  
#   RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]  
# </IfModule>
```

```
# -----
```

```
# Option 2:  
# To rewrite "example.com -> www.example.com" uncomment the following lines.  
# Be aware that the following rule might not be a good idea if you  
# use "real" subdomains for certain parts of your website.
```

```
# <IfModule mod_rewrite.c>  
#   RewriteCond %{HTTPS} !=on  
#   RewriteCond %{HTTP_HOST} !^www/\.+$ [NC]  
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]  
# </IfModule>
```

```
# -----
```

```
# Built-in filename-based cache busting
```

```
# -----
```

```
# If you're not using the build script to manage your filename version revving,  
# you might want to consider enabling this, which will route requests for  
# /css/style.20110203.css to /css/style.css
```

```
# To understand why this is important and a better idea than all.css?v1231,  
# read: github.com/h5bp/html5-boilerplate/wiki/cachebusting
```

```
# -----
```

```
# uncomment to enable.
# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(\.+)\/(\d+)\. (jst cssl pngl jpgl gif)$ $1. $3 [L]
# </IfModule>

# -----
# Prevent SSL cert warnings
# -----

# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.example.com when your cert only allows https://secure.example.com
# Uncomment the following lines to use this feature.

# <IfModule mod_rewrite.c>
#   RewriteCond %{SERVER_PORT} !^443
#   RewriteRule ^ https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Prevent 404 errors for non-existing redirected folders
# -----

# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name does
# e.g. /blog/hello : webmasterworld.com/apache/3808792.htm

# Options -MultiViews

# -----
# Custom 404 page
# -----

# You can add custom pages to handle 500 or 403 pretty easily, if you like.
# If you are hosting your site in subdirectory, adjust this accordingly
# e.g. ErrorDocument 404 /subdir/404.html
# ErrorDocument 404 /404.html

# -----
# UTF-8 encoding
# -----
```

```
# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .css .js .xml .json .rss .atom

# -----
# A little more security
# -----

# Do we want to advertise the exact version number of Apache we're running?
# Probably not.
## This can only be enabled if used in httpd.conf - It will not work in .htaccess
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a default document
# Usually you should leave this activated, because you shouldn't allow everybody to surf thi
# every folder on your server (which includes rather private places like CMS system folders.
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a period. This
# includes directories used by version control systems such as Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
</IfModule>

# Block access to backup and source files
# This files may be left by some text/html editors and
# pose a great security danger, when someone can access them
<FilesMatch "(\\. (bak|config|sql|fla|psd|ini|log|sh|incl|swp|dist)|\\.*)">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# Block access to WordPress files that reveal version information.
```

```
<FilesMatch "^(wp-config\.php|readme\.html|license\.txt)">
  Order allow,deny
  Deny from all
  Satisfy All
</FilesMatch>
```

```
# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS :
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Rename session cookie to something else, than PHPSESSID
# php_value session.name sid

# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of )
# php_flag magic_quotes_gpc Off

# Do not show you are using PHP
# Note: Move this line to php.ini since it won't work in .htaccess
# php_flag expose_php Off

# Level of log detail - log all errors
# php_value error_reporting -1

# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off
```

```
# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

# END HTML5 Boilerplate
```