

```
# Apache configuration file
# httpd.apache.org/docs/2.2/mod/quickreference.html

# Note .htaccess files are an overhead, this logic should be in your Apache
# config if possible: httpd.apache.org/docs/2.2/howto/htaccess.html

# Techniques in here adapted from all over, including:
#   Kroc Camen: camendesign.com/.htaccess
#   perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
#   Sample .htaccess file of CMS MODx: modx.com

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *ever!
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|oggl|m4al|ogvl|mp4l|m4vl|webml|svgl|svgz|eotl|ttfl|otfl|woff|icol|webpl|appcache|manifest|
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>
```

```

# -----
# CORS-enabled images (@crossorigin)
# -----

# Send CORS headers if browsers request them; enabled by default for images,
# developer.mozilla.org/en/CORS_Enabled_Image
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    # mod_headers, y u no match by Content-Type?!
    <FilesMatch "\.(gif|png|jpe?g|svg|svgz|ico|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts,
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

<IfModule mod_headers.c>
  <FilesMatch "\.(ttf|ttc|otf|eot|woff|font.css)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# "application/javascript" vs "text/javascript"

```

*# tools.ietf.org/html/rfc4329#section-7.2*

AddType application/javascript js jsonp  
AddType application/json json

*# Audio*

AddType audio/ogg oga ogg  
AddType audio/mp4 m4a f4a f4b

*# Video*

AddType video/ogg ogv  
AddType video/mp4 mp4 m4v f4v f4p  
AddType video/webm webm  
AddType video/x-flv flv

*# SVG*

*# Required for svg webfonts on iPad*

*# twitter.com/FontSquirrel/status/14855840545*

AddType image/svg+xml svg svgz  
AddEncoding gzip svgz

*# Webfonts*

AddType application/vnd.ms-fontobject eot  
AddType application/x-font-ttf ttf ttc  
AddType font/opentype otf  
AddType application/x-font-woff woff

*# Assorted types*

AddType image/x-icon ico  
AddType image/webp webp  
AddType text/cache-manifest appcache manifest  
AddType text/x-component htc  
AddType application/xml rss atom xml rdf  
AddType application/x-chrome-extension crx  
AddType application/x-opera-extension oex  
AddType application/x-xpinstall xpi  
AddType application/octet-stream safariextz  
AddType application/x-web-app-manifest+json webapp  
AddType text/x-vcard vcf  
AddType application/x-shockwave-flash swf  
AddType text/vtt vtt

```

# -----
# Allow concatenation from within specific js and css files
# -----

# e. g. Inside of script.combined.js you could have
# <!--#include file="libs/jquery-1.5.0.min.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# This is not in use in the boilerplate as it stands. You may
# choose to use this technique if you do not have a build process.

<FilesMatch "\.combined\.js$" >
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
</FilesMatch>

<FilesMatch "\.combined\.css$" >
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
</FilesMatch>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

# Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-bi
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$ ^((gzip|deflate)\
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
<IfModule mod_filter.c>

```

```

AddOutputFilterByType DEFLATE application/atom+xml \
                        application/javascript \
                        application/json \
                        application/rss+xml \
                        application/vnd.ms-fontobject \
                        application/x-font-ttf \
                        application/xhtml+xml \
                        application/xml \
                        font/opentype \
                        image/svg+xml \
                        image/x-icon \
                        text/css \
                        text/html \
                        text/plain \
                        text/x-component \
                        text/xml

</IfModule>

</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week".

<IfModule mod_expires.c>
    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault          "access plus 1 month"

    # cache, apcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
    ExpiresByType text/cache-manifest "access plus 0 seconds"

```

```
# Your document html
ExpiresByType text/html "access plus 0 seconds"

# Data
ExpiresByType text/xml "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"

# Feed
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 week"

# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"
```

```
</IfModule>
```

```
# -----
```

```
# Prevent mobile network providers from modifying your site
# -----

# The following header prevents modification of your code over 3G on some
# European providers.
# This is the official 'bypass' suggested by O2 in the UK.

# <IfModule mod_headers.c>
# Header set Cache-Control "no-transform"
# </IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above).

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
# Set Keep-Alive Header
# -----
```

```
# Keep-Alive allows the server to send multiple requests through one
# TCP-connection. Be aware of possible disadvantages of this setting. Turn on
# if you serve a lot of static content.

# <IfModule mod_headers.c>
#   Header set Connection Keep-Alive
# </IfModule>

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, specify a path or regex in the Location directive.

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\"", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
# </IfModule>

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and
# features. FollowSymLinks must be enabled for this to work.

# Some cloud hosting services require RewriteBase to be set: goo.gl/H0cPN
# If using the h5bp in a subdirectory, use `RewriteBase /foo` instead where
# 'foo' is your directory.

# If your web host doesn't allow the FollowSymLinks option, you may need to
# comment it out and use `Options +SymLinksIfOwnerMatch`, but be aware of the
# performance impact: http://goo.gl/Mluzd

<IfModule mod_rewrite.c>
    Options +FollowSymLinks
# Options +SymLinksIfOwnerMatch
    RewriteEngine On
# RewriteBase /
</IfModule>
```



```
# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs -
# especially not with and without "www." at the beginning, since this can cause
# SEO problems (duplicate content). That's why you should choose one of the
# alternatives and redirect the other one.

# By default option 1 (no "www.") is activated.
# no-www.org/faq.php?q=class_b

# If you'd prefer to use option 2, just comment out all option 1 lines
# and uncomment option 2.

# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----

# Option 1:
# Rewrite "www.example.com -> example.com".

<IfModule mod_rewrite.c>
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2:
# Rewrite "example.com -> www.example.com".
# Be aware that the following rule might not be a good idea if you use "real"
# subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\..+$ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>
```

```
# -----
# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version rewving,
# you might want to consider enabling this, which will route requests for
# /css/style.20110203.css to /css/style.css

# To understand why this is important and a better idea than all.css?v1231,
# read: github.com/h5bp/html5-boilerplate/wiki/cachebusting

# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1.$3 [L]
# </IfModule>

# -----
# Prevent SSL cert warnings
# -----

# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.example.com when your cert only allows https://secure.example.com

# <IfModule mod_rewrite.c>
#   RewriteCond %{SERVER_PORT} !^443
#   RewriteRule ^https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Prevent 404 errors for non-existing redirected folders
# -----

# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the
# same name does not exist.
# webmasterworld.com/apache/3808792.htm
```

## Options -MultiViews

```
# -----
# Option 404 ----
```

```
# Custom 404 page
# -----

# You can add custom pages to handle 500 or 403 pretty easily, if you like.
# If you are hosting your site in subdirectory, adjust this accordingly
#   e.g. ErrorDocument 404 /subdir/404.html
ErrorDocument 404 /404.html

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml

# -----
# A little more security
# -----

# To avoid displaying the exact version number of Apache being used, add the
# following to httpd.conf (it will not work in .htaccess):
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a
# default document. Usually you should leave this activated, because you
# shouldn't allow everybody to surf through every folder on your server (which
# includes rather private places like CMS system folders).
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a
# period. This includes directories used by version control systems such as
# Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
```

```
</IfModule>
```

```
# Block access to backup and source files. These files may be left by some  
# text/html editors and pose a great security danger, when anyone can access  
# them.
```

```
<FilesMatch "(\\. (bak| config| sql| fl| psd| ini| log| sh| incl| swp| dist)| \"\")$" >
```

```
    Order allow,deny
```

```
    Deny from all
```

```
    Satisfy All
```

```
</FilesMatch>
```

```
# If your server is not already configured as such, the following directive  
# should be uncommented in order to set PHP's register_globals option to OFF.  
# This closes a major security hole that is abused by most XSS (cross-site  
# scripting) attacks. For more information: http://php.net/register\_globals  
#
```

```
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS:
```

```
#
```

```
# Your server does not allow PHP directives to be set via .htaccess. In that  
# case you must make this change in your php.ini file instead. If you are  
# using a commercial web host, contact the administrators for assistance in  
# doing this. Not all servers allow local php.ini files, and they should  
# include all PHP configurations (not just this one), or you will effectively  
# reset everything to PHP defaults. Consult www.php.net for more detailed  
# information about setting PHP directives.
```

```
# php_flag register_globals Off
```

```
# Rename session cookie to something else, than PHPSESSID
```

```
# php_value session.name sid
```

```
# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of )
```

```
# php_flag magic_quotes_gpc Off
```

```
# Do not show you are using PHP
```

```
# Note: Move this line to php.ini since it won't work in .htaccess
```

```
# php_flag expose_php Off
```

```
# Level of log detail - log all errors
```

```
# php_value error_reporting -1
```

```
# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

RewriteEngine On
RewriteCond %{QUERY_STRING} (.*)|(http|https|ftp):/(.*)
RewriteRule ^(.+)$ - [F,L]

RewriteRule ^home$ index.php?act=home_/index

RewriteRule ^products$ index.php?act=products_/index
RewriteRule ^products-view/(.*)/(.*)/(.*)/(.*)$ index.php?act=products_/index&cat=$1&t
```

```

RewriteRule ^products-detail/(.+)/(.+)/(.*)$ index.php?act=products_/details&cat=$1&
RewriteRule ^products-detail/(.+)/(.*)$ index.php?act=products_/details&cat=$1&
RewriteRule ^download-specification/(.)*$ index.php?act=static/download&filename=

RewriteRule ^color-cards$ index.php?act=color-cards_/index
RewriteRule ^color-cards-detail/(.+)/(.*)$ index.php?act=color-cards_/details&ci

RewriteRule ^color-woods$ index.php?act=color-woods_/index
RewriteRule ^color-woods-detail/(.+)/(.*)$ index.php?act=color-woods_/details&ci

RewriteRule ^projects$ index.php?act=projects_/index
RewriteRule ^projects-view/(.+)/(.*)$ index.php?act=projects_/index&cid=$1&

# --- NEWS --- #
RewriteRule ^news-events$ index.php?act=news-events_/index
RewriteRule ^news-events-view/(.+)/(.+)/(.*)$ index.php?act=news-events_/index&nid=$

RewriteRule ^news-events-detail/(.+)/(.+)/(.*)$ index.php?act=news-events_/details&n

#RewriteRule ^item$ index.php?act=shop_/details

# PATTERN : item/[category name]/[product name]/[type name]
RewriteRule ^item/(.+)/(.+)/(.*)$ index.php?act=shop_/details&prod_cat=$

# RewriteRule ^shop-view/(.)*-(.+)/(.*)$ index.php?act=(shop)/index&shop_cat=$1&shop
# RewriteRule ^item/(.)*-type-(.)*$ index.php?act=(shop)/details&shop_detail_a
# RewriteRule ^shop-search/name-(.)*$ index.php?act=(shop)/index&src_name=$1
# RewriteRule ^add-to-bag$ index.php?act=(shop)/add_to_bag

# --- BLOG --- #
RewriteRule ^blog$ index.php?act=blog_/index
RewriteRule ^blog-view/(.+)/(.*)$ index.php?act=blog_/index&cat_news=$1&cat_r
RewriteRule ^read$ index.php?act=blog_/details
# RewriteRule ^blog-cat/(.+)/(.*)$ index.php?act=blog_/index&category=$1&reco
# RewriteRule ^blog-arc/(.+)/(.*)$ index.php?act=blog_/index&date=$1&record=$
# RewriteRule ^blog-view/(.+)/(.+)/(.*)$ index.php?act=blog_/index&category=$1&date:
# RewriteRule ^read/(.)*$ index.php?act=blog/details&nt=$1

RewriteRule ^ajax-add$ index.php?act=shop_/ajax_add_bag

# --- ORDER --- #

```

```

RewriteRule ^bag$ index.php?act=order_/bag
RewriteRule ^order-login$ index.php?act=order_/order-login
RewriteRule ^checkout$ index.php?act=order_/checkout
RewriteRule ^finish$ index.php?act=order_/finish

# --- ACCOUNT --- #
RewriteRule ^account/(.*)$ index.php?act=account_/index&aid=$1
RewriteRule ^confirm$ index.php?act=confirm_/index
RewriteRule ^order-history$ index.php?act=account_/order
Rewriterule ^order-detail/(.*)$ index.php?act=account_/orderdetails&oid=$1
RewriteRule ^shipping-details$ index.php?act=account_/shippingdetails
RewriteRule ^account-details$ index.php?act=account_/accountdetails

RewriteRule ^login$ index.php?act=account_/login
RewriteRule ^logout$ logout.php

#RewriteRule ^account$ index.php?act=account_/index
#Rewriterule ^order-detail$ index.php?act=account_/orderdetails

# --- PAGES --- #
RewriteRule ^history$ index.php?act=pages/about
RewriteRule ^vision-mission$ index.php?act=pages/about
RewriteRule ^quality-policy$ index.php?act=pages/about
RewriteRule ^activities$ index.php?act=pages/about
RewriteRule ^where-to-buy$ index.php?act=pages/where_to_buy
RewriteRule ^where-to-buy-view/(.*)/(.*)/(.*)$ index.php?act=pages/where_to_buy&dept_id=$1
RewriteRule ^faq$ index.php?act=pages/faq
RewriteRule ^contact-us$ index.php?act=pages/contact
RewriteRule ^career$ index.php?act=pages/careers
RewriteRule ^career-view/(.*)/(.*)$ index.php?act=pages/careers&dept_id=$1&dept
RewriteRule ^service-center$ index.php?act=pages/service_center
RewriteRule ^service-center-view/(.*)/(.*)$ index.php?act=pages/service_center&dept_id=
RewriteRule ^search-(.*)$ index.php?act=pages/search&srcval=$1
RewriteRule ^product-search-(.*)$ index.php?act=pages/src_product&srcval=$1
RewriteRule ^color-search-(.*)$ index.php?act=pages/src_color&srcval=$1
RewriteRule ^news-search-(.*)$ index.php?act=pages/src_news&srcval=$1

# -----
# DUAL LANGUAGE
# -----

```

```

# --- PRODUCT --- #
RewriteRule ^products/(.*)$ index.php?act=products_/index&lang=$1

# --- PAGES --- #
RewriteRule ^history/(.*)$ index.php?act=pages/about&lang=$1
RewriteRule ^vision-mission/(.*)$ index.php?act=pages/about&lang=$1
RewriteRule ^quality-policy/(.*)$ index.php?act=pages/about&lang=$1
RewriteRule ^activities/(.*)$ index.php?act=pages/about&lang=$1

# --- NEWS & EVENT --- #
RewriteRule ^news-events/(.*)$ index.php?act=news-events_/index&lang=$1
RewriteRule ^news-events-view/(.*)/(.*)/(.*)$ index.php?act=news-events_/index&nid=$1
RewriteRule ^news-events-detail/(.*)/(.*)/(.*)/(.*)$ index.php?act=news-events_/details&nid=$1

# --- COLOR CARD (SOLID) --- #
#RewriteRule ^color-cards/(.*)$ index.php?act=color-cards_/index&lang=$1
#RewriteRule ^color-cards-detail/(.*)/(.*)/(.*)$ index.php?act=color-cards_/details&nid=$1

#####
# #
# ADMIN #
# #
#####

# -----
# DASHBOARD
# -----
RewriteRule ^admin/bless$ admin/index.php?act=dashboard/index

# -----
# ACCOUNT
# -----
RewriteRule ^admin/accounts$ admin/index.php?act=settings/account/account

# -----
# GENERAL
# -----
RewriteRule ^admin/general$ admin/index.php?act=settings/general

# -----
# NOTIFICATION

```



```

# -----
RewriteRule ^admin/notifications$      admin/index.php?act=settings/notifications/index

# -----
# PAYMENT
# -----
RewriteRule ^admin/payment$           admin/index.php?act=settings/payment/index

# HOME
RewriteRule ^admin/home$              admin/index.php?act=pages/home/home

# -----
# ABOUT
# -----
RewriteRule ^admin/about$             admin/index.php?act=pages/about/about

# -----
# CONTACT
# -----
RewriteRule ^admin/contact$           admin/index.php?act=pages/contact/contact

# -----
# ORDERS
# -----
RewriteRule ^admin/order$              admin/index.php?act=orders/
RewriteRule ^admin/order-view/(, *)/(, *)/(, *)/(, *)-(, *)$      admin/index.
act=orders/index&pg=$1 &qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/order-detail/(, *)$      admin/index.php?act=orders/detail
RewriteRule ^admin/order-detailing/(, *)$    admin/index.php?act=orders/detailing

# -----
# PRODUCTS
# -----
RewriteRule ^admin/product$            admin/index.php?act=products/
RewriteRule ^admin/product-details-(, *)$  admin/index.php?act=products/details
RewriteRule ^admin/add-product$         admin/index.php?act=products/add-product

RewriteRule ^admin/product-view/(, *)/(, *)/(, *)/(, *)/(, *)-(, *)$      admin/index.php?
act=products/index&pg=$1 &cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]

RewriteRule ^admin/products/add/index.php      admin/add-product

```

```

# -----
# CATEGORY
# -----

RewriteRule ^admin/category$ admin/index.php?act=products:
RewriteRule ^admin/detail-category/(.+)/(.*)$ admin/index.php?
act=products/category/detail&cid=$1&cname=$2
RewriteRule ^admin/category-view/(.+)/(.+)/(.+)/(.*)-(.)*$ admin/index.
act=products/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/add-category$ admin/index.
RewriteRule ^admin/edit-category$ admin/index.

RewriteRule ^admin/child-category/(.+)/(.*)$ admin/index.php?
act=products/category/child/index&cid=$1&cname=$2
RewriteRule ^admin/child-category-view/(.+)/(.+)/(.+)/(.+)/(.*)-(.)*$ admin/index.
act=products/category/child/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B]

# -----
# COLOR
# -----

RewriteRule ^admin/color$ admin/index.php?act=products:
RewriteRule ^admin/color-view/(.+)/(.+)/(.+)/(.*)-(.)*$ admin/index.ph
act=products/color/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/add-color$ admin/index.
RewriteRule ^admin/edit-color$ admin/index.

# -----
# SIZE
# -----

RewriteRule ^admin/size$ admin/index.php
RewriteRule ^admin/size-view/(.+)/(.+)/(.+)/(.*)-(.)*$ admin/index.php?
act=products/size/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/add-size$ admin/index.
RewriteRule ^admin/edit-size$ admin/index.

# -----
# CUSTOMER
# -----

RewriteRule ^admin/customer$ admin/index.php?act=customers/i

```

```

RewriteRule ^admin/add-customer$ admin/index.php?act=customers/ac
RewriteRule ^admin/customer/(.*)$ admin/index.php?act=customers/de
RewriteRule ^admin/edit-customer/(.*)$ admin/index.php?act=customers/de
RewriteRule ^admin/customer-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=customers/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/customer-details/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=customers/details/index&cid=$1&pg=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# SHIPPING
# -----
RewriteRule ^admin/shipping$ admin/index.php?act=settings/shi
RewriteRule ^admin/shipping-view/(.*)/(.*)/(.*)/(.*)-(.*)$$ admin/index.php
act=settings/shipping/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/add-shipping$ admin/index.php?act=settings/:
RewriteRule ^admin/shipping/(.*)$ admin/index.php?act=settings/
RewriteRule ^admin/edit-shipping/(.*)$ admin/index.php?act=settir

# -----
# LOGOUT
# -----
RewriteRule ^admin/logout$ admin/logout

# ADDITION

RewriteRule ^admin/forgot-password$ admin/index.
RewriteRule ^admin/recover-password/(.*)/(.*)/(.*)$ admin/index.
act=account/recover&name=$1&code=$2&time=$3 [B]

RewriteRule ^admin/reset-password$ admin/email:

#####
# #
# CUSTOMS #
# #
#####

# -----
# SALE

```

```

# CHILL
# -----
RewriteRule ^admin/sale$ admin/index.php?act=custom/
RewriteRule ^admin/sale-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/promotions/sale/index&pg=$1 &cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]

# -----
# NEW ARRIVAL
# -----
RewriteRule ^admin/new-arrivals$ admin/index.php?act=cu
RewriteRule ^admin/new-arrivals-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/new_arrival/index&pg=$1 &cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]

# -----
# GALLERY
# -----
RewriteRule ^admin/project-category$ admin/index.php?act=custom/
RewriteRule ^admin/project-category-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/inspiration/category/index&pg=$1 &qpp=$2&srt=$3&src=$4&srcval=$5 [B]

RewriteRule ^admin/add-project-category$ admin/index.php?act=cus
RewriteRule ^admin/project-category-detail/(.*)$ admin/index.php?
act=custom/inspiration/category/details&ins_id=$1

RewriteRule ^admin/project$ admin/index.php?act=custom/ins
RewriteRule ^admin/view-project/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/inspiration/index&pg=$1 &cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]

RewriteRule ^admin/add-project$ admin/index.php?act=cust
RewriteRule ^admin/project-detail/(.*)$ admin/index.php?
act=custom/inspiration/detail/index&ins_id=$1

RewriteRule ^admin/project-meta-tag$ admin/index.
act=custom/inspiration/meta/index

# -----
# NEWS
# -----
RewriteRule ^admin/news-category$ admin/index.
act=custom/news/category/index
RewriteRule ^admin/news-category-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.

```

```

act=custom/news/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
RewriteRule ^admin/add-news-category$ admin/index.
RewriteRule ^admin/news-category-detail/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/news/category/details&cid=$1&c_name=$2

RewriteRule ^admin/news$ admin/index.
RewriteRule ^admin/news-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/news/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]
RewriteRule ^admin/news-detail/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/news/details/index&nid=$1&nn=$2
RewriteRule ^admin/news-edit/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/news/details/edit&nid=$1&nn=$2
RewriteRule ^admin/add-news$ admin/index.

# -----
# CAREER
# -----

RewriteRule ^admin/career-department$ admin/index.
RewriteRule ^admin/career-department-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/careers/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/add-department$ admin/index.
RewriteRule ^admin/career-department-detail/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/careers/details/index&cat_id=$1&cat_name=$2

RewriteRule ^admin/career$ admin/index.
RewriteRule ^admin/career-view/(.+)/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/careers/jobs/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

RewriteRule ^admin/add-career$ admin/index.
act=custom/careers/jobs/add/index
RewriteRule ^admin/career-detail/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.
act=custom/careers/jobs/details/index&cat_id=$1&cat_name=$2

RewriteRule ^admin/career-meta-tag$ admin/index.

# -----
# STORE
# -----

```

```
RewriteRule ^admin/store-city$ admin/index.
RewriteRule ^admin/store-city-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/store/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/add-city$ admin/index.
RewriteRule ^admin/store-city-detail/(.*)/(.*)$ admin/index.
act=custom/store/details/index&cat_id=$1&cat_name=$2

RewriteRule ^admin/store$ admin/index.
RewriteRule ^admin/store-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/store/jobs/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

RewriteRule ^admin/add-store$ admin/index.
act=custom/store/jobs/add/index
RewriteRule ^admin/store-detail/(.*)/(.*)$ admin/index.
act=custom/store/jobs/details/index&cat_id=$1&cat_name=$2

RewriteRule ^admin/store-meta-tag$ admin/index.

# -----
# SERVICE CENTER
# -----

RewriteRule ^admin/service-city$ admin/index.
RewriteRule ^admin/service-city-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/service/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/add-service-city$ admin/index.
RewriteRule ^admin/service-city-detail/(.*)/(.*)$ admin/index.
act=custom/service/details/index&cat_id=$1&cat_name=$2

RewriteRule ^admin/service$ admin/index.
RewriteRule ^admin/service-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.
act=custom/service/jobs/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

RewriteRule ^admin/add-service$ admin/index.
act=custom/service/jobs/add/index
RewriteRule ^admin/service-detail/(.*)/(.*)$ admin/index.
act=custom/service/jobs/details/index&cat_id=$1&cat_name=$2

RewriteRule ^admin/service-meta-tag$ admin/index.
```

```

# -----
# TAGS
# -----

RewriteRule ^admin/tag$ admin/index.php?act=custom/tag/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/detail-tag/(.+)/(.+)$ admin/index.php?act=custom/tag/index&cid=$1&cname=$2
RewriteRule ^admin/tag-view/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?act=custom/tag/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B]

RewriteRule ^admin/add-tag$ admin/index.php
RewriteRule ^admin/edit-tag$ admin/index.php

RewriteRule ^admin/child-tag/(.+)/(.+)$ admin/index.php?act=custom/tag/child/index&cid=$1&cname=$2
RewriteRule ^admin/child-tag-view/(.+)/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?act=custom/tag/child/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B]

# -----
# TAGS 2
# -----

RewriteRule ^admin/tagging$ admin/index.php?act=custom/tagging/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/detail-tagging/(.+)/(.+)$ admin/index.php?act=custom/tagging/index&cid=$1&cname=$2
RewriteRule ^admin/tagging-view/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?act=custom/tagging/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B]

RewriteRule ^admin/add-tagging$ admin/index.php
RewriteRule ^admin/edit-tagging$ admin/index.php

RewriteRule ^admin/child-tagging/(.+)/(.+)$ admin/index.php?act=custom/tagging/child/index&cid=$1&cname=$2
RewriteRule ^admin/child-tagging-view/(.+)/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?act=custom/tagging/child/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B]

# -----
# FILTER
# -----

RewriteRule ^admin/filter$ admin/index.php?act=custom/filter/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/filter-view/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?act=custom/filter/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B]

RewriteRule ^admin/add-filter$ admin/index.php
RewriteRule ^admin/filter-detail/(.+)/(.+)$ admin/index.php

```

```

act=custom/filter/details/index&cat_id=$1&cat_name=$2

# -----
# FILTER SUBSTRAT
# -----
RewriteRule ^admin/filter-substrat$                                admin/index.
RewriteRule ^admin/filter-substrat-view/(.)/(.)/(.)/(.)-(.)$    admin/index.
act=custom/substrat_/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/add-filter-substrat$                          admin/index.
act=custom/substrat_/add/index
RewriteRule ^admin/filter-substrat-detail/(.)/(.)$              admin/index.
act=custom/substrat_/details/index&cat_id=$1&cat_name=$2

RewriteRule ^admin/products-substrat$                            admin/index.php?act=c
RewriteRule ^admin/products-substrat-view/(.)/(.)/(.)/(.)/(.)-(.)$  admin/index.
act=custom/substrat/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]

# -----
# DUAL LANGUAGE
# -----

# -----
# FRONT END
# -----
RewriteRule ^bahasa-(.)$          lang_id.php?&cur=$1
RewriteRule ^default-(.)$        lang_en.php?&cur=$1

# -----
# ABOUT
# -----
RewriteRule ^admin/(.)-about$     admin/index.php?
act=custom/language/pages/about/about&lang=$1

# -----
# PRODUCTS
# -----
RewriteRule ^admin/(.)-product-details-(.)$      admin/index.php?
act=custom/language/products/edit&lang=$1&product_alias=$2
RewriteRule ^admin/(.)-detail-category/(.)/(.)$  admin/index.php?
act=custom/language/products/category/detail&lang=$1&cid=$2&cname=$3

```



```
# -----  
# NEWS  
# -----  
RewriteRule ^admin/(.*)-news-category-detail/(.*)/(.*)$ admin/index.php  
act=custom/language/pages/news/category/category&lang=$1&nid=$2&nn=$3  
  
RewriteRule ^admin/(.*)-news-detail/(.*)/(.*)$ admin/index.php?  
act=custom/language/pages/news/news&lang=$1&nid=$2&nn=$3  
RewriteRule ^admin/(.*)-news-edit/(.*)/(.*)$ admin/index.php?  
act=custom/language/pages/news/news_edit&lang=$1&nid=$2&nn=$3  
  
# -----  
# END DUAL LANGUAGE  
# -----  
  
RewriteRule sitemap.xml sitemap.php [nocase]
```