

Apache Configuration File

(!) Using `.htaccess` files slows down Apache, therefore, if you have access to the main server config file (usually called `httpd.conf`), you should add this logic there: <http://httpd.apache.org/docs/current/howto/htaccess.html>.

```
# #####  
# # CROSS-ORIGIN RESOURCE SHARING (CORS) #  
# #####
```

```
# -----  
# | Cross-domain AJAX requests |  
# -----
```

Enable cross-origin AJAX requests.
<http://code.google.com/p/html5security/wiki/CrossOriginRequestSecurity>
<http://enable-cors.org/>

```
# <IfModule mod_headers.c>  
#   Header set Access-Control-Allow-Origin "*"   
# </IfModule>
```

```
# -----  
# | CORS-enabled images |  
# -----
```

Send the CORS header for images when browsers request it.
https://developer.mozilla.org/en/CORS_Enabled_Image
<http://blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html>
<http://hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/>

```
<IfModule mod_setenvif.c>  
  <IfModule mod_headers.c>  
    <FilesMatch "\.(gif|ico|jpe?g|png|svg|svgz|webp)$">  
      SetEnvIf Origin ":" IS_CORS  
      Header set Access-Control-Allow-Origin "*" env=IS_CORS  
    </FilesMatch>  
  </IfModule>  
</IfModule>
```

```

# -----
# | Web fonts access |
# -----

# Allow access from all domains for web fonts

<IfModule mod_headers.c>
    <FilesMatch "\.(eot|font\.css|otf|ttc|ttf|woff)$">
        Header set Access-Control-Allow-Origin "*"
    </FilesMatch>
</IfModule>

# #####
# # ERRORS #
# #####

# -----
# | 404 error prevention for non-existing redirected folders |
# -----

# Prevent Apache from returning a 404 error for a rewrite if a directory
# with the same name does not exist.
# http://httpd.apache.org/docs/current/content-negotiation.html#multiviews
# http://www.webmasterworld.com/apache/3808792.htm

Options -MultiViews

# -----
# | Custom error messages / pages |
# -----

# You can customize what Apache returns to the client in case of an error (see
# http://httpd.apache.org/docs/current/mod/core.html#errordocument), e.g.:
```

ErrorDocument 404 /404.html

```

# #####
# # INTERNET EXPLORER #
# #####

# -----
# | Internet Explorer 6 compatibility mode |
# -----

```

```

# | Better website experience |
# -----

# Force IE to render pages in the highest available mode in the various
# cases when it may not: http://hsivonen.iki.fi/doctype/ie-mode.pdf.

<IfModule mod_headers.c>
    #RequestHeader set X-Prerender-Token "YOUR_TOKEN"
    Header set X-UA-Compatible "IE=edge"
    # `mod_headers` can't match based on the content-type, however, we only
    # want to send this header for HTML pages and not for the other resources
    <FilesMatch "\.(appcache|crx|css|eot|gif|htc|icol|jpe?g|js|m4a|m4v|manifest|mp4|ogg|ogv|
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# -----

# | Cookie setting from iframes |
# -----

# Allow cookies to be set from iframes in IE.

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
# </IfModule>

# -----

# | Screen flicker |
# -----

# Stop screen flicker in IE on CSS rollovers (this only works in
# combination with the `ExpiresByType` directives for images from below).

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# #####
# # MIME TYPES AND ENCODING #
# #####

```

```
# -----
# | Proper MIME types for all files |
# -----

<IfModule mod_mime.c>

# Audio
AddType audio/mp4          m4a f4a f4b
AddType audio/ogg          oga ogg

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways):
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript    js jsonp
AddType application/json         json

# Video
AddType video/mp4          mp4 m4v f4v f4p
AddType video/ogg          ogv
AddType video/webm         webm
AddType video/x-flv        flv

# Web fonts
AddType application/font-woff    woff
AddType application/vnd.ms-fontobject    eot

# Browsers usually ignore the font MIME types and sniff the content,
# however, Chrome shows a warning if other MIME types are used for the
# following fonts.
AddType application/x-font-ttf    ttc ttf
AddType font/opentype             otf

# Make SVGZ fonts work on iPad:
# https://twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml           svg svgz
AddEncoding gzip                 svgz

# Other
AddType application/octet-stream  safariextz
AddType application/x-chrome-extension    crx
```

```

AddType application/x-opera-extension      oex
AddType application/x-shockwave-flash     swf
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall           xpi
AddType application/xml                   atom rdf rss xml
AddType image/webp                        webp
AddType image/x-icon                      ico
AddType text/cache-manifest               appcache manifest
AddType text/vtt                          vtt
AddType text/x-component                  htc
AddType text/x-vcard                      vcf

```

```
</IfModule>
```

```

# -----
# | UTF-8 encoding |
# -----

```

```

# Use UTF-8 encoding for anything served as `text/html` or `text/plain`.
AddDefaultCharset utf-8

```

```
# Force UTF-8 for certain file formats.
```

```

<IfModule mod_mime.c>
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
</IfModule>

```

```

# #####
# # URL REWRITES #
# #####

```

```

# -----
# | Rewrite engine |
# -----

```

```

# Turning on the rewrite engine and enabling the `FollowSymLinks` option is
# necessary for the following directives to work.

```

```

# If your web host doesn't allow the `FollowSymLinks` option, you may need to
# comment it out and use `Options +SymLinksIfOwnerMatch` but, be aware of the
# performance impact: http://httpd.apache.org/docs/current/misc/perf-tuning.html#symlinks

```

```
# Also, some cloud hosting services require `RewriteBase` to be set:  
# http://www.rackspace.com/knowledge_center/frequently-asked-question/why-is-mod-rewrite-not-working
```

```
<IfModule mod_rewrite.c>  
    Options +FollowSymlinks  
    # Options +SymLinksIfOwnerMatch  
    RewriteEngine On  
    # RewriteBase /  
</IfModule>
```

```
# -----  
# | Suppressing / Forcing the "www." at the beginning of URLs |  
# -----
```

```
# The same content should never be available under two different URLs especially  
# not with and without "www." at the beginning. This can cause SEO problems  
# (duplicate content), therefore, you should choose one of the alternatives and  
# redirect the other one.
```

```
# By default option 1 (no "www.") is activated:  
# http://no-www.org/faq.php?q=class_b
```

```
# If you'd prefer to use option 2, just comment out all the lines from option 1  
# and uncomment the ones from option 2.
```

```
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!
```

```
# -----
```

```
# Option 1: rewrite www.example.com → example.com
```

```
<IfModule mod_rewrite.c>  
    RewriteCond %{HTTPS} !=on  
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]  
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]  
</IfModule>
```

```
# -----
```

```
# Option 2: rewrite example.com → www.example.com
```

```
# Be aware that the following might not be a good idea if you use "real"
# subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#     RewriteCond %{HTTPS} !=on
#     RewriteCond %{HTTP_HOST} !^www\..+$ [NC]
#     RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# #####
# # SECURITY #
# #####

# -----
# | Content Security Policy (CSP) |
# -----

# You can mitigate the risk of cross-site scripting and other content-injection
# attacks by setting a Content Security Policy which whitelists trusted sources
# of content for your site.

# The example header below allows ONLY scripts that are loaded from the current
# site's origin (no inline scripts, no CDN, etc). This almost certainly won't
# work as-is for your site!

# To get all the details you'll need to craft a reasonable policy for your site,
# read: http://html5rocks.com/en/tutorials/security/content-security-policy (or
# see the specification: http://w3.org/TR/CSP).

# <IfModule mod_headers.c>
#     Header set Content-Security-Policy "script-src 'self'; object-src 'self'"
#     <FilesMatch "\.(appcache|crx|css|eot|gif|htc|ico|jpe?g|js|m4a|m4v|manifest|mp4|oex|oga|
#         Header unset Content-Security-Policy
#     </FilesMatch>
# </IfModule>

# -----
# | File access |
# -----

# Block access to directories without a default document.
```

```

# Usually you should leave this uncommented because you shouldn't allow anyone
# to surf through every directory on your server (which may includes rather
# private places like the CMS's directories).

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# -----

# Block access to hidden files and directories.
# This includes directories used by version control systems such as Git and SVN.

<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
</IfModule>

# -----

# Block access to backup and source files.
# These files may be left by some text editors and can pose a great security
# danger when anyone has access to them.

<FilesMatch "(^#.#|\. (bak| config| dist| fl| incl| ini| log| psd| sh| sql| sw[op])| (^)$">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# -----
# | Secure Sockets Layer (SSL) |
# -----

# Rewrite secure requests properly to prevent SSL certificate warnings, e.g.:
# prevent `https://www.example.com` when your certificate only allows
# `https://secure.example.com`.

# <IfModule mod_rewrite.c>
#     RewriteCond %{SERVER_PORT} !^443

```



```
.. -----  
# RewriteRule ^ https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]  
# </IfModule>  
  
# -----  
  
# Force client-side SSL redirection.  
  
# If a user types "example.com" in his browser, the above rule will redirect him  
# to the secure version of the site. That still leaves a window of opportunity  
# (the initial HTTP connection) for an attacker to downgrade or redirect the  
# request. The following header ensures that browser will ONLY connect to your  
# server via HTTPS, regardless of what the users type in the address bar.  
# http://www.html5rocks.com/en/tutorials/security/transport-layer-security/  
  
# <IfModule mod_headers.c>  
# Header set Strict-Transport-Security max-age=16070400;  
# </IfModule>  
  
# -----  
# | Server software information |  
# -----  
  
# Avoid displaying the exact Apache version number, the description of the  
# generic OS-type and the information about Apache's compiled-in modules.  
  
# ADD THIS DIRECTIVE IN THE `httpd.conf` AS IT WILL NOT WORK IN THE `.htaccess`!  
  
# ServerTokens Prod  
  
# #####  
# # WEB PERFORMANCE #  
# #####  
  
# -----  
# | Compression |  
# -----  
  
<IfModule mod_deflate.c>  
  
# Force compression for mangled headers.  
# http://developer.yahoo.com/blogs/uda/posts/2010/12/pushing-beyond-gzip/
```

```

# http://developer.yahoo.com/yql/yql_examples.html#yql-ucygnu-yzppuuy
<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        SetEnvIfNoCase ^(\Accept-Encoding X-cept-Encoding X(15)|^(15)|-(15))$ ^((gzip def
        RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
    </IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        text/xml

</IfModule>

</IfModule>

# -----
# | Content transformations |
# -----

# Prevent some of the mobile network providers from modifying the content of
# your site: http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9.5.

# IfModule mod_headers.c

```

```

# <!--Module mod_headers.c>
#   Header set Cache-Control "no-transform"
# </IfModule>

# -----
# | ETag removal |
# -----

# Since we're sending far-future expires headers (see below), ETags can
# be removed: http://developer.yahoo.com/performance/rules.html#etags.

# `FileETag None` is not enough for every server.
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>

FileETag None

# -----
# | Expires headers (for better cache control) |
# -----

# The following expires headers are set pretty far in the future. If you don't
# control versioning with filename-based cache busting, consider lowering the
# cache time for resources like CSS and JS to something like 1 week.

<IfModule mod_expires.c>

    ExpiresActive on
    ExpiresDefault "access plus 1 month"

# CSS
    ExpiresByType text/css "access plus 1 year"

# Data interchange
    ExpiresByType application/json "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType text/xml "access plus 0 seconds"

# Favicon (cannot be renamed!)
    ExpiresByType image/x-icon "access plus 1 week"

```

```

# HTML components (HTCs)
ExpiresByType text/x-component "access plus 1 month"

# HTML
ExpiresByType text/html "access plus 0 seconds"

# JavaScript
ExpiresByType application/javascript "access plus 1 year"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# Web feeds
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"

```

```
</IfModule>
```

```

# -----
# | Filename-based cache busting |
# -----

```

```
# If you're not using a build process to manage your filename version revving,
```

```
# you might want to consider enabling the following directives to route all
# requests such as `/css/style.12345.css` to `/css/style.css`.

# To understand why this is important and a better idea than `*.css?v231`, read:
# http://stevesouder.com/blog/2008/08/23/rewriting-filenames-dont-use-querystring

# <IfModule mod_rewrite.c>
#     RewriteCond %{REQUEST_FILENAME} !-f
#     RewriteCond %{REQUEST_FILENAME} !-d
#     RewriteRule ^(.+)?\.(?d+)\.(j?sl?css?png?jpg?gif)$ $1.$3 [L]
# </IfModule>

# -----
# | File concatenation |
# -----

# Allow concatenation from within specific CSS and JS files, e.g.:
# Inside of `script.combined.js` you could have
# <!--#include file="libs/jquery.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# <IfModule mod_include.c>
#     <FilesMatch "\.combined\.js$" >
#         Options +Includes
#         AddOutputFilterByType INCLUDES application/javascript application/json
#         SetOutputFilter INCLUDES
#     </FilesMatch>
#     <FilesMatch "\.combined\.css$" >
#         Options +Includes
#         AddOutputFilterByType INCLUDES text/css
#         SetOutputFilter INCLUDES
#     </FilesMatch>
# </IfModule>

# -----
# | Persistent connections |
# -----

# Allow multiple requests to be sent over the same TCP connection:
# http://httpd.apache.org/docs/current/en/mod/core.html#keepalive.
```

```

# Enable if you serve a lot of static content but, be aware of the
# possible disadvantages!

# <IfModule mod_headers.c>
#   Header set Connection Keep-Alive
# </IfModule>

# Change YOUR_TOKEN to your prerender token and uncomment that line if you want to cache url
# Change http://example.com (at the end of the last RewriteRule) to your website url

<IfModule mod_headers.c>
    #RequestHeader set X-Prerender-Token "0wL7Y0yZGLGJVoPwtJjL"
</IfModule>

<IfModule mod_rewrite.c>
    RewriteEngine On

    <IfModule mod_proxy_http.c>
        RewriteCond %{HTTP_USER_AGENT} baiduspider|facebookexternalhit|twitterbot|rogerbot|
        RewriteCond %{QUERY_STRING} _escaped_fragment_

        # Only proxy the request to Prerender if it's a request for HTML
        RewriteRule ^(?:.*?
(\.js|\.css|\.xml|\.less|\.png|\.jpg|\.jpeg|\.gif|\.pdf|\.doc|\.txt|\.ico|\.rss|\.zip|\.mp3|
(.*) http://service.prerender.io/http://snielportfolio.azurewebsites.net/$2 [P,L]
    </IfModule>
</IfModule>

Options +FollowSymLinks

<ifModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteCond %{REQUEST_URI} !index
    RewriteRule (,*) index.html [L]
</ifModule>

```