

```

# Turn off MultiViews
Options +FollowSymLinks -MultiViews

# Rewrite engine setup
RewriteEngine On
RewriteBase /

# Directive to ensure files are served with the appropriate content type,
# if not present in main Apache config.
AddType application/rdf+xml .rdf
AddType text/turtle .ttl
AddType application/vnd.ogc.gml .gml
AddType application/vnd.google-earth.kml+xml .kml
AddType application/json .geojson

# Redirect from HTML home to PHP
RewriteRule ^index.html$ index.php [L,R=301]

#####
# RULES FOR ONTOLOGY
#####

# Rewrite rule to serve HTML content from the vocabulary URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} text/html [OR]
RewriteCond %{HTTP_ACCEPT} application/xhtml+xml
RewriteRule ^ontology(.*)$ ontology.html$1 [L,R=303]

# Rewrite rule to redirect the ontology URI to a RDF definition
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^ontology(.*)$ ontology.rdf [L,QSA]

#####
# RULES FOR IGDV AGREEMENTS
#####

# Rewrite rule to serve HTML content from the vocabulary URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d

```

```

RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} text/html [OR]
RewriteCond %{HTTP_ACCEPT} application/xhtml+xml
RewriteRule ^igov(.*)$ igov.html$1 [L,R=303]

# Rewrite rule to redirect the agreement's URI to a RDF definition
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^igov(.*)$ igov.rdf [L, QSA]

#####
# RULES FOR SEARCH
#####

# Rewrite rule to serve RDF/XML content from the search URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/rdf+xml
RewriteRule ^search?(.*)$ search.php?content_type=rdf&$1 [L, QSA]

# Rewrite rule to remove PHP extension from the search URI
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^search(.*)$ search.php$1 [L, QSA]

#####
# RULES FOR Neogeo
#####

# Rewrite rule to serve RDF/XML content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/rdf+xml
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))? $ services/neogeo.php?relation=$1&content_type=rdf

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^neogeo/(\w+).rdf(?! \.php)(\?(. *))? $ services/neogeo.php?relation=$1&content_ty

# Rewrite rule to serve Turtle content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f

```

```
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} text/turtle
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=$1&content_type=t1

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} text/turtle
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=$1&content_type=t1

# Rewrite rule to serve KML content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd\.google\-earth\.kml\+xml
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=$1&content_type=kr

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^neogeo/(\w+).kml(\?(. *))?$ services/neogeo.php?relation=$1&content_type=kml&$3

# Rewrite rule to serve KMZ content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd\.google\-earth\.kmz
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=$1&content_type=kr

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^neogeo/(\w+).kmz(\?(. *))?$ services/neogeo.php?relation=$1&content_type=kmz&$3

# Rewrite rule to serve GML content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd\.ogc\.gml
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=$1&content_type=gr

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^neogeo/(\w+).gml(\?(. *))?$ services/neogeo.php?relation=$1&content_type=gml&$3

# Rewrite rule to serve SVG content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
```

```

RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} image/svg+xml
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=${1}content_type=sv

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^neogeo/(\w+)\.svg(\?(. *))?$ services/neogeo.php?relation=${1}content_type=svg&${3}

# Rewrite rule to serve GeoJSON content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/json
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=${1}&content_type=geojso

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/json
RewriteRule ^neogeo/(\w+)\.json(\?(. *))?$ services/neogeo.php?relation=${1}&content_type=geojsco

# Rewrite rule to remove PHP extension from the services' URI
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^neogeo/(\w+)(?! \.php)(\?(. *))?$ services/neogeo.php?relation=${1}&content_type=rco

#####
# RULES FOR BBOX (deprecated)
#####

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^services/boundingBox(?! \.php)(\?(. *))?$ neogeo/0$2 [L, R=301]

#####
# RULES FOR SERVICES
#####

# Rewrite rule to serve RDF/XML content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/rdf+xml
RewriteRule ^services/(\w+)(?! \.php)(\?(. *))?$ services/${1}.php?content_type=rdf&${3} [L, QSA]

```

```
# Rewrite rule to serve Turtle content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} text/turtle
RewriteRule ^services/(\w+)(? \. php)(\?(. *))?$ services/$1.php?content_type=ttl&#3 [L, QSA]

# Rewrite rule to serve KML content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd\. google\-earth\. kml\+xml
RewriteRule ^services/(\w+)(? \. php)(\?(. *))?$ services/$1.php?content_type=kml&#3 [L, QSA]

# Rewrite rule to serve KMZ content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd\. google\-earth\. kmz
RewriteRule ^services/(\w+)(? \. php)(\?(. *))?$ services/$1.php?content_type=kmz&#3 [L, QSA]

# Rewrite rule to serve GML content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd\. ogc\. gml
RewriteRule ^services/(\w+)(? \. php)(\?(. *))?$ services/$1.php?content_type=gml&#3 [L, QSA]

# Rewrite rule to serve SVG content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} image/svg\+xml
RewriteRule ^services/(\w+)(? \. php)(\?(. *))?$ services/$1.php?content_type=svg&#3 [L, QSA]

# Rewrite rule to serve GeoJSON content from the services' URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/json
RewriteRule ^services/(\w+)(? \. php)(\?(. *))?$ services/$1.php?content_type=geojson&#3 [L, QSA]

# Rewrite rule to remove PHP extension from the services' URI
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^services/(\w+)(? \. php)(\?(. *))?$ services/$1.php?content_type=rdf&#3 [L, QSA]
```

```
#####
```

```
# RULES FOR SUB
```

```
#####
```

```
# HTML
```

```
# Let the service provide the HTML content for the feature
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteRule ^id/([0-3])/(\\d+)/sub.html$ sub.php?level=$1&id=$2&feature=1&resolution=1&geomet
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(HTTP_ACCEPT) application/xhtml+xml
```

```
RewriteRule ^id/([0-3])/(\\d+)/sub$ id/$1/$2/sub.html [L,R=303]
```

```
#rdf
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteRule ^id/([0-3])/(\\d+)/sub.rdf$ sub.php?level=$1&id=$2&feature=1&resolution=1&geometr
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(HTTP_ACCEPT) application/rdf+xml
```

```
RewriteRule ^id/([0-3])/(\\d+)/sub$ id/$1/$2/sub.rdf [L,R=303]
```

```
#ttl
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteRule ^id/([0-3])/(\\d+)/sub.ttl$ sub.php?level=$1&id=$2&feature=1&resolution=1&geometr
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(HTTP_ACCEPT) text/turtle
```

```
RewriteRule ^id/([0-3])/(\\d+)/sub$ id/$1/$2/sub.ttl [L,R=303]
```

```
#kml
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteRule ^id/([0-3])/(\\d+)/sub.kml$ sub.php?level=$1&id=$2&geometry=1&resolution=1&geomet
```

```

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd\.google\-earth\.kml\+xml
RewriteRule ^id/([0-3])/(\d+)/sub$ id/$1/$2/sub.kml [L,R=303]

#####
# RULES FOR REGIONS
#####

# HTML

# Let the service provide the HTML content for the geometry, resolution 100m
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(\d+)/geometry_100m.html$ region.php?level=$1&id=$2&geometry=1&content_type=html [L,QSA]

# Let the service provide the HTML content for the geometry, resolution 1km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(\d+)/geometry_1km.html$ region.php?level=$1&id=$2&geometry=1&content_type=html [L,QSA]

# Let the service provide the HTML content for the geometry, resolution 10km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(\d+)/geometry_10km.html$ region.php?level=$1&id=$2&geometry=1&content_type=html [L,QSA]

# Let the service provide the HTML content for the geometry, resolution 100km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(\d+)/geometry_100km.html$ region.php?level=$1&id=$2&geometry=1&content_type=html [L,QSA]

# Let the service provide the HTML content for the geometry
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(\d+)/geometry.html$ region.php?level=$1&id=$2&geometry=1&content_type=html [L,QSA]

# Let the service provide the HTML content for the feature
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(\d+)/.html$ region.php?level=$1&id=$2&feature=1&content_type=html [L,QSA]

```

```

# Rewrite rule to serve HTML content from the URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} text/html [OR]
RewriteCond %{HTTP_ACCEPT} application/xhtml+xml
RewriteRule ^id/([0-4])/(d+)/geometry)?(w+)?$ id/$1/$2$3$4.html [L,R=303]

# RDF/XML

# Let the service provide the RDF/XML content for the geometry, resolution 100m
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(d+)/geometry_100m.rdf region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the RDF/XML content for the geometry, resolution 1km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(d+)/geometry_1km.rdf region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the RDF/XML content for the geometry, resolution 10km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(d+)/geometry_10km.rdf region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the RDF/XML content for the geometry, resolution 100km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(d+)/geometry_100km.rdf region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the RDF/XML content for the geometry
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(d+)/geometry.rdf$ region.php?level=$1&id=$2&geometry=1&content_type

# Let the service provide the RDF/XML content for the feature
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(d+).rdf$ region.php?level=$1&id=$2&feature=1&content_type=rdf [L,R=303]

# Rewrite rule to serve RDF/XML content from the URI if requested

```

```

-----
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond %(HTTP_ACCEPT) application/rdf\+xml
RewriteRule ^id/([0-4])/(.+)/(geometry)?(._w+)?$ id/$1/$2$3.rdf [L,R=303]

# Turtle

# Let the service provide the Turtle content for the geometry, resolution 100m
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(.+)/geometry_100m.ttl region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the Turtle content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(.+)/geometry_1km.ttl region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the Turtle content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(.+)/geometry_10km.ttl region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the Turtle content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(.+)/geometry_100km.ttl region.php?level=$1&id=$2&geometry=1&conter

# Let the service provide the Turtle content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(.+)/geometry.ttl region.php?level=$1&id=$2&geometry=1&content_type:

# Let the service provide the Turtle content for the feature
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(.+).ttl region.php?level=$1&id=$2&feature=1&content_type=ttl [L,Q]

# Rewrite rule to serve Turtle content from the URI if requested
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond %(HTTP_ACCEPT) text/turtle

```

```
RewriteCond %{HTTP_REFERER} !example.com [OR]
```

```
RewriteRule ^id/([0-4])/(d+)/geometry)?(w+)?$ id/$1/$2$3.ttl [L,R=303]
```

```
# GML
```

```
# Let the service provide the GML content for the geometry, resolution 100m
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^id/([0-4])/(d+)/geometry_100m.gml region.php?level=$1&id=$2&geometry=1&content
```

```
# Let the service provide the GML content for the geometry, resolution 1km
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^id/([0-4])/(d+)/geometry_1km.gml region.php?level=$1&id=$2&geometry=1&content
```

```
# Let the service provide the GML content for the geometry, resolution 10km
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^id/([0-4])/(d+)/geometry_10km.gml region.php?level=$1&id=$2&geometry=1&content
```

```
# Let the service provide the GML content for the geometry, resolution 100km
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^id/([0-4])/(d+)/geometry_100km.gml region.php?level=$1&id=$2&geometry=1&content
```

```
# Let the service provide the GML content for the geometry
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^id/([0-4])/(d+)/geometry.gml region.php?level=$1&id=$2&geometry=1&content_type
```

```
# Rewrite rule to serve GML content from the URI if requested
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{HTTP_ACCEPT} application/vnd\.ogc\*.gml
```

```
RewriteRule ^id/([0-4])/(d+)/geometry)?(w+)?$ id/$1/$2$3.gml [L,R=303]
```

```
# SVG
```

```
# Let the service provide the SVG content for the geometry, resolution 100m
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^id/([0-4])/(d+)/geometry_100m.svg region.php?level=$1&id=$2&geometry=1&content
```

```

RewriteRule ^id/([0-4])/(\\d+)/geometry_100m.svg region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the SVG content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_1km.svg region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the SVG content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_10km.svg region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the SVG content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_100km.svg region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the SVG content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry.svg region.php?level=$1&id=$2&geometry=1&content_type=

# Rewrite rule to serve SVG content from the URI if requested
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond %(HTTP_ACCEPT) image/svg+xml
RewriteRule ^id/([0-4])/(\\d+)(/geometry)?(\\w+)?$ id/$1/$2$3.svg [L,R=303]

# KML

# Let the service provide the KML content for the geometry, resolution 100m
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_100m.kml region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the KML content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_1km.kml region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the KML content for the geometry, resolution 10km

```

```

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(.+)/geometry_10km.kml region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the KML content for the geometry, resolution 100km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(.+)/geometry_100km.kml region.php?level=$1&id=$2&geometry=1&conter

# Return a simplified version of the geometry with a reduced number of coordinates so that :
Maps limit.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(.+)/simplified_geometry.kml region.php?level=$1&id=$2&geometry=1&

# Let the service provide the KML content for the geometry
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(.+)/geometry.kml region.php?level=$1&id=$2&geometry=1&content_type:

# Rewrite rule to serve KML content from the URI if requested
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd.google-earth.kml+xml
RewriteRule ^id/([0-4])/(.+)(/geometry)?(._w+)?$ id/$1/$2$3.kml [L,R=303]

# KMZ

# Let the service provide the KMZ content for the geometry, resolution 100m
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(.+)/geometry_100m.kmz region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the KMZ content for the geometry, resolution 1km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])/(.+)/geometry_1km.kmz region.php?level=$1&id=$2&geometry=1&content.

# Let the service provide the KMZ content for the geometry, resolution 10km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d

```

```

RewriteRule ^id/([0-4])/(\\d+)/geometry_10km.kmz region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the KMZ content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_100km.kmz region.php?level=$1&id=$2&geometry=1&content

# Return a simplified version of the geometry with a reduced number of coordinates so that it fits the
# Maps limit.
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/simplified_geometry.kmz region.php?level=$1&id=$2&geometry=1&content

# Let the service provide the KMZ content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry.kmz region.php?level=$1&id=$2&geometry=1&content_type=kmz

# Rewrite rule to serve KMZ content from the URI if requested
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond %(HTTP_ACCEPT) application/vnd\\.google\\-earth\\.kmz
RewriteRule ^id/([0-4])/(\\d+)(/geometry)?(\\w+)?$ id/$1/$2$3.kmz [L, R=303]

# GeoJSON

# Let the service provide the GeoJSON content for the geometry, resolution 100m
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_100m.gejson region.php?level=$1&id=$2&geometry=1&content_type=gejson [L, QSA]

# Let the service provide the GeoJSON content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(\\d+)/geometry_1km.gejson region.php?level=$1&id=$2&geometry=1&content_type=gejson [L, QSA]

# Let the service provide the GeoJSON content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d

```

```

RewriteRule ^id/([0-4])/(d+)/geometry_100km_geojson_region.php?level=$1&id=$2&geometry=1&cor
[L, QSA]

# Let the service provide the GeoJSON content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(d+)/geometry_100km_geojson_region.php?level=$1&id=$2&geometry=1&cor
[L, QSA]

# Let the service provide the GeoJSON content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(d+)/geometry_geojson_region.php?level=$1&id=$2&geometry=1&content_
[L, QSA]

# Rewrite rule to serve GeoJSON content from the URI if requested
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond %(HTTP_ACCEPT) application/json
RewriteRule ^id/([0-4])/(d+)(/geometry)?(w+)?$ id/$1/$2$3_geojson [L, R=303]

# DEFAULT (HTML)

# Rewrite rule to serve HTML content if the Accept Header is not set or does not match a cor
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])/(d+)(/geometry)?(w+)?$ id/$1/$2$3.html [L, R=303]

#####
# RULES FOR LEVELS
#####

# HTML
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond expr "!%(QUERY_STRING) -strmatch '*limit*"
RewriteRule ^id/([0-4]).html$id/$1.html?limit=0,20 [L, R=303]

RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteCond expr "%(QUERY_STRING) -strmatch '*limit*"
RewriteRule ^id\([0-4])\.html_level.php?level=$1&feature=1&content_type=html [L, QSA]

```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/xhtml+xml
RewriteRule ^id/([0-4])$ id/$1.html [L,R=303]

#rdf
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4]).rdf?(.*)$ level.php?level=$1&feature=1&content_type=rdf&$2 [L,QSA]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4]).rdf$ id/$1.rdf?limit=0,20 [L,R=303]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/rdf+xml
RewriteRule ^id/([0-4])$ id/$1.rdf [L,R=303]

#ttl
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4]).ttl$ level.php?level=$1&feature=1&content_type=rdf [L,QSA]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} text/turtle
RewriteRule ^id/([0-4])$ id/$1.rdf [L,R=303]

#kml
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4]).kml$ level.php?level=$1&id=$2&geometry=1&geometry=1&resolution=100&

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{HTTP_ACCEPT} application/vnd.google-earth.kml+xml
RewriteRule ^id/([0-4])$ id/$1.kml [L,R=303]
```

#####

#Compatibility mode (started on 31st of Juli 2013)

#####

#####

# RULES FOR REGIONS

#####

#basic rules

RewriteCond %(REQUEST\_FILENAME) !-f

RewriteCond %(REQUEST\_FILENAME) !-d

RewriteRule ^id/([0-4])\_(\d+)\_geometry?(\\_w+)?\$ id/\$1/\$2/geometry [L,R=301]

#basic rules

RewriteCond %(REQUEST\_FILENAME) !-f

RewriteCond %(REQUEST\_FILENAME) !-d

RewriteRule ^id/([0-4])\_(\d+)(\\_geometry)?(\\_w+)?\$ id/\$1/\$2 [L,R=301]

# HTML

# Let the service provide the HTML content for the geometry, resolution 100m

RewriteCond %(REQUEST\_FILENAME) !-f

RewriteCond %(REQUEST\_FILENAME) !-d

RewriteRule ^id/([0-4])\_(\d+)\_geometry\_100m.html\$ id/\$1/\$2/geometry\_100m.html [L,R=301]

# Let the service provide the HTML content for the geometry, resolution 1km

RewriteCond %(REQUEST\_FILENAME) !-f

RewriteCond %(REQUEST\_FILENAME) !-d

RewriteRule ^id/([0-4])\_(\d+)\_geometry\_1km.html\$ id/\$1/\$2/geometry\_1km.html [L,R=301]

# Let the service provide the HTML content for the geometry, resolution 10km

RewriteCond %(REQUEST\_FILENAME) !-f

RewriteCond %(REQUEST\_FILENAME) !-d

RewriteRule ^id/([0-4])\_(\d+)\_geometry\_10km.html\$ id/\$1/\$2/geometry\_10km.html [L,R=301]

# Let the service provide the HTML content for the geometry, resolution 100km

RewriteCond %(REQUEST\_FILENAME) !-f

RewriteCond %(REQUEST\_FILENAME) !-d

RewriteRule ^id/([0-4])\_(\d+)\_geometry\_100km.html\$ id/\$1/\$2/geometry\_100km.html [L,R=301]

# Let the service provide the HTML content for the geometry

RewriteCond %(REQUEST\_FILENAME) !-f

```
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.html$ id/$1/$2/geometry.html [L,R=301]

# Let the service provide the HTML content for the feature
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+).html$ id/$1/$2.html [L,R=301]

# RDF/XML

# Let the service provide the rdf content for the geometry, resolution 100m
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100m.rdf$ id/$1/$2/geometry_100m.rdf [L,R=301]

# Let the service provide the rdf content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_1km.rdf$ id/$1/$2/geometry_1km.rdf [L,R=301]

# Let the service provide the rdf content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_10km.rdf$ id/$1/$2/geometry_10km.rdf [L,R=301]

# Let the service provide the rdf content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100km.rdf$ id/$1/$2/geometry_100km.rdf [L,R=301]

# Let the service provide the rdf content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.rdf$ id/$1/$2/geometry.rdf [L,R=301]

# Let the service provide the rdf content for the feature
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+).rdf$ id/$1/$2.rdf [L,R=301]

# Turtle
```

```

# Let the service provide the ttf content for the geometry, resolution 100m
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100m.ttf$ id/$1/$2/geometry_100m.ttf [L,R=301]

# Let the service provide the ttf content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_1km.ttf$ id/$1/$2/geometry_1km.ttf [L,R=301]

# Let the service provide the ttf content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_10km.ttf$ id/$1/$2/geometry_10km.ttf [L,R=301]

# Let the service provide the ttf content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100km.ttf$ id/$1/$2/geometry_100km.ttf [L,R=301]

# Let the service provide the ttf content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.ttf$ id/$1/$2/geometry.ttf [L,R=301]

# Let the service provide the ttf content for the feature
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+).ttf$ id/$1/$2.ttf [L,R=301]

# GML

# Let the service provide the gml content for the geometry, resolution 100m
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100m.gml$ id/$1/$2/geometry_100m.gml [L,R=301]

# Let the service provide the gml content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d

```

```
 RewriteRule ^id/([0-4])_(\d+)_geometry_1km.gml$ id/$1/$2/geometry_1km.gml [L,R=301]

# Let the service provide the gml content for the geometry, resolution 10km
 RewriteCond %(REQUEST_FILENAME) !-f
 RewriteCond %(REQUEST_FILENAME) !-d
 RewriteRule ^id/([0-4])_(\d+)_geometry_10km.gml$ id/$1/$2/geometry_10km.gml [L,R=301]

# Let the service provide the gml content for the geometry, resolution 100km
 RewriteCond %(REQUEST_FILENAME) !-f
 RewriteCond %(REQUEST_FILENAME) !-d
 RewriteRule ^id/([0-4])_(\d+)_geometry_100km.gml$ id/$1/$2/geometry_100km.gml [L,R=301]

# Let the service provide the gml content for the geometry
 RewriteCond %(REQUEST_FILENAME) !-f
 RewriteCond %(REQUEST_FILENAME) !-d
 RewriteRule ^id/([0-4])_(\d+)_geometry.gml$ id/$1/$2/geometry.gml [L,R=301]

# SVG

# Let the service provide the svg content for the geometry, resolution 100m
 RewriteCond %(REQUEST_FILENAME) !-f
 RewriteCond %(REQUEST_FILENAME) !-d
 RewriteRule ^id/([0-4])_(\d+)_geometry_100m.svg$ id/$1/$2/geometry_100m.svg [L,R=301]

# Let the service provide the svg content for the geometry, resolution 1km
 RewriteCond %(REQUEST_FILENAME) !-f
 RewriteCond %(REQUEST_FILENAME) !-d
 RewriteRule ^id/([0-4])_(\d+)_geometry_1km.svg$ id/$1/$2/geometry_1km.svg [L,R=301]

# Let the service provide the svg content for the geometry, resolution 10km
 RewriteCond %(REQUEST_FILENAME) !-f
 RewriteCond %(REQUEST_FILENAME) !-d
 RewriteRule ^id/([0-4])_(\d+)_geometry_10km.svg$ id/$1/$2/geometry_10km.svg [L,R=301]

# Let the service provide the svg content for the geometry, resolution 100km
 RewriteCond %(REQUEST_FILENAME) !-f
 RewriteCond %(REQUEST_FILENAME) !-d
 RewriteRule ^id/([0-4])_(\d+)_geometry_100km.svg$ id/$1/$2/geometry_100km.svg [L,R=301]

# Let the service provide the svg content for the geometry
 RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.svg$ id/$1/$2/geometry.svg [L,R=301]

# KML

# Let the service provide the kml content for the geometry, resolution 100m
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100m.kml$ id/$1/$2/geometry_100m.kml [L,R=301]

# Let the service provide the kml content for the geometry, resolution 1km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_1km.kml$ id/$1/$2/geometry_1km.kml [L,R=301]

# Let the service provide the kml content for the geometry, resolution 10km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_10km.kml$ id/$1/$2/geometry_10km.kml [L,R=301]

# Let the service provide the kml content for the geometry, resolution 100km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100km.kml$ id/$1/$2/geometry_100km.kml [L,R=301]

# Let the service provide the kml content for the geometry
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.kml$ id/$1/$2/geometry.kml [L,R=301]

# KMZ

# Let the service provide the kmz content for the geometry, resolution 100m
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100m.kmz$ id/$1/$2/geometry_100m.kmz [L,R=301]

# Let the service provide the kmz content for the geometry, resolution 1km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_1km.kmz$ id/$1/$2/geometry_1km.kmz [L,R=301]

# Let the service provide the kmz content for the geometry, resolution 10km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_10km.kmz$ id/$1/$2/geometry_10km.kmz [L,R=301]

# Let the service provide the kmz content for the geometry, resolution 100km
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100km.kmz$ id/$1/$2/geometry_100km.kmz [L,R=301]
```

```
RewriteRule ^id/([0-4])_(\d+)_geometry_1km.kmz$ id/$1/$2/geometry_1km.kmz [L,R=301]

# Let the service provide the kmz content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_10km.kmz$ id/$1/$2/geometry_10km.kmz [L,R=301]

# Let the service provide the kmz content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100km.kmz$ id/$1/$2/geometry_100km.kmz [L,R=301]

# Let the service provide the kmz content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.kmz$ id/$1/$2/geometry.kmz [L,R=301]

# GeoJSON

# Let the service provide the geojson content for the geometry, resolution 100m
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100m.geojson$ id/$1/$2/geometry_100m.geojson [L,R=301]

# Let the service provide the geojson content for the geometry, resolution 1km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_1km.geojson$ id/$1/$2/geometry_1km.geojson [L,R=301]

# Let the service provide the geojson content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_10km.geojson$ id/$1/$2/geometry_10km.geojson [L,R=301]

# Let the service provide the geojson content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100km.geojson$ id/$1/$2/geometry_100km.geojson [L,R=301]

# Let the service provide the geojson content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.gejson$ id/$1/$2/geometry.gejson [L,R=301]

# Let the service provide the gejson content for the geometry, resolution 10km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_10km.gejson$ id/$1/$2/geometry_10km.gejson [L,R=301]

# Let the service provide the gejson content for the geometry, resolution 100km
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry_100km.gejson$ id/$1/$2/geometry_100km.gejson [L,R=301]

# Let the service provide the gejson content for the geometry
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) !-d
RewriteRule ^id/([0-4])_(\d+)_geometry.gejson$ id/$1/$2/geometry.gejson [L,R=301]
```