

```
# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
</IfModule>
# END WordPress

# Force PDF Download
<FilesMatch "\.(?i:pdf)$">
  ForceType application/octet-stream
  Header set Content-Disposition attachment
</FilesMatch>

#Boilerplate-----

# Apache configuration file
# httpd.apache.org/docs/2.2/mod/quickreference.html

# Note .htaccess files are an overhead, this logic should be in your Apache
# config if possible: httpd.apache.org/docs/2.2/howto/htaccess.html

# Techniques in here adapted from all over, including:
#   Kroc Camen: camendesign.com/.htaccess
#   perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
#   Sample .htaccess file of CMS MODx: modxcms.com

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # end header set to catch by content type but we don't want to send this header on www
```

```

# mod_headers can't match by content-type, but we don't want to send this header on *ever!
<FilesMatch "\.(appcache|crx|css|eot|gif|html|ico|jpe?
gl|js|m4a|m4v|manifest|mp4|oexl|ogal|oggl|ogvl|otfl|pdf|png|safariextz|svg|svgz|ttf|vcf|webm|webp|
Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# CORS-enabled images (@crossorigin)
# -----

# Send CORS headers if browsers request them; enabled by default for images.
# developer.mozilla.org/en/CORS_Enabled_Image
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    # mod_headers, y u no match by Content-Type?!
    <FilesMatch "\.(gif|ico|jpe?gl|png|svg|svgz|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

# -----
# Webfont access
..

```

```
# -----  
  
# Allow access from all domains for webfonts.  
# Alternatively you could only whitelist your  
# subdomains like "subdomain.example.com".  
  
<IfModule mod_headers.c>  
  <FilesMatch "\.(eot|font\.css|otf|ttc|ttf|woff)$">  
    Header set Access-Control-Allow-Origin "*"   
  </FilesMatch>  
</IfModule>  
  
# -----  
  
# Proper MIME type for all files  
# -----  
  
# JavaScript  
# Normalize to standard type (it's sniffed in IE anyways)  
# tools.ietf.org/html/rfc4329#section-7.2  
AddType application/javascript      js jsonp  
AddType application/json            json  
  
# Audio  
AddType audio/mp4                   m4a f4a f4b  
AddType audio/ogg                    oga ogg  
  
# Video  
AddType video/mp4                    mp4 m4v f4v f4p  
AddType video/ogg                     ogv  
AddType video/webm                     webm  
AddType video/x-flv                     flv  
  
# SVG  
# Required for svg webfonts on iPad  
# twitter.com/FontSquirrel/status/14855840545  
AddType image/svg+xml                svg svgz  
AddEncoding gzip                      svgz  
  
# Webfonts  
AddType application/vnd.ms-fontobject eot  
AddType application/x-font-ttf        ttf ttc
```

```
AddType application/x-font-woff          woff
AddType font/opentype                    otf
```

Assorted types

```
AddType application/octet-stream        safariextz
AddType application/x-chrome-extension   crx
AddType application/x-opera-extension    oex
AddType application/x-shockwave-flash    swf
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall          xpi
AddType application/xml                  rss atom xml rdf
AddType image/webp                       webp
AddType image/x-icon                     ico
AddType text/cache-manifest              appcache manifest
AddType text/vtt                         vtt
AddType text/x-component                 htc
AddType text/x-vcard                     vcf
```

```
# -----
# Allow concatenation from within specific js and css files
# -----
```

```
# e. g. Inside of script.combined.js you could have
# <!--#include file="libs/jquery-1.5.0.min.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.
```

```
# This is not in use in the boilerplate as it stands. You may
# choose to use this technique if you do not have a build process.
```

```
#<FilesMatch "\.combined\.js$">
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
#</FilesMatch>
```

```
#<FilesMatch "\.combined\.css$">
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
#</FilesMatch>
```

```

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

    # Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-bi
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\
(4,13)$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines as
    # `AddOutputFilterByType` is still in the core directives)
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
                                application/javascript \
                                application/json \
                                application/rss+xml \
                                application/vnd.ms-fontobject \
                                application/x-font-ttf \
                                application/xhtml+xml \
                                application/xml \
                                font/opentype \
                                image/svg+xml \
                                image/x-icon \
                                text/css \
                                text/html \
                                text/plain \
                                text/x-component \
                                text/xml

    </IfModule>

</IfModule>

```

```
# -----  
# Expires headers (for better cache control)  
# -----  
  
# These are pretty far-future expires headers.  
# They assume you control versioning with filename-based cache busting  
# Additionally, consider that outdated proxies may miscache  
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/  
  
# If you don't use filenames to version, lower the CSS and JS to something like  
# "access plus 1 week".  
  
<IfModule mod_expires.c>  
    ExpiresActive on  
  
# Perhaps better to whitelist expires rules? Perhaps.  
    ExpiresDefault          "access plus 1 month"  
  
# cache, appcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")  
    ExpiresByType text/cache-manifest "access plus 0 seconds"  
  
# Your document html  
    ExpiresByType text/html          "access plus 0 seconds"  
  
# Data  
    ExpiresByType application/json   "access plus 0 seconds"  
    ExpiresByType application/xml    "access plus 0 seconds"  
    ExpiresByType text/xml           "access plus 0 seconds"  
  
# Feed  
    ExpiresByType application/atom+xml "access plus 1 hour"  
    ExpiresByType application/rss+xml  "access plus 1 hour"  
  
# Favicon (cannot be renamed)  
    ExpiresByType image/x-icon       "access plus 1 week"  
  
# Media: images, video, audio  
    ExpiresByType audio/ogg           "access plus 1 month"  
    ExpiresByType image/gif          "access plus 1 month"  
    ExpiresByType image/jpeg         "access plus 1 month"  
    ExpiresByType image/png          "access plus 1 month"
```

```

ExpiresByType video/mp4                "access plus 1 month"
ExpiresByType video/ogg                 "access plus 1 month"
ExpiresByType video/webm               "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component         "access plus 1 month"

# Webfonts
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf      "access plus 1 month"
ExpiresByType application/x-font-woff    "access plus 1 month"
ExpiresByType font/opentype             "access plus 1 month"
ExpiresByType image/svg+xml            "access plus 1 month"

# CSS and JavaScript
ExpiresByType application/javascript     "access plus 1 year"
ExpiresByType text/css                   "access plus 1 year"

</IfModule>

# -----
# Prevent mobile network providers from modifying your site
# -----

# The following header prevents modification of your code over 3G on some
# European providers.
# This is the official 'bypass' suggested by O2 in the UK.

# <IfModule mod_headers.c>
# Header set Cache-Control "no-transform"
# </IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

```

```
# Since we're sending far-future expires, we don't need ETags for
# static content.
```

```
# developer.yahoo.com/performance/rules.html#etags
```

```
FileETag None
```

```
# -----
# Stop screen flicker in IE on CSS rollovers
# -----
```

```
# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above).
```

```
# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary
```

```
# -----
# Set Keep-Alive Header
# -----
```

```
# Keep-Alive allows the server to send multiple requests through one
# TCP-connection. Be aware of possible disadvantages of this setting. Turn on
# if you serve a lot of static content.
```

```
# <IfModule mod_headers.c>
# Header set Connection Keep-Alive
# </IfModule>
```

```
# -----
# Cookie setting from iframes
# -----
```

```
# Allow cookies to be set from iframes (for IE only)
# If needed, specify a path or regex in the Location directive.
```

```
# <IfModule mod_headers.c>
# Header set P3P "policyref=\"/w3c/p3p.xml\"", CP="IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
OUR IND CNT\\""
# </IfModule>
```



```
# -----  
# Start rewrite engine  
# -----  
  
# Turning on the rewrite engine is necessary for the following rules and  
# features. FollowSymLinks must be enabled for this to work.  
  
# Some cloud hosting services require RewriteBase to be set: goo.gl/H0cPM  
# If using the h5bp in a subdirectory, use `RewriteBase /foo` instead where  
# 'foo' is your directory.  
  
# If your web host doesn't allow the FollowSymLinks option, you may need to  
# comment it out and use `Options +SymLinksIfOwnerMatch`, but be aware of the  
# performance impact: http://goo.gl/Mluzd  
  
<IfModule mod_rewrite.c>  
  Options +FollowSymLinks  
  # Options +SymLinksIfOwnerMatch  
  RewriteEngine On  
  # RewriteBase /  
</IfModule>  
  
# -----  
# Suppress or force the "www." at the beginning of URLs  
# -----  
  
# The same content should never be available under two different URLs -  
# especially not with and without "www." at the beginning, since this can cause  
# SEO problems (duplicate content). That's why you should choose one of the  
# alternatives and redirect the other one.  
  
# By default option 1 (no "www.") is activated.  
# no-www.org/faq.php?q=class_b  
  
# If you'd prefer to use option 2, just comment out all option 1 lines  
# and uncomment option 2.  
  
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!  
  
# -----
```

```

# Option 1:
# Rewrite "www.example.com -> example.com".

<IfModule mod_rewrite.c>
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2:
# Rewrite "example.com -> www.example.com".
# Be aware that the following rule might not be a good idea if you use "real"
# subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\..+$ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version rewriting,
# you might want to consider enabling this, which will route requests for
# `/css/style.20110203.css` to `/css/style.css`.

# To understand why this is important and a better idea than all.css?v1231,
# please refer to the bundled documentation about `.htaccess`.

# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(.+)\.(.+)\.(js|css|png|jpg|gif)$ $1.$3 [L]
# </IfModule>

# -----
# Prevent CSS asset updates

```



```
# A little more security
# -----

# To avoid displaying the exact version number of Apache being used, add the
# following to httpd.conf (it will not work in .htaccess):
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a
# default document. Usually you should leave this activated, because you
# shouldn't allow everybody to surf through every folder on your server (which
# includes rather private places like CMS system folders).
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a
# period. This includes directories used by version control systems such as
# Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [F]
</IfModule>

# Block access to backup and source files. These files may be left by some
# text/html editors and pose a great security danger, when anyone can access
# them.
<FilesMatch "(\\. (bak|config|dist|fla|incl|ini|log|psd|shl|sql|swp)|")$" >
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS:
#
# Your server does not allow PHP directives to be set via .htaccess. In that
```

```
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Rename session cookie to something else, than PHPSESSID
# php_value session.name sid

# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of )
# php_flag magic_quotes_gpc Off

# Do not show you are using PHP
# Note: Move this line to php.ini since it won't work in .htaccess
# php_flag expose_php Off

# Level of log detail - log all errors
# php_value error_reporting -1

# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off
```

```
# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule mod_php5.c>
    php_value session.cookie_httponly true
</IfModule>
```