

### #禁止下载

```
<FilesMatch "\.  
(engine|incl|info|install|lang|module|profile|test|pol|sh|. *sql|theme|tpl(\. php)?|x|tmp|svn-  
base)$|^(\code-style|. pl|Entries. *| Repository| Root| Tag| Template| all-  
wc|props| entries| format)$">  
    Order allow,deny  
</FilesMatch>
```

### # PHP 设置

```
<IfModule mod_php5.c>  
    php_flag magic_quotes_gpc                off  
    php_flag magic_quotes_sybase            off  
    php_flag register_globals                off  
    php_flag session.auto_start             off  
    php_value mbstring.http_input           pass  
    php_value mbstring.http_output          pass  
    php_value mbstring.internal_encoding    utf-8  
    php_flag mbstring.encoding_translation  off  
</IfModule>
```

### #重写规则

```
Options +FollowSymLinks
```

### #默认404页面

```
ErrorDocument 404 /index.php
```

### #默认首页

```
DirectoryIndex index.php
```

### #设置 header 缓存过期时间

```
<IfModule mod_expires.c>  
    ExpiresActive On  
    ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
    # php 文件例外
```

```
    ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

*# 返回压缩*

```
<IfModule mod_deflate.c>
    AddOutputFilterByType DEFLATE text/html text/plain text/xml application/x-httpd-php
    AddOutputFilter DEFLATE js css
</IfModule>
```

*# 伪静态化*

```
<IfModule mod_rewrite.c>
    RewriteEngine on

    # 以下两种方式不能同时启用
    # 使用 www 访问，未加 www 前缀的访问将跳转
    # RewriteCond %{HTTP_HOST} !^www\. [NC]
    # RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [L,R=301]
    #
    # 不使用 www 前缀，以 www 前缀的访问将跳转
    # RewriteCond %{HTTP_HOST} ^www\. (.+)$ [NC]
    # RewriteRule ^ http://%1%{REQUEST_URI} [L,R=301]

    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteCond %{REQUEST_URI} !=/favicon.ico
    RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>
```