

```

# Apache Server Configs v2.1.0 | MIT License
# https://github.com/h5bp/server-configs-apache

# (!) Using `.htaccess` files slows down Apache, therefore, if you have access
# to the main server config file (usually called `httpd.conf`), you should add
# this logic there: http://httpd.apache.org/docs/current/howto/htaccess.html.

# #####
# # CROSS-ORIGIN RESOURCE SHARING (CORS) #
# #####

# -----
# | Cross-domain AJAX requests |
# -----

# Enable cross-origin AJAX requests.
# http://code.google.com/p/html5security/wiki/CrossOriginRequestSecurity
# http://enable-cors.org/

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# | CORS-enabled images |
# -----

# Send the CORS header for images when browsers request it.
# https://developer.mozilla.org/en-US/docs/HTML/CORS_Enabled_Image
# http://blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# http://hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    <FilesMatch "\.(curl|gif|icol|jpe?g|png|svgz?|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

```

```
# -----
# | Web fonts access |
# -----
```

*# Allow access from all domains for web fonts*

```
<IfModule mod_headers.c>
  <FilesMatch "\.(eot|otf|ttc|ttf|woff)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>
```

```
# #####
# # ERRORS #
# #####
```

```
# -----
# | 404 error prevention for non-existing redirected folders |
# -----
```

*# Prevent Apache from returning a 404 error for a rewrite if a directory  
# with the same name does not exist.  
# <http://httpd.apache.org/docs/current/content-negotiation.html#multiviews>  
# <http://www.webmasterworld.com/apache/3808792.htm>*

## Options -MultiViews

```
# -----
# | Custom error messages / pages |
# -----
```

*# You can customize what Apache returns to the client in case of an error (see  
# <http://httpd.apache.org/docs/current/mod/core.html#errordocument>).*

ErrorDocument 404 /404.html

```
# #####
# # INTERNET EXPLORER #
# #####
```

```

# -----
# | Better website experience |
# -----

# Force IE to render pages in the highest available mode in the various
# cases when it may not: http://hsivonen.iki.fi/doctype/ie-mode.pdf.

<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge"
    # `mod_headers` can't match based on the content-type, however, we only
    # want to send this header for HTML pages and not for the other resources
    <FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|ico|jpe?
gl|jst|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogv|opus|otf|pdf|png|safariextz|svgz?
|ttf|vcf|webapp|webm|webpl|woff|xml|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# -----
# | Cookie setting from iframes |
# -----

# Allow cookies to be set from iframes in IE.
# http://msdn.microsoft.com/en-us/library/ms537343.aspx
# http://www.w3.org/TR/2000/CR-P3P-20001215/

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
CONi HIS OUR IND CNT\""
# </IfModule>

# #####
# # MIME TYPES AND ENCODING #
# #####

# -----
# | Proper MIME types for all files |
# -----

<IfModule mod_mime.c>

```

```

# Audio
AddType audio/mp4          m4a f4a f4b
AddType audio/ogg          oga ogg opus

# Data interchange
AddType application/json   json map

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways):
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript  js

# Video
AddType video/mp4          f4v f4p m4v mp4
AddType video/ogg          ogv
AddType video/webm         webm
AddType video/x-flv        flv

# Web fonts
AddType application/font-woff          woff
AddType application/vnd.ms-fontobject eot

# Browsers usually ignore the font MIME types and sniff the content,
# however, Chrome shows a warning if other MIME types are used for the
# following fonts.
AddType application/x-font-ttf          ttc ttf
AddType font/opentype                   otf

# Make SVGZ fonts work on iPad:
# https://twitter.com/FontSquirrel/status/14855840545
AddType    image/svg+xml                svgz
AddEncoding gzip                        svgz

# Other
AddType application/octet-stream        safariextz
AddType application/x-chrome-extension  crx
AddType application/x-opera-extension   oex
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall         xpi
AddType application/xml                  atom rdf rss xml
AddType image/webp                       webp

```

```

AddType image/x-icon                cur
AddType text/cache-manifest         appcache manifest
AddType text/vtt                    vtt
AddType text/x-component             htc
AddType text/x-vcard                vcf

</IfModule>

# -----
# | UTF-8 encoding |
# -----

# Use UTF-8 encoding for anything served as `text/html` or `text/plain`.
AddDefaultCharset utf-8

# Force UTF-8 for certain file formats.
<IfModule mod_mime.c>
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
</IfModule>

# #####
# # URL REWRITES #
# #####

# -----
# | Rewrite engine |
# -----

# Turning on the rewrite engine and enabling the `FollowSymLinks` option is
# necessary for the following directives to work.

# If your web host doesn't allow the `FollowSymLinks` option, you may need to
# comment it out and use `Options +SymLinksIfOwnerMatch` but, be aware of the
# performance impact: http://httpd.apache.org/docs/current/misc/perf-tuning.html#symlinks

# Also, some cloud hosting services require `RewriteBase` to be set:
# http://www.rackspace.com/knowledge\_center/frequently-asked-question/why-is-mod-rewrite-not-working-on-my-site

<IfModule mod_rewrite.c>
    Options +FollowSymLinks

```

```
# Options +SymLinksIfOwnerMatch
RewriteEngine On
# RewriteBase /
</IfModule>

# -----
# | Suppressing / Forcing the "www." at the beginning of URLs |
# -----

# The same content should never be available under two different URLs especially
# not with and without "www." at the beginning. This can cause SEO problems
# (duplicate content), therefore, you should choose one of the alternatives and
# redirect the other one.

# By default option 1 (no "www.") is activated:
# http: //no-www. org/faq. php?q=class_b

# If you'd prefer to use option 2, just comment out all the lines from option 1
# and uncomment the ones from option 2.

# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----

# Option 1: rewrite www. example. com → example. com

<IfModule mod_rewrite. c>
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(. +)$ [NC]
    RewriteRule ^ http: //%1%(REQUEST_URI) [R=301,L]
</IfModule>

# -----

# Option 2: rewrite example. com → www. example. com

# Be aware that the following might not be a good idea if you use "real"
# subdomains for certain parts of your website.

# <IfModule mod_rewrite. c>
#     RewriteCond %{HTTPS} !=on
```

```
# RewriteCond %{HTTP_HOST} !^www\. [NC]
# RewriteCond %{SERVER_ADDR} !=127.0.0.1
# RewriteCond %{SERVER_ADDR} !=::1
# RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

#####
# # SECURITY #
# #####

# -----
# | Clickjacking |
# -----

# Protect web site against clickjacking.

# The example below sends the `X-Frame-Options` response header with the value
# `DENY`, informing browsers not to display the web page content in any frame.

# This might not be the best setting for everyone. You should read about the
# other two possible values for `X-Frame-Options`: `SAMEORIGIN` and `ALLOW-FROM`
# http://tools.ietf.org/html/rfc7034#section-2.1.

# Keep in mind that while you could send the `X-Frame-Options` header for all
# of your site's pages, this has the potential downside that it forbids even
# non-malicious framing of your content (e.g.: when users visit your site using
# a Google Image Search results page).

# Nonetheless, you should ensure that you send the `X-Frame-Options` header for
# all pages that allow a user to make a state changing operation (e.g: pages
# that contain one-click purchase links, checkout or bank-transfer confirmation
# pages, pages that make permanent configuration changes, etc.).

# Sending the `X-Frame-Options` header can also protect your web site against
# more than just clickjacking attacks: https://cure53.de/xfo-clickjacking.pdf.

# http://tools.ietf.org/html/rfc7034
# http://blogs.msdn.com/b/ieinternals/archive/2010/03/30/combating-clickjacking-with-x-frame-options.aspx
# https://www.owasp.org/index.php/Clickjacking
```

```
# <IfModule mod_headers.c>
#   Header set X-Frame-Options "DENY"
#   <FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|icol|jpe?
gl|js|m4a|m4v|manifest|mp4|oex|ogal|ogg|ogv|opus|otf|pdf|png|safari-ext|svgz?
|ttf|vcf|webapp|webm|webp|woff|xml|xpi)$">
#       Header unset X-Frame-Options
#   </FilesMatch>
# </IfModule>

# -----
# | Content Security Policy (CSP) |
# -----

# You can mitigate the risk of cross-site scripting and other content-injection
# attacks by setting a Content Security Policy which whitelists trusted sources
# of content for your site.

# The example header below allows ONLY scripts that are loaded from the current
# site's origin (no inline scripts, no CDN, etc). This almost certainly won't
# work as-is for your site!

# For more details on how to craft a reasonable policy for your site, read:
# http://html5rocks.com/en/tutorials/security/content-security-policy (or the
# specification: http://w3.org/TR/CSP). Also, to make things easier, you can
# use an online CSP header generator such as: http://cspisawesome.com/.

# <IfModule mod_headers.c>
#   Header set Content-Security-Policy "script-src 'self'; object-src 'self'"
#   <FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|icol|jpe?
gl|js|m4a|m4v|manifest|mp4|oex|ogal|ogg|ogv|opus|otf|pdf|png|safari-ext|svgz?
|ttf|vcf|webapp|webm|webp|woff|xml|xpi)$">
#       Header unset Content-Security-Policy
#   </FilesMatch>
# </IfModule>

# -----
# | File access |
# -----

# Block access to directories without a default document.
# Usually you should leave this uncommented because you shouldn't allow anyone
```



```
-----
# to surf through every directory on your server (which may includes rather
# private places like the CMS's directories).

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# -----

# Block access to hidden files and directories.
# This includes directories used by version control systems such as Git and SVN.

<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [F]
</IfModule>

# -----

# Block access to backup and source files.
# These files may be left by some text editors and can pose a great security
# danger when anyone has access to them.

<FilesMatch "(^#. *#| \.(bak|config|dist|fla|incl|ini|log|psd|sh|sql|sw[op])| (^)$">

    # Apache < 2.3
    <IfModule !mod_authz_core.c>
        Order allow,deny
        Deny from all
        Satisfy All
    </IfModule>

    # Apache ≥ 2.3
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>

</FilesMatch>

# -----
```

```
" -----
# | Reducing MIME-type security risks |
# -----

# Prevent some browsers from MIME-sniffing the response.

# This reduces exposure to drive-by download attacks and should be enable
# especially if the web server is serving user uploaded content, content
# that could potentially be treated by the browser as executable.

# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-v-comprehensive-protection
# http://msdn.microsoft.com/en-us/library/ie/gg622941.aspx
# http://mimesniff.spec.whatwg.org/

# <IfModule mod_headers.c>
#     Header set X-Content-Type-Options "nosniff"
# </IfModule>

# -----
# | Reflected Cross-Site Scripting (XSS) attacks |
# -----

# (1) Try to re-enable the Cross-Site Scripting (XSS) filter built into the
#     most recent web browsers.
#
#     The filter is usually enabled by default, but in some cases it may be
#     disabled by the user. However, in IE for example, it can be re-enabled
#     just by sending the `X-XSS-Protection` header with the value of `1`.
#
# (2) Prevent web browsers from rendering the web page if a potential reflected
#     (a.k.a. a non-persistent) XSS attack is detected by the filter.
#
#     By default, if the filter is enabled and browsers detect a reflected
#     XSS attack, they will attempt to block the attack by making the smallest
#     possible modifications to the returned web page.
#
#     Unfortunately, in some browsers (e.g.: IE), this default behavior may
#     allow the XSS filter to be exploited, thereby, it's better to tell
#     browsers to prevent the rendering of the page altogether, instead of
#     attempting to modify it.
#
#     http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-v-comprehensive-protection
```

```

# http://nackademix.net/2009/11/21/ie8-xss-filter-creates-xss-vulnerabilities
#
# IMPORTANT: Do not rely on the XSS filter to prevent XSS attacks! Ensure that
# you are taking all possible measures to prevent XSS attacks, the most obvious
# being: validating and sanitizing your site's inputs.

# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-iv-the-xss-filter.aspx
# http://blogs.msdn.com/b/ieinternals/archive/2011/01/31/controlling-the-internet-explorer-;
filter-with-the-x-xss-protection-http-header.aspx
# https://www.owasp.org/index.php/Cross-site_Scripting_%28XSS%29

# <IfModule mod_headers.c>
#     # (1) (2)
#     Header set X-XSS-Protection "1; mode=block"
#     <FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|ico|jpe?
gl|js|m4a|m4v|manifest|mp4|oex|ogal|ogg|ogv|opus|otf|pdf|png|safariextz|svgz?
|ttf|vcf|webapp|webml|webpl|woff|xml|xpi)$">
#         Header unset X-XSS-Protection
#     </FilesMatch>
# </IfModule>

# -----
# | Secure Sockets Layer (SSL) |
# -----

# Rewrite secure requests properly to prevent SSL certificate warnings, e.g.:
# prevent `https://www.example.com` when your certificate only allows
# `https://secure.example.com`.

# <IfModule mod_rewrite.c>
#     RewriteCond %{SERVER_PORT} !^443
#     RewriteRule ^ https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# | HTTP Strict Transport Security (HSTS) |
# -----

# Force client-side SSL redirection.

# If a user types "example.com" in his browser, the above rule will redirect
"

```

```
# him to the secure version of the site. That still leaves a window of oppor-
# tunity (the initial HTTP connection) for an attacker to downgrade or redirect
# the request. The following header ensures that browser will ONLY connect to
# your server via HTTPS, regardless of what the users type in the address bar.
# http://tools.ietf.org/html/draft-ietf-websec-strict-transport-sec-14#section-6.1
# http://www.html5rocks.com/en/tutorials/security/transport-layer-security/
```

```
# (!) Remove the `includeSubDomains` optional directive if the subdomains are
# not using HTTPS.
```

```
# <IfModule mod_headers.c>
#   Header set Strict-Transport-Security "max-age=16070400; includeSubDomains"
# </IfModule>
```

```
# -----
# | Server software information |
# -----
```

```
# Avoid displaying the exact Apache version number, the description of the
# generic OS-type and the information about Apache's compiled-in modules.
```

```
# ADD THIS DIRECTIVE IN THE `httpd.conf` AS IT WILL NOT WORK IN THE `.htaccess`!
```

```
# ServerTokens Prod
```

```
# #####
# # WEB PERFORMANCE #
# #####
```

```
# -----
# | Compression |
# -----
```

```
<IfModule mod_deflate.c>
```

```
    # Force compression for mangled headers.
```

```
    # http://developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping
```

```
    <IfModule mod_setenvif.c>
```

```
        <IfModule mod_headers.c>
```

```
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
```

```
            ^((gzip|deflate)\s*,\s*\?|s*)+ [X"-] {4,13}$ HAVE_Accept-Encoding
```

```

RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        text/xml

</IfModule>

</IfModule>

# -----
# | Content transformations |
# -----

# Prevent some of the mobile network providers from modifying the content of
# your site: http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9.5.

# <IfModule mod_headers.c>
#     Header set Cache-Control "no-transform"
# </IfModule>

```

```
# -----
# | ETag removal |
# -----

# Since we're sending far-future expires headers (see below), ETags can
# be removed: http://developer.yahoo.com/performance/rules.html#etags.

# `FileETag None` is not enough for every server.
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>

FileETag None

# -----
# | Expires headers (for better cache control) |
# -----

# The following expires headers are set pretty far in the future. If you don't
# control versioning with filename-based cache busting, consider lowering the
# cache time for resources like CSS and JS to something like 1 week.

<IfModule mod_expires.c>

    ExpiresActive on
    ExpiresDefault "access plus 1 month"

    # CSS
    ExpiresByType text/css "access plus 1 year"

    # Data interchange
    ExpiresByType application/json "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType text/xml "access plus 0 seconds"

    # Favicon (cannot be renamed!) and cursor images
    ExpiresByType image/x-icon "access plus 1 week"

    # HTML components (HTCs)
    ExpiresByType text/x-component "access plus 1 month"
```

```

# HTML
ExpiresByType text/html "access plus 0 seconds"

# JavaScript
ExpiresByType application/javascript "access plus 1 year"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# Web feeds
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"

```

```
</IfModule>
```

```

# -----
# | Filename-based cache busting |
# -----

```

```

# If you're not using a build process to manage your filename version revving,
# you might want to consider enabling the following directives to route all
# requests such as /css/style.12345.css to /css/style.css.

```

```

# To understand why this is important and a better idea than *.css?v231, read:

```

```
# http://stevesouders.com/blog/2008/08/23/rewriting-filenames-dont-use-querystring

# <IfModule mod_rewrite.c>
#     RewriteCond %{REQUEST_FILENAME} !-f
#     RewriteRule ^(.+)?\.(.+)$ $1.$2 [L]
# </IfModule>

# -----
# | File concatenation |
# -----

# Allow concatenation from within specific CSS and JS files, e.g.:
# Inside of `script.combined.js` you could have
# <!--#include file="libs/jquery.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# <IfModule mod_include.c>
#     <FilesMatch "\.combined\.js$">
#         Options +Includes
#         AddOutputFilterByType INCLUDES application/javascript application/json
#         SetOutputFilter INCLUDES
#     </FilesMatch>
#     <FilesMatch "\.combined\.css$">
#         Options +Includes
#         AddOutputFilterByType INCLUDES text/css
#         SetOutputFilter INCLUDES
#     </FilesMatch>
# </IfModule>

# -----
# | Persistent connections |
# -----

# Allow multiple requests to be sent over the same TCP connection:
# http://httpd.apache.org/docs/current/en/mod/core.html#keepalive.

# Enable if you serve a lot of static content but, be aware of the
# possible disadvantages!

# <IfModule mod_headers.c>
```



```

# Header set Connection Keep-Alive
# </IfModule>

#####
# # MOBILE SPECIFIC #
#####

# Proper MIME types

<IfModule mod_mime.c>

# Blackberry
# http://docs.blackberry.com/en/developers/deliverables/18169/
AddType application/x-bb-appworld          bbaw
AddType text/vnd.rim.location.xloc         xloc

# Nokia
#
# http://www.developer.nokia.com/Community/Wiki/Apache_configuration_for_mobile_application_development
#
# http://wiki.forum.nokia.com/index.php/How_to_enable_OTA_(Over_The_Air)_SIS_install_from_your_device
AddType application/octet-stream          six
AddType application/vnd.symbian.install   sis

</IfModule>

# -----

# Prevent mobile transcoding

# <FilesMatch "\.(php|cgi|pl)$">
#   <IfModule mod_headers.c>
#     Header append Cache-Control "no-transform"
#     Header append Vary "User-Agent, Accept"
#   </IfModule>
# </FilesMatch>

# -----

# Mobile Redirection Script is used to detect if user is viewing the site from
# mobile device. If the script detects the user is viewing from mobile phone.

```

```
#####
# they will be redirected to the mobile version of the site. One thing to note
# is that if you want to allow the user on the mobile version of your site to
# have the option to switch to desktop version, you may consider using other
# methods like JavaScript or PHP at http://detectmobilebrowser.com/.
#
# To use the script, first, uncomment the lines below, and second, change
# 'http://www.example.com/mobile' to the URL of your mobile site.

# <IfModule mod_rewrite.c>
#     RewriteEngine On
#     RewriteBase /
#     RewriteCond %{HTTP_USER_AGENT}
android|avantgo|blackberry|blazer|compal|elaine|fennec|hiptop|iemobile|ip(hone|od)|iris|kin
|maemo|mipd|mmp|opera\ m(ob|in)i|palm(\ os)?|phone|p(ixi|re)\|plucker|pocket|psp|symbi|t(
|browser|link)|vodafone|wap|windows\ (cel|phone)|xda|xiino [NC,OR]
#RewriteCond %{HTTP_USER_AGENT} ^(1207|6310|6590|3gso|4thp|50[1-6]|i[ ]770s|802s|a\
wal|abacl|ac(er|ool|s)-
)|ai(kol|rn)|al(av|cal|co)|amoi|an(ex|nyl|yw)|aptu|ar(ch|go)|as(tel|us)|attw|au(dil|-ml|r)|ls
)|avani|be(ckl|ll|nq)|bi(1bl|rd)|bl(ack|az)|br(el|v)w|bumbl|bu\-(nl|u)|c55\|capil|ccwal|cdm\
|cell|chtml|cl|dcl|cmd\|-|co(mpl|nd)|crawl|da(it|ll|ng)|dbtel|dc\|-|devil|di|cal|dmobl|do(cl|p)|ds(12|
d)|el(49|ai)|em(12|ul)|er(ic|k0)|esl8|ez([4-7]0|osl|wal|ze)|fetcl|fly(\|-_|)g1\|ul|g560|genel|gf
|mol|go(\.|ul|od)|gr(ad|un)|hai|el|hc|ti|hd\-(ml|pl|t)|hei\|-|hi(pt|ta)|hp(\|il|ip)|hs\|-cl|ht(c\|-|
|_|)al|gl|pl|sl|t)|tp|hu(aw|tc)|i\-(20|gol|ma)|i230|iac(\| |)
| |)\|ibrol|ideal|ig01|i|kom|i|m1|k|innol|ipaql|iris|ja(tl|v)al|jbrol|jemul|jigsl|kddil|ke|jil|kgt(\| |)\|k|
|kuc\|-|kyo(cl|k)|le(nol|xi)|lg(\|gl|\|(kl|ll|u)|50|54|e\|-|e\| \|-[a-w])|libul|lynxl|m1\
|ul|m3gal|m50\|ma(tel|uil|x)|mc(01|21|ca)|m\-crl|me(dil|rc|ri)|mi(o|oal|ts)|mnefl|mo(01|02|bil|del|
|ol|v)|zz|mt(50|p1|v\|)|mubpl|mywal|n10[0-2]|n20[2-3]|n30(0|2)|n50(0|2|5)|n7(0(0|1)|10)|ne((cl
|onl|tfl|wfl|wgl|wt)|nok(6|i)|nzphl|o2i|ml|op(til|uv)|oranl|owg1|p800|pan(al|dl|t)|pdxgl|pg(13|\|[1-
8]|c))|phi1|pirel|pl(ayl|uc)|pn\|-2|po(ckl|rtl|se)|proxl|psi|ol|pt\|-gl|qa\|-al|qc(07|12|21|32|60|\|[2-
)|qtekl|r380|r600|raksl|rim9|ro(vel|zo)|s55\|sa(gel|mal|mml|msl|nyl|va)|sc(01|h\|-|ool|p\|-)|sdk\|se
|l0|1)|47l|mcl|ndl|ri)|sgh\|-|sharl|sie(\|-|m)|sk\|-0|sl(45|id)|sm(a|ll|arl|b3|itl|t5)|so(ftl|ny)|sp(01|)
|v\|)|sy(01|mb)|t2(18|50)|t6(00|10|18)|ta(gt|lk)|tcl\|-|tdg\|-|tel(il|m)|tim\|-|t\
|mol|to(p1l|sh)|ts(70|m\|-|m3|m5)|tx\|-9|up(\.|bl|g1|si)|utstl|v400|v750|veril|vi(rgl|te)|vk(40|5[0-3
v)|vm40|vodal|vu|cl|vx(52|53|60|61|70|80|81|83|85|98)|w3c(\|-| |)|webcl|whi|tl|wi(g\
|ncl|nu)|wm1bl|wonul|x700|xda(\|-|2|g)|yas\|-|yourl|zetol|zte\|-) [NC]
#     RewriteRule ^$ http://www.example.com/mobile [R,L]
# </IfModule>
```