

```
# Apache configuration file
# httpd.apache.org/docs/2.2/mod/quickreference.html

# Note .htaccess files are an overhead, this logic should be in your Apache
# config if possible: http://httpd.apache.org/docs/2.2/howto/htaccess.html

# Techniques in here adapted from all over, including:
#   Kroc Camen: camendesign.com/.htaccess
#   perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
#   Sample .htaccess file of CMS MODx: modx.com

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *ever!
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|oggl|m4al|ogvl|mp4l|m4vl|webml|svg|svgz|eotl|ttfl|otfl|woff|icol|webpl|appcache|manifest|
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>
```

```

# -----
# CORS-enabled images (@crossorigin)
# -----

# Send CORS headers if browsers request them; enabled by default for images.
# developer.mozilla.org/en/CORS_Enabled_Image
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    # mod_headers, y u no match by Content-Type?!
    <FilesMatch "\.(gif|png|jpe?g|svg|svgz|ico|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

<IfModule mod_headers.c>
  <FilesMatch "\.(ttf|ttc|otf|eot|woff|font.css)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
"application/javascript" <!--

```

*# tools.ietf.org/html/rfc4329#section-7.2*

AddType application/javascript js jsonp  
AddType application/json json

*# Audio*

AddType audio/ogg oga ogg  
AddType audio/mp4 m4a f4a f4b

*# Video*

AddType video/ogg ogv  
AddType video/mp4 mp4 m4v f4v f4p  
AddType video/webm webm  
AddType video/x-flv flv

*# SVG*

*# Required for svg webfonts on iPad*

*# twitter.com/FontSquirrel/status/14855840545*

AddType image/svg+xml svg svgz  
AddEncoding gzip svgz

*# Webfonts*

AddType application/vnd.ms-fontobject eot  
AddType application/x-font-ttf ttf ttc  
AddType font/opentype otf  
AddType application/x-font-woff woff

*# Assorted types*

AddType image/x-icon ico  
AddType image/webp webp  
AddType text/cache-manifest appcache manifest  
AddType text/x-component htc  
AddType application/xml rss atom xml rdf  
AddType application/x-chrome-extension crx  
AddType application/x-opera-extension oex  
AddType application/x-xpinstall xpi  
AddType application/octet-stream safariextz  
AddType application/x-web-app-manifest+json webapp  
AddType text/x-vcard vcf  
AddType application/x-shockwave-flash swf  
AddType text/vtt vtt

```

# -----
# Allow concatenation from within specific js and css files
# -----

# e. g. Inside of script.combined.js you could have
# <!--#include file="libs/jquery-1.5.0.min.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# This is not in use in the boilerplate as it stands. You may
# choose to use this technique if you do not have a build process.

#<FilesMatch "\.combined\.js$"
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
#</FilesMatch>

#<FilesMatch "\.combined\.css$"
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
#</FilesMatch>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

# Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-bi
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$ ^((gzip|deflate)\
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
<IfModule mod_filter.c>

```

```
AddOutputFilterByType DEFLATE application/atom+xml \
                        application/javascript \
                        application/json \
                        application/rss+xml \
                        application/vnd.ms-fontobject \
                        application/x-font-ttf \
                        application/xhtml+xml \
                        application/xml \
                        font/opentype \
                        image/svg+xml \
                        image/x-icon \
                        text/css \
                        text/html \
                        text/plain \
                        text/x-component \
                        text/xml

</IfModule>

</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week".

<IfModule mod_expires.c>
    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault          "access plus 1 month"

    # cache, apache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
    ExpiresByType text/cache-manifest "access plus 0 seconds"
```

```
# Your document html
ExpiresByType text/html "access plus 0 seconds"

# Data
ExpiresByType text/xml "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"

# Feed
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 week"

# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"

</IfModule>
```

```
# -----
```

```
# Prevent mobile network providers from modifying your site
# -----

# The following header prevents modification of your code over 3G on some
# European providers.
# This is the official 'bypass' suggested by O2 in the UK.

# <IfModule mod_headers.c>
# Header set Cache-Control "no-transform"
# </IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above).

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
# Set Keep-Alive Header
# -----
```

```
# Keep-Alive allows the server to send multiple requests through one
# TCP-connection. Be aware of possible disadvantages of this setting. Turn on
# if you serve a lot of static content.

# <IfModule mod_headers.c>
#   Header set Connection Keep-Alive
# </IfModule>

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, specify a path or regex in the Location directive.

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\"", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
# </IfModule>

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and
# features. FollowSymLinks must be enabled for this to work.

# Some cloud hosting services require RewriteBase to be set: goo.gl/H0cPN
# If using the h5bp in a subdirectory, use `RewriteBase /foo` instead where
# 'foo' is your directory.

# If your web host doesn't allow the FollowSymLinks option, you may need to
# comment it out and use `Options +SymLinksIfOwnerMatch`, but be aware of the
# performance impact: http://goo.gl/Mluzd

<IfModule mod_rewrite.c>
    Options +FollowSymLinks
# Options +SymLinksIfOwnerMatch
    RewriteEngine On
# RewriteBase /
</IfModule>
```



```
# -----  
# Suppress or force the "www." at the beginning of URLs  
# -----  
  
# The same content should never be available under two different URLs -  
# especially not with and without "www." at the beginning, since this can cause  
# SEO problems (duplicate content). That's why you should choose one of the  
# alternatives and redirect the other one.  
  
# By default option 1 (no "www.") is activated.  
# no-www.org/faq.php?q=class_b  
  
# If you'd prefer to use option 2, just comment out all option 1 lines  
# and uncomment option 2.  
  
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!  
  
# -----  
  
# Option 1:  
# Rewrite "www.example.com -> example.com".  
  
<IfModule mod_rewrite.c>  
  RewriteCond %{HTTPS} !=on  
  RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]  
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]  
</IfModule>  
  
# -----  
  
# Option 2:  
# Rewrite "example.com -> www.example.com".  
# Be aware that the following rule might not be a good idea if you use "real"  
# subdomains for certain parts of your website.  
  
# <IfModule mod_rewrite.c>  
#   RewriteCond %{HTTPS} !=on  
#   RewriteCond %{HTTP_HOST} !^www\..+$ [NC]  
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]  
# </IfModule>
```

```

# -----
# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version rewving,
# you might want to consider enabling this, which will route requests for
# /css/style.20110203.css to /css/style.css

# To understand why this is important and a better idea than all.css?v1231,
# read: github.com/h5bp/html5-boilerplate/wiki/cachebusting

# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1.$3 [L]
# </IfModule>

# -----
# Prevent SSL cert warnings
# -----

# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.example.com when your cert only allows https://secure.example.com

# <IfModule mod_rewrite.c>
#   RewriteCond %{SERVER_PORT} !^443
#   RewriteRule ^https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Prevent 404 errors for non-existing redirected folders
# -----

# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the
# same name does not exist.
# webmasterworld.com/apache/3808792.htm

```

## Options -MultiViews

```

# -----
# Option 404 -----

```

```
# Custom 404 page
# -----

# You can add custom pages to handle 500 or 403 pretty easily, if you like.
# If you are hosting your site in subdirectory, adjust this accordingly
#   e.g. ErrorDocument 404 /subdir/404.html
ErrorDocument 404 /404.html

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml

# -----
# A little more security
# -----

# To avoid displaying the exact version number of Apache being used, add the
# following to httpd.conf (it will not work in .htaccess):
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a
# default document. Usually you should leave this activated, because you
# shouldn't allow everybody to surf through every folder on your server (which
# includes rather private places like CMS system folders).
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a
# period. This includes directories used by version control systems such as
# Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
```

```
</IfModule>
```

```
# Block access to backup and source files. These files may be left by some  
# text/html editors and pose a great security danger, when anyone can access  
# them.
```

```
<FilesMatch "(\\. (bak| config| sql| fl| psd| ini| log| sh| incl| swp| dist)|\\.*)">
```

```
    Order allow,deny
```

```
    Deny from all
```

```
    Satisfy All
```

```
</FilesMatch>
```

```
# If your server is not already configured as such, the following directive  
# should be uncommented in order to set PHP's register_globals option to OFF.  
# This closes a major security hole that is abused by most XSS (cross-site  
# scripting) attacks. For more information: http://php.net/register\_globals  
#
```

```
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS:
```

```
#
```

```
# Your server does not allow PHP directives to be set via .htaccess. In that  
# case you must make this change in your php.ini file instead. If you are  
# using a commercial web host, contact the administrators for assistance in  
# doing this. Not all servers allow local php.ini files, and they should  
# include all PHP configurations (not just this one), or you will effectively  
# reset everything to PHP defaults. Consult www.php.net for more detailed  
# information about setting PHP directives.
```

```
# php_flag register_globals Off
```

```
# Rename session cookie to something else, than PHPSESSID
```

```
# php_value session.name sid
```

```
# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of )
```

```
# php_flag magic_quotes_gpc Off
```

```
# Do not show you are using PHP
```

```
# Note: Move this line to php.ini since it won't work in .htaccess
```

```
# php_flag expose_php Off
```

```
# Level of log detail - log all errors
```

```
# php_value error_reporting -1
```

```
# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

RewriteEngine On
RewriteCond %{QUERY_STRING} (.*)|(http|https|ftp):/(.*)
RewriteRule ^(.+)$ - [F,L]

# -----
# FRONT END
# -----
RewriteRule ^welcome$ index.php?act=pages.
```

```

# -----
# SHOP
# -----
#RewriteRule ^shop-all$ index.php?act=shop_
RewriteRule ^shop-all$ index.php?act=shop_/_
RewriteRule ^shop/(.*)$ index.php?act=shop/_/_shop&shop_
RewriteRule ^shop-filter/(.*)/(.*)$ index.php?act=shop/_/_shop
RewriteRule ^shop-view/(.*)/(.*)/(.*)/(.*)/(.*)$ index.php?
act=shop/_/_shop&shop_cat_id=$1&shop_filter=$2&shop_sort=$3&shop_page=$4&shop_view=$5 [B]
#RewriteRule ^shop-by-(.*)/(.*)$ index.php?act=shop_/_
#RewriteRule ^shop-by-(.*)/(.*)$ index.php?act=shop_/_
RewriteRule ^item/(.*)/(.*)/(.*)$ index.php?
act=shop/_/details/_/details&prod_cat=$1&prod_name=$2&prod_type=$3

# RewriteRule ^shop-view/(.*)-(.*)/(.*)$ index.php?act=
(shop)/index&shop_cat=$1&shop_sort=$2&shop_record=$3
# RewriteRule ^item/(.*)-type-(.*)$ index.php?act=
(shop)/details&shop_detail_alias=$1&shop_detail_tname=$2
# RewriteRule ^shop-search/name-(.*)$ index.php?act=(shop.
# RewriteRule ^add-to-bag$ index.php?act=(shop.

# -----
# SEARCH
# -----
RewriteRule ^shop-all$ index.php?act=shop_
RewriteRule ^search-(.*)/(.*)$ index.php?act=shop_/_
RewriteRule ^filter-search-(.*)/(.*)/(.*)$ index.php?
act=shop/_/_search&key=$1&shop_cat_id=$2&filter=$3 [B]

# -----
# NEW ARRIVAL
# -----
RewriteRule ^new-arrival$ index.php?act=shop_/_
RewriteRule ^new-arrival/(.*)$ index.php?act=shop_/_
RewriteRule ^new-arrival-filter/(.*)/(.*)$ index.php?act=shop_/_

# -----
# SALE
# -----
RewriteRule ^sale$ index.php?act=shop_/_

```

```

RewriteRule ^sale/(.*)$ index.php?act=shop.
RewriteRule ^sale-filter/(.+)/(.*)$ index.php?act=shop.
[B]

# -----
# BLOG
# -----
RewriteRule ^news index.php?act=_blog/
RewriteRule ^news-view/(.+)/(.*)$ index.php?act=_blog/
RewriteRule ^read-blog/(.+)/(.+)/(.*)$ index.php?
act=_blog/detail_blog&category=$1&news_date=$2&news_alias=$3
#RewriteRule ^read/(.+)/(.+)/(.*)$ index.php?
act=_blog/_details/details&category=$1&news_date=$2&news_alias=$3

# -----
# PRESS
# -----
RewriteRule ^press-release/(.*)$ index.php?act=_press:
RewriteRule ^press-release-video$ index.php?act=_press:
RewriteRule ^press-release-view/(.+)/(.*)$ index.php?
act=_press/press_print&cat_news=$1&record=$2

# -----
# SERVICE
# -----
RewriteRule ^services/(.*)$ index.php?act=_servi
RewriteRule ^full-services-list index.php?act=_servi

# -----
# ARTICLE
# -----
RewriteRule ^article$ index.php?act=artic
RewriteRule ^article-view/(.+)/(.*)$ index.php?act=articl
RewriteRule ^article-read/(.+)/(.+)/(.*)$ index.php?
act=article/_details/details&category=$1&news_date=$2&news_alias=$3

# -----
# RECIPES
# -----
RewriteRule ^recipes$ index.php?act=pages:
RewriteRule ^recipes-view/(.+)/(.*)$ index.php?

```

```

act=pages_/recipes_/index&cat_news=$1&record=$2
RewriteRule ^recipes-read/(. *)/(. *)/(. *)$ index.php?
act=recipes_/_details/details&category=$1&news_date=$2&news_alias=$3
RewriteRule ^ajax-add$ index.php?act=shop_/

# -----
# ORDER
# -----
RewriteRule ^bag$ index.php?act=order
# RewriteRule ^order-login$ index.php?act=order
RewriteRule ^checkout$ index.php?act=order
RewriteRule ^email-order-customer/(. *)$ index.php?
act=admin/emails/order_/customer_/order_placed&order_number=$1
RewriteRule ^email-order-admin/(. *)$ index.php?
act=admin/emails/order_/admin_/order_placed&order_number=$1
RewriteRule ^finish$ index.php?act=order
RewriteRule ^wishlist$ index.php?act=order

# -----
# ACCOUNT
# -----
RewriteRule ^my-account$ index.php?act=accou
RewriteRule ^confirm$ index.php?act=confi
RewriteRule ^confirm-notification-customer/(. *)$ index.php?
act=admin/emails/confirm_/customer_/index&order_number=$1
RewriteRule ^confirm-notification-admin/(. *)$ index.php?
act=admin/emails/confirm_/admin_/index&order_number=$1

RewriteRule ^order-history$ index.php?act=accou
RewriteRule ^order-detail/(. *)$ index.php?act=accou
history_/detail_/orderdetails&oid=$1

RewriteRule ^edit-shipping$ index.php?act=accou
shipping_/shippingdetails
RewriteRule ^edit-account$ index.php?act=accou

RewriteRule ^reset-password/(. *)$ index.php?act=accou
RewriteRule ^login$ index.php?act=accou
RewriteRule ^register$ index.php?act=accou
RewriteRule ^logout$ index.php?act=static

```



```

# -----
# PAGES
# -----
RewriteRule ^faqs$ index.php?act=_faq/
RewriteRule ^story$ index.php?act=_stor
RewriteRule ^where-to-buy/(.*)$ index.php?act=pages_
RewriteRule ^contact-us index.php?act=_book
RewriteRule ^terms-conditions$ index.php?act=pages:
RewriteRule ^policy$ index.php?act=pages:
RewriteRule ^help$ index.php?act=pages:

# -----
# DUAL CURRENCY
# -----
RewriteRule ^change-currency/redirect-(.*)$ index.php?act=stati

# -----
# DUAL LANGUAGE
# -----
RewriteRule ^change-language/redirect-(.*)$ index.php?act=stati

# -----
#
# ADMIN
#
# -----
#
# LOGIN
#
RewriteRule ^admin/login$ admin/index.php?act=
RewriteRule ^admin/logout$ admin/index.php?act=:
RewriteRule ^admin/forgot-password$ admin/index.php?act=
RewriteRule ^admin/recover-password/(.*)$ admin/index.php?act=

# -----
# SETTINGS
# -----
RewriteRule ^admin/accounts$ admin/index.php?act=:
RewriteRule ^admin/general$ admin/index.php?act=:
RewriteRule ^admin/configuration$ admin/index.php?act=:

```

```

-----
RewriteRule ^admin/notifications$ admin/index.php?act=
RewriteRule ^admin/payments$ admin/index.php?act=
RewriteRule ^admin/payments-detail/(.*)$ admin/index.php?
act=settings/payment/details/index&id
RewriteRule ^admin/server-info$ admin/index.php?act=

# -----
# PAGES
# -----
# RewriteRule ^admin/home$ admin/index.php?act=
RewriteRule ^admin/home admin/index.php?
act=custom/inspiration/detail/index&ins_id=19
RewriteRule ^admin/about admin/index.php?
act=custom/inspiration/detail/index&ins_id=33
RewriteRule ^admin/page-slider/(.*)$ admin/index.php?act=
#RewriteRule ^admin/about$ admin/index.php?act=
RewriteRule ^admin/page-(.*)/(.*)$ admin/index.php?
act=pages/about/about&param=$1&lang=$2
RewriteRule ^admin/contact$ admin/index.php?act=

# -----
# PAYMENT: BANK
# -----
RewriteRule ^admin/add-payment-bank$ admin/index.php?
act=custom/_payment/_bank/category/_add/index
RewriteRule ^admin/payment-bank-detail/(.*)$ admin/index.php?
act=custom/_payment/_bank/category/_details/index&id=$1
RewriteRule ^admin/payment-bank$ admin/index.php?
act=custom/_payment/_bank/category/index
RewriteRule ^admin/payment-bank-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?
act=custom/_payment/_bank/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/add-payment-bank-account$ admin/index.php?act=
RewriteRule ^admin/payment-bank-account-detail/(.*)$ admin/index.php?
act=custom/_payment/_bank/details/edit&id=$1
RewriteRule ^admin/payment-bank-account$ admin/index.php?act=
RewriteRule ^admin/payment-bank-account-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?
act=custom/_payment/_bank/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# NONFD

```

# URLS

```
# -----  
RewriteRule ^admin/order$ admin/index.php?act=  
RewriteRule ^admin/order-view/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=orders/_all&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5  
RewriteRule ^admin/order-detail/(, *)$ admin/index.php?act=  
RewriteRule ^admin/order-detailing/(, *)$ admin/index.php?act=  
RewriteRule ^admin/order-verified-customer/(, *)$ admin/index.php?  
act=emails/paid_/customer_/index&order_number=$1  
RewriteRule ^admin/order-verified-warehouse/(, *)$ admin/index.php?  
act=emails/paid_/warehouse_/index&order_number=$1  
RewriteRule ^admin/order-shipping/(, *)$ admin/index.php?  
act=emails/shipping_/index&order_number=$1  
RewriteRule ^admin/order-open$ admin/index.php?act=  
RewriteRule ^admin/order-open-view/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=orders/_open&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5  
RewriteRule ^admin/order-expired$ admin/index.php?act=  
RewriteRule ^admin/order-expired-view/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=orders/_expired&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5  
RewriteRule ^admin/order-cancelled$ admin/index.php?act=  
RewriteRule ^admin/order-cancelled-view/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=orders/_cancel&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5  
RewriteRule ^admin/email-order-details-cancelled/(, *)$ admin/index.php?  
act=emails/order/_cancel/_cancel&order_number=$1  
RewriteRule ^admin/add-orders$ admin/index.php?act=
```

# -----

# PRODUCT

```
# -----  
RewriteRule ^admin/product/(, *)$ admin/index.php?act=  
RewriteRule ^admin/product-view/(, *)/(, *)/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=products/_all&active=$1&pg=$2&cat=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B]  
RewriteRule ^admin/product-active$ admin/index.php?act=  
RewriteRule ^admin/product-activeview/(, *)/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=products/_active/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]  
RewriteRule ^admin/product-all$ admin/index.php?act=  
RewriteRule ^admin/product-allview/(, *)/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=products/_active/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]  
RewriteRule ^admin/product-inactive$ admin/index.php?act=  
RewriteRule ^admin/product-inactiveview/(, *)/(, *)/(, *)/(, *)/(, *)-(, *)$ admin/index.php?  
act=products/_inactive/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]  
RewriteRule ^admin/product-detail/(, *)/(, *)-(, *)$ admin/index.php?
```

```

RewriteRule ^admin/product-details/(.*)$ admin/index.php?
act=products/details/edit&product_alias=$1
RewriteRule ^admin/add-product$ admin/index.php?act=
admin/add-product
RewriteRule ^admin/products/add/index.php

# -----
# CATEGORY
# -----
RewriteRule ^admin/category$ admin/index.php?act=
RewriteRule ^admin/add-category$ admin/index.php?act=
RewriteRule ^admin/edit-category$ admin/index.php?act=
#RewriteRule ^admin/detail-category/(.+)/(.*)$ admin/index.php?
act=products/_category/_detail/detail&cid=$1&cname=$2
RewriteRule ^admin/detail-category/(.+)/(.+)/(.*)$ admin/index.php?
act=products/_category/_detail/detail&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/category-view/(.+)/(.+)/(.+)/(.*)-(.*)$ admin/index.php?
act=products/_category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/child-category/(.+)/(.*)$ admin/index.php?
act=products/_category/child/index&cid=$1&cname=$2
RewriteRule ^admin/child-category-view/(.+)/(.+)/(.+)/(.+)/(.*)-(.*)$ admin/index.php?
act=products/_category/child/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7

# -----
# STOCK MANAGER
# -----
RewriteRule ^admin/stock-manager$ admin/index.php?act=
RewriteRule ^admin/stock-view/(.+)/(.+)/(.+)/(.*)-(.*)$ admin/index.php?
act=products/stock/sizemanager&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]
RewriteRule ^admin/stock-grouped$ admin/index.php?act=
RewriteRule ^admin/stock-grouped-view/(.+)/(.+)/(.*)-(.*)$ admin/index.php?
act=products/stock/_grouped/grouped&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

# -----
# COLOR MANAGER
# -----
RewriteRule ^admin/color$ admin/index.php?act=
RewriteRule ^admin/add-color$ admin/index.php?act=
RewriteRule ^admin/color-detail/(.+)/(.*)$ admin/index.php?
act=products/color/edit/edit&color_id=$1&color_name=$2
RewriteRule ^admin/color-view/(.+)/(.+)/(.*)-(.*)$ admin/index.php?

```

act=products/color/index&pg=\$1 &qpp=\$2&srt=\$3&src=\$4&srcval=\$5

# -----

# *SIZE MANAGER*

# -----

RewriteRule ^admin/size\$ admin/index.php?act=

RewriteRule ^admin/size-detail/(.)/(.)\$ admin/index.php?

act=products/size/\_details/edit&size\_id=\$1 &size\_name=\$2

RewriteRule ^admin/size-view/(.)/(.)/(.)/(.)-(.)\$ admin/index.php?

act=products/size/index&pg=\$1 &qpp=\$2&srt=\$3&src=\$4&srcval=\$5

RewriteRule ^admin/add-size\$ admin/index.php?act=

RewriteRule ^admin/edit-size\$ admin/index.php?act=

# -----

# *CUSTOMER*

# -----

RewriteRule ^admin/customer\$ admin/index.php?act=

RewriteRule ^admin/add-customer\$ admin/index.php?act=

RewriteRule ^admin/customer/(.)/(.)\$ admin/index.php?act=

RewriteRule ^admin/customer-details/(.)/(.)/(.)/(.)/(.)-(.)\$ admin/index.php?

act=customers/details/index&cid=\$1 &pg=\$2&qpp=\$3&srt=\$4&src=\$5&srcval=\$6

RewriteRule ^admin/edit-customer/(.)/(.)\$ admin/index.php?

act=customers/details/\_edit/edit&cid=\$1

RewriteRule ^admin/customer-view/(.)/(.)/(.)/(.)-(.)\$ admin/index.php?

act=customers/index&pg=\$1 &qpp=\$2&srt=\$3&src=\$4&srcval=\$5

RewriteRule ^admin/customer-details/(.)/(.)/(.)/(.)/(.)-(.)\$ admin/index.php?

act=customers/details/index&cid=\$1 &pg=\$2&qpp=\$3&srt=\$4&src=\$5&srcval=\$6

# -----

# *SHIPPING*

# -----

RewriteRule ^admin/shipping\$ admin/index.php?act=

RewriteRule ^admin/shipping-view/(.)/(.)/(.)/(.)-(.)\$ admin/index.php?

act=settings/shipping/index&pg=\$1 &qpp=\$2&srt=\$3&src=\$4&srcval=\$5

RewriteRule ^admin/add-shipping\$ admin/index.php?act=

RewriteRule ^admin/shipping/(.)/(.)\$ admin/index.php?

act=settings/shipping/detail/index&sid=\$1

RewriteRule ^admin/edit-shipping/(.)/(.)\$ admin/index.php?

act=settings/shipping/detail/edit&sid=\$1

# -----

```

#
# CUSTOM
#
# -----
RewriteRule ^admin/menu_bar$                                admin/index.php/

# -----
# PRODUCT: GENDER
# -----
RewriteRule ^admin/gender$                                  admin/index.php?act=
RewriteRule ^admin/gender-view/(.*)/(.*)/(.*)/(.*)-(.*)$  admin/index.php?
act=custom/products/_gender/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
RewriteRule ^admin/add-gender$                              admin/index.php?act=
RewriteRule ^admin/detail-gender/(.*)/(.*)$                admin/index.php?
act=custom/products/_gender/edit/edit&collection_id=$1&collection_name=$2

# -----
# PRODUCT: COLLECTION
# -----
RewriteRule ^admin/collection$                              admin/index.php?act=custom/pr
RewriteRule ^admin/collection-view/(.*)/(.*)/(.*)/(.*)-(.*)$  admin/index.php?
act=custom/products/_collection/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
RewriteRule ^admin/add-collection$                          admin/index.php?
act=custom/products/_collection/add/add
RewriteRule ^admin/detail-collection/(.*)/(.*)$             admin/index.php?
act=custom/products/_collection/edit/edit&collection_id=$1&collection_name=$2

# -----
# PROMOTION: NEW ARRIVAL
# -----
RewriteRule ^admin/new-arrivals$                            admin/index.php?act=custom/pr
RewriteRule ^admin/new-arrivals-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$  admin/index.php?
act=custom/promotions/new_arrival/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]

# -----
# PROMOTION: SALE
# -----
RewriteRule ^admin/sale$                                    admin/index.php?act=custom/promoti
RewriteRule ^admin/sale-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$  admin/index.php?
act=custom/promotions/_sale/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]

```

```

# -----
# PROMOTION: VOUCHER
# -----
RewriteRule ^admin/voucher$ admin/index.php?act=custom/promo
RewriteRule ^admin/voucher-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?
act=custom/promotions/_voucher/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
RewriteRule ^admin/add-voucher$ admin/index.php?act=custom/pr
RewriteRule ^admin/voucher-details-(.*)$ admin/index.php?
act=custom/promotions/_voucher/_details/details&voucher_id=$1
RewriteRule ^admin/voucher-detail/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?
act=custom/promotions/_voucher/_details/details&voucher_id=$1&pg=$2&qpp=$3&srt=$4&src=$5&src

# -----
# GALLERY
# -----
RewriteRule ^admin/project-category$ admin/index.php?
act=custom/inspiration/category/index
RewriteRule ^admin/project-category-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?
act=custom/inspiration/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
RewriteRule ^admin/add-project-category$ admin/index.php?act=
RewriteRule ^admin/project-category-detail/(.*)$ admin/index.php?
act=custom/inspiration/category/details&ins_id=$1
RewriteRule ^admin/project$ admin/index.php?act=
RewriteRule ^admin/view-project/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?
act=custom/inspiration/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]
RewriteRule ^admin/add-project$ admin/index.php?act=
RewriteRule ^admin/project-detail/(.*)$ admin/index.php?
act=custom/inspiration/detail/index&ins_id=$1
RewriteRule ^admin/project-meta-tag$ admin/index.php?act=

# -----
# NEWS
# -----
RewriteRule ^admin/add-news-category$ admin/index.php?act=
#RewriteRule ^admin/lang-(.*)/add-news-category$ admin/index.php?
act=custom/news/category/_add/add&lang=$1
RewriteRule ^admin/news-category$ admin/index.php?act=
RewriteRule ^admin/news-category-detail/(.*)/(.*)/(.*)$ admin/index.php?
act=custom/news/category/_details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/news-category-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?
act=custom/news/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

```

```

RewriteRule ^admin/news$ admin/index.php?act:
#RewriteRule ^admin/news-detail/(.+)/(.+)$ admin/index.php?
act=custom/news/details/index&nid=$1&nn=$2
RewriteRule ^admin/news-detail/(.+)/(.+)/(.+)$ admin/index.php?
act=custom/news/details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-news$ admin/index.php?act:
RewriteRule ^admin/news-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?
act=custom/news/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# SERVICES (SPALOSOPHY)
# -----
RewriteRule ^admin/add-services-category$ admin/index.php?
act=custom/_services/category/_add/add
RewriteRule ^admin/services-category$ admin/index.php?act:
RewriteRule ^admin/services-category-detail/(.+)/(.+)/(.+)$ admin/index.php?
act=custom/_services/category/details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/services-category-view/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?
act=custom/_services/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/services$ admin/index.php?act:
RewriteRule ^admin/service-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?
act=custom/_services/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6
RewriteRule ^admin/service-detail/(.+)/(.+)/(.+)$ admin/index.php?
act=custom/_services/details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-services admin/index.php?act:

# -----
# PRESS
# -----
RewriteRule ^admin/add-press-category$ admin/index.php?
act=custom/_pressrelease/category/_add/add
#RewriteRule ^admin/lang-(.+)/add-news-category$ admin/index.php?
act=custom/_pressrelease/category/_add/add&lang=$1
RewriteRule ^admin/press-category$ admin/index.php?
act=custom/_pressrelease/category/index
RewriteRule ^admin/press-category-detail/(.+)/(.+)/(.+)$ admin/index.php?
act=custom/_pressrelease/category/details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/press-category-view/(.+)/(.+)/(.+)/(.+)-(.)$ admin/index.php?
act=custom/_pressrelease/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/press admin/index.php?act:
RewriteRule ^admin/detail-press/(.+)/(.+)/(.+)$ admin/index.php?

```



```

act=custom/_pressrelease/details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-press                                     admin/index.php?act=
RewriteRule ^admin/view-press/(. *)/(. *)/(. *)/(. *)/(. *)-(. *)$  admin/index.php?
act=custom/_pressrelease/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# RECIPES
# -----
RewriteRule ^admin/add-recipes-category$                       admin/index.php?act=custom/recipes_/
#RewriteRule ^admin/lang-(. *)/add-recipes-category$         admin/index.php?act=custom/rc
RewriteRule ^admin/recipes-category$                          admin/index.php?act=custom/recipes_/c/
RewriteRule ^admin/recipes-category-detail/(. *)/(. *)/(. *)$  admin/index.php?
act=custom/recipes_/category/_details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/recipes-category-view/(. *)/(. *)/(. *)/(. *)-(. *)$  admin/index.php?
act=custom/recipes_/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/recipes$                                    admin/index.php?act=custom/recipes_/inde
#RewriteRule ^admin/recipes-detail/(. *)/(. *)$              admin/index.php?act=custom/recipe
RewriteRule ^admin/recipes-detail/(. *)/(. *)/(. *)$         admin/index.php?
act=custom/recipes_/details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-recipes$                                admin/index.php?act=custom/recipes_/ad
RewriteRule ^admin/recipes-view/(. *)/(. *)/(. *)/(. *)/(. *)-(. *)$  admin/index.php?
act=custom/recipes_/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# ARTICLE
# -----
RewriteRule ^admin/add-article-category$                       admin/index.php?act=custom/article_/
#RewriteRule ^admin/lang-(. *)/add-article-category$         admin/index.php?act=custom/ar
RewriteRule ^admin/article-category$                          admin/index.php?act=custom/article_/c/
RewriteRule ^admin/article-category-detail/(. *)/(. *)/(. *)$  admin/index.php?
act=custom/article_/category/_details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/article-category-view/(. *)/(. *)/(. *)/(. *)-(. *)$  admin/index.php?
act=custom/article_/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/article$                                    admin/index.php?act=custom/article_/inde
#RewriteRule ^admin/article-detail/(. *)/(. *)$              admin/index.php?act=custom/articl
RewriteRule ^admin/article-detail/(. *)/(. *)/(. *)$         admin/index.php?
act=custom/article_/details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-article$                                admin/index.php?act=custom/article_/ad
RewriteRule ^admin/article-view/(. *)/(. *)/(. *)/(. *)/(. *)-(. *)$  admin/index.php?
act=custom/article_/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

```

```

# -----
# LOCATIONS
# -----
RewriteRule ^admin/add-location-city$                admin/index.php?act=custom/_location/
RewriteRule ^admin/location-city$                   admin/index.php?act=
RewriteRule ^admin/location-city-detail/(.*)/(.*)$   admin/index.php?
act=custom/_location/category/_details/details&cid=$1&cname=$2
RewriteRule ^admin/location-city-view/(.*)/(.*)/(.*)/(.*)-(.*)$   admin/index.php?
act=custom/_location/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/location$                         admin/index.php?act=
#RewriteRule ^admin/location-detail/(.*)/(.*)$      admin/index.php?
act=custom/_location/details/index&nid=$1&nn=$2
RewriteRule ^admin/location-detail/(.*)/(.*)$       admin/index.php?
act=custom/_location/details/edit&nid=$1&nn=$2
RewriteRule ^admin/add-location$                    admin/index.php?act=
RewriteRule ^admin/location-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$   admin/index.php?
act=custom/_location/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# BACK ORDER
# -----
RewriteRule ^admin/back-order$                      admin/index.php?act=custom/order
RewriteRule ^admin/back-order-view/(.*)/(.*)/(.*)/(.*)-(.*)$       admin/index.php?
act=custom/orders/_backorder/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
#RewriteRule ^admin/back-order-detail/(.*)$         admin/index.php?act=custom/order
RewriteRule ^admin/back-order-detail/(.*)$         admin/index.php?
act=custom/orders/_backorder/details/index&oid=$1
RewriteRule ^admin/back-order-notification/(.*)$   admin/index.php?act=emails/bi

# -----
# REPORT
# -----
RewriteRule ^admin/reporting$                       admin/index.php?act=custom/reports/
RewriteRule ^admin/reporting/sales-by-category$    admin/index.php?
act=custom/reports/sales/items/categories/index
RewriteRule ^admin/reporting/sales-by-category/(.*)/(.*)$           admin/index.php?
act=custom/reports/sales/items/categories/index&date_start=$1&date_end=$2
RewriteRule ^admin/reporting/sales-by-order$       admin/index.php?act=custom/r
RewriteRule ^admin/reporting/sales-by-order/(.*)/(.*)$             admin/index.php?
act=custom/reports/sales/items/orders/index&date_start=$1&date_end=$2
RewriteRule ^admin/reporting/inventoru$           admin/index.php?act=custom/re

```

```
-----  
RewriteRule ^admin/reporting/inventory/(.*)$ admin/index.php?act=custom/r  
RewriteRule ^admin/reporting-export/inventory$ admin/index.php?act=custor  
RewriteRule ^admin/reporting-export/inventory/(.*)$ admin/index.php?  
act=custom/reports/inventory/export&root=$1
```

```
# -----
```

```
# LIST ADD MENU FUJIN
```

```
# -----
```

```
RewriteRule ^admin/add-menu-category$ admin/index.php?  
act=custom/list_add_menu/category/_add/add  
RewriteRule ^admin/menu-category$ admin/index.php?act=cust  
RewriteRule ^admin/menu-category-detail/(.*)/(.*)/(.*)$ admin/index.php?  
act=custom/list_add_menu/category/_details/details&lang=$1&cid=$2&cname=$3  
RewriteRule ^admin/menu-category-view/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?  
act=custom/list_add_menu/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5  
RewriteRule ^admin/menu$ admin/index.php?act=cust  
RewriteRule ^admin/menu-view/(.*)/(.*)/(.*)/(.*)/(.*)-(.*)$ admin/index.php?  
act=custom/list_add_menu/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6  
RewriteRule ^admin/menu-detail/(.*)/(.*)/(.*)$ admin/index.php?  
act=custom/list_add_menu/details/edit&lang=$1&nid=$2&nn=$3  
RewriteRule ^admin/add-menu admin/index.php?act=cust
```

```
# -----
```

```
# VERITRANS
```

```
# -----
```

```
RewriteRule ^admin/payment-veritrans$ admin/index.php?  
act=custom/_payment/_veritrans/_antikode/admin/index  
RewriteRule ^control-veritrans/(.*)$ index.php?  
act=order/_payment/_veritrans/_antikode/control&order_number=$1  
RewriteRule ^payment-veritrans/(.*)$ index.php?act=order/_payment/_  
web/checkout-process&order_number=$1  
RewriteRule ^bag-veritrans$ index.php?act=order/_payment/_veri  
RewriteRule ^finish-veritrans$ index.php?act=order/_payment/_
```

```
RewriteRule ^email-veritrans-customer-success/(.*)$ index.php?  
act=admin/custom/_payment/_veritrans/emails_/success_/customer_/order_placed&order_number=$1  
RewriteRule ^email-veritrans-warehouse-success/(.*)$ index.php?  
act=admin/custom/_payment/_veritrans/emails_/success_/warehouse_/index&order_number=$1  
RewriteRule ^email-veritrans-admin-success/(.*)$ index.php?  
act=admin/custom/_payment/_veritrans/emails_/success_/admin_/order_placed&order_number=$1
```



```

RewriteRule admin/mailchimp$ admin/index.php?act=

RewriteRule ^admin/email-notification/(.*)$ admin/index.php?act=custom/email_notification/index&alias=$1

# FRONT END
RewriteRule ^news-category/(.*)$ index.php?act=(news)
RewriteRule ^details-news/(.*)/(.*)$ index.php?act=(news)

# DUAL LANGUAGE
RewriteRule ^indonesia$ lang_id.php
RewriteRule ^english$ lang_en.php

#ABOUT
RewriteRule ^admin/(.*)-page-(.*)$ admin/index.php?act=custom/language/pages/about/about&lang=$1&param=$2

# PRODUCTS
RewriteRule ^admin/(.*)-product-details-(.*)$ admin/index.php?act=custom/language/products/edit&lang=$1&product_alias=$2

#NEWS
RewriteRule ^admin/(.*)-news-detail/(.*)/(.*)$ admin/index.php?act=custom/language/pages/news/news&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/(.*)-news-edit/(.*)/(.*)$ admin/index.php?act=custom/language/pages/news/news_edit&lang=$1&nid=$2&nn=$3

php_value upload_max_filesize 100M
php_value post_max_size 100M

RewriteRule sitemap.xml sitemap.php [nocase]

```