

```
# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /casbahdance.org/
RewriteRule ^index\.php$ - [L]
RewriteRule ^assets/css/(.*) /casbahdance.org/wp-content/themes/casbah_dance_custom/assets/c
RewriteRule ^assets/js/(.*) /casbahdance.org/wp-content/themes/casbah_dance_custom/assets/js
RewriteRule ^assets/img/(.*) /casbahdance.org/wp-content/themes/casbah_dance_custom/assets/i
RewriteRule ^assets/fonts/(.*) /casbahdance.org/wp-content/themes/casbah_dance_custom/asset:
RewriteRule ^plugins/(.*) /casbahdance.org/wp-content/plugins/$1 [QSA,L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /casbahdance.org/index.php [L]
</IfModule>
```

```
# END WordPress
```

```
# BEGIN HTML5 Boilerplate
```

```
###
### This contains the HTML5 Boilerplate .htaccess that can be found at:
### github.com/h5bp/html5-boilerplate/blob/master/.htaccess
###
### Added:
### Block access to access to WordPress files that reveal version information.
###
### Commented out by default:
### Expires headers:      Use WP Super Cache or W3 Total Cache (unless using the H5BP buil
### ETag removal:        Use WP Super Cache or W3 Total Cache (unless using the H5BP buil
### Start rewrite engine: Handled by WordPress
### Suppress/force www:  Handled by WordPress
### Options -MultiViews: Causes a server 500 error on most shared hosts
### Custom 404 page:     Handled by WordPress
###
### Anytime you update this file the .htaccess file in the root of your
### WordPress install is automatically updated with the changes whenever
### the permalinks are flushed or set
###
```

```
# -----
# Better website experiences for 15 years
```

```
# better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *every*
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|ogg|m4a|ogv|mp4|m4v|webm|svg|svgz|eot|ttf|otf|woff|ico|webp|appcache|manifest|
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# CORS-enabled images (@crossorigin)
# -----

# Send CORS headers if browsers request them; enabled by default for images.
# developer.mozilla.org/en/CORS_Enabled_Image
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</IfModule>
```

```
# mod_headers, y u no match by Content-Type?!
<FilesMatch "\.(gif|png|jpe?g|svg|svgz|ico|webp)$">
  SetEnvIf Origin ":" IS_CORS
  Header set Access-Control-Allow-Origin "*" env=IS_CORS
</FilesMatch>
</IfModule>
</IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

<IfModule mod_headers.c>
  <FilesMatch "\.(ttf|ttd|otf|eot|woff|font. css)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js jsonp
AddType application/json            json

# Audio
AddType audio/ogg                    oga ogg
AddType audio/mp4                    m4a f4a f4b

# Video
AddType video/ogg                     ogv
AddType video/mp4                     mp4 m4v f4v f4p
AddType video/webm                     webm
AddType video/x-flv                     flv
```

```
# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml          svg svgz
AddEncoding gzip                svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf       ttf ttc
AddType font/opentype               otf
AddType application/x-font-woff      woff

# Assorted types
AddType image/x-icon               ico
AddType image/webp                 webp
AddType text/cache-manifest         appcache manifest
AddType text/x-component            htc
AddType application/xml             rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall     xpi
AddType application/octet-stream    safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard                vcf
AddType application/x-shockwave-flash swf
```

```
# -----
# Allow concatenation from within specific js and css files
# -----
```

```
# e.g. Inside of script.combined.js you could have
# <!--#include file="libs/jquery-1.5.0.min.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.
```

```
# This is not in use in the boilerplate as it stands. You may
# choose to name your files in this way for this advantage or
# concatenate and minify them manually.
# Disabled by default.
```

```

#<FilesMatch "\.combined\.js$"
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
#</FilesMatch>
#<FilesMatch "\.combined\.css$"
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
#</FilesMatch>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

# Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-bu
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip deflate)\
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

# HTML, TXT, CSS, JavaScript, JSON, XML, HTC:
<IfModule filter_module>
  FilterDeclare    COMPRESS
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/html
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/css
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/plain
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/xml
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/x-component
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/javascript
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/json
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/xml
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/xhtml+xml
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/rss+xml
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/atom+xml
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/vnd.ms-fontobject

```

```

FilterProvider COMPRESS DEFLATE resp=Content-Type $image/svg+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/x-icon
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/x-font-ttf
FilterProvider COMPRESS DEFLATE resp=Content-Type $font/opentype
FilterChain COMPRESS
FilterProtocol COMPRESS DEFLATE change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
  # Legacy versions of Apache
  AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
  AddOutputFilterByType DEFLATE application/javascript
  AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
  AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml application/atom
  AddOutputFilterByType DEFLATE image/x-icon image/svg+xml application/vnd.ms-fontobject :
font/opentype
</IfModule>

</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week" or so.

# <IfModule mod_expires.c>
# ExpiresActive on

# Perhaps better to whitelist expires rules? Perhaps.
# ExpiresDefault "access plus 1 month"

# cache. apache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
# ExpiresByType text/cache-manifest "access plus 0 seconds"

```

```
# Your document html
# ExpiresByType text/html "access plus 0 seconds"

# Data
# ExpiresByType text/xml "access plus 0 seconds"
# ExpiresByType application/xml "access plus 0 seconds"
# ExpiresByType application/json "access plus 0 seconds"

# Feed
# ExpiresByType application/rss+xml "access plus 1 hour"
# ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
# ExpiresByType image/x-icon "access plus 1 week"

# Media: images, video, audio
# ExpiresByType image/gif "access plus 1 month"
# ExpiresByType image/png "access plus 1 month"
# ExpiresByType image/jpg "access plus 1 month"
# ExpiresByType image/jpeg "access plus 1 month"
# ExpiresByType video/ogg "access plus 1 month"
# ExpiresByType audio/ogg "access plus 1 month"
# ExpiresByType video/mp4 "access plus 1 month"
# ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
# ExpiresByType text/x-component "access plus 1 month"

# Webfonts
# ExpiresByType application/x-font-ttf "access plus 1 month"
# ExpiresByType font/opentype "access plus 1 month"
# ExpiresByType application/x-font-woff "access plus 1 month"
# ExpiresByType image/svg+xml "access plus 1 month"
# ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
# ExpiresByType text/css "access plus 1 year"
# ExpiresByType application/javascript "access plus 1 year"

# </IfModule>
```

```
# -----  
# Prevent mobile network providers from modifying your site  
# -----  
  
# The following header prevents modification of your code over 3G on some European provider:  
# This is the official 'bypass' suggested by O2 in the UK  
  
# <IfModule mod_headers.c>  
# Header set Cache-Control "no-transform"  
# </IfModule>  
  
# -----  
# ETag removal  
# -----  
  
# FileETag None is not enough for every server.  
# <IfModule mod_headers.c>  
#   Header unset ETag  
# </IfModule>  
  
# Since we're sending far-future expires, we don't need ETags for  
# static content.  
#   developer.yahoo.com/performance/rules.html#etags  
# FileETag None  
  
# -----  
# Stop screen flicker in IE on CSS rollovers  
# -----  
  
# The following directives stop screen flicker in IE on CSS rollovers - in  
# combination with the "ExpiresByType" rules for images (see above). If  
# needed, un-comment the following rules.  
  
# BrowserMatch "MSIE" brokenvary=1  
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1  
# BrowserMatch "Opera" !brokenvary  
# SetEnvIf brokenvary 1 force-no-vary  
  
# -----  
# Set Keep-Alive Header  
# -----
```



```
..

# Keep-Alive allows the server to send multiple requests through one TCP-connection.
# Be aware of possible disadvantages of this setting. Turn on if you serve a lot of
# static content.

# <IfModule mod_headers.c>
#   Header set Connection Keep-Alive
# </IfModule>

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, uncomment and specify a path or regex in the Location directive

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\"", CP="IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
# </IfModule>

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and features.
# FollowSymLinks must be enabled for this to work.
#
# Some cloud hosting services require RewriteBase to be set: goo.gl/H0cPM
# If using the h5bp in a subdirectory, use `RewriteBase /foo` instead where 'foo' is your d

# <IfModule mod_rewrite.c>
#   Options +FollowSymLinks
#   RewriteEngine On
# # RewriteBase /
# </IfModule>

# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs - especially not with
```

```
# THE SAME CONTENT SHOULD NEVER BE AVAILABLE UNDER TWO DIFFERENT URLS - especially not with
# without "www." at the beginning, since this can cause SEO problems (duplicate content).
# That's why you should choose one of the alternatives and redirect the other one.

# By default option 1 (no "www.") is activated. Remember: Shorter URLs are sexier.
# no-www.org/faq.php?q=class_b

# If you rather want to use option 2, just comment out all option 1 lines
# and uncomment option 2.
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----

# Option 1:
# Rewrite "www.example.com -> example.com"

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} ^www\.(.+) [NC]
#   RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----

# Option 2:
# To rewrite "example.com -> www.example.com" uncomment the following lines.
# Be aware that the following rule might not be a good idea if you
# use "real" subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\..+ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----

# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version rewriting,
# you might want to consider enabling this, which will route requests for
# /css/styles-00110000.css to /css/styles-00110000.css
```

```
# /css/style, 20110203, CSS to /css/style, CSS

# To understand why this is important and a better idea than all, css?v1231,
# read: github.com/h5bp/html5-boilerplate/wiki/cachebusting

# Uncomment to enable.
# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1. $3 [L]
# </IfModule>

# -----
# Prevent SSL cert warnings
# -----

# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.example.com when your cert only allows https://secure.example.com
# Uncomment the following lines to use this feature.

# <IfModule mod_rewrite.c>
#   RewriteCond %{SERVER_PORT} !^443
#   RewriteRule ^https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Prevent 404 errors for non-existing redirected folders
# -----

# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name does
# e.g. /blog/hello : webmasterworld.com/apache/3808792.htm

# Options -MultiViews

# -----
# Custom 404 page
# -----

# You can add custom pages to handle 500 or 403 pretty easily, if you like.
# If you are hosting your site in subdirectory, adjust this accordingly
# e.g. ErrorDocument 404 /subdir/404.html
"-----
# Custom 500 page
# -----
```

```
# ErrorDocument 404 /404.html

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .css .js .xml .json .rss .atom

# -----
# A little more security
# -----

# Do we want to advertise the exact version number of Apache we're running?
# Probably not.
## This can only be enabled if used in httpd.conf - It will not work in .htaccess
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a default document
# Usually you should leave this activated, because you shouldn't allow everybody to surf thi
# every folder on your server (which includes rather private places like CMS system folders.
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a period. This
# includes directories used by version control systems such as Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [F]
</IfModule>

# Block access to backup and source files
# This files may be left by some text/html editors and
# pose a great security danger, when someone can access them
<FilesMatch "(\\. (bak|config|sql|fla|psd|ini|log|sh|incl|swp|dist)|\\.")$">
    Order allow,deny
```

```
Deny from all
Satisfy All
</FilesMatch>
```

```
# Block access to WordPress files that reveal version information.
```

```
<FilesMatch "^(wp-config\.php|readme\.html|license\.txt)">
```

```
Order allow,deny
```

```
Deny from all
```

```
Satisfy All
```

```
</FilesMatch>
```

```
# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register_globals
#
```

```
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS :
```

```
#
```

```
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.
```

```
# php_flag register_globals Off
```

```
# Rename session cookie to something else, than PHPSESSID
```

```
# php_value session.name sid
```

```
# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of )
```

```
# php_flag magic_quotes_gpc Off
```

```
# Do not show you are using PHP
```

```
# Note: Move this line to php.ini since it won't work in .htaccess
```

```
# php_flag expose_php Off
```

```
# Level of log detail - log all errors
```

```
# php_value error_reporting -1
```

```
# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

# END HTML5 Boilerplate
```