

```

# -----
# | Cross-origin images |
# -----
# Send the CORS header for images when browsers request it.
<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        <FilesMatch "\.(bmp|curl|gif|ico|jpe?g|png|svgz?|webp)$">
            SetEnvIf Origin ":" IS_CORS
            Header set Access-Control-Allow-Origin "*" env=IS_CORS
        </FilesMatch>
    </IfModule>
</IfModule>
# -----
# | Cross-origin web fonts |
# -----
# Allow cross-origin access to web fonts.
<IfModule mod_headers.c>
    <FilesMatch "\.(eot|otf|tt[cf]|woff2?)$">
        Header set Access-Control-Allow-Origin "*"
    </FilesMatch>
</IfModule>
# -----
# | Document modes |
# -----
# Force Internet Explorer 8/9/10 to render pages in the highest mode
# available in the various cases when it may not.
<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge"
    # `mod_headers` cannot match based on the content-type, however,
    # the `X-UA-Compatible` response header should be send only for
    # HTML documents and not for the other resources.
    <FilesMatch "\.
(appcache|atom|bbaw|bmp|crx|css|curl|eot|f4[abpv]|flv|geojson|gif|htc|ico|jpe?
g|js|json|ld)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdfl|rssl|safariextz|svgz?
|swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|woff2?|xlcl|xsl|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>
# -----
# | File access |
#

```

```

# -----
# Block access to directories without a default document.
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>
# -----
# Block access to files that can expose sensitive information.
#
<FilesMatch "(^#.#|\.|(bak|conf|dist|fla|in[ci]|log|psd|sh|sql|sw[op])|")$" >
    # Apache < 2.3
    <IfModule !mod_authz_core.c>
        Order allow,deny
        Deny from all
        Satisfy All
    </IfModule>
    # Apache ≥ 2.3
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>
</FilesMatch>
</IfModule>
# -----
# | Rewrite engine |
# -----
<IfModule mod_rewrite.c>
    # (1)
    RewriteEngine On
    # (2)
    # Options +FollowSymlinks
    # (3)
    # Options +SymLinksIfOwnerMatch
    # (4)
    # RewriteBase /
    # (5)
    # RewriteOptions <options>
    # (6)
</IfModule>
<IfModule mod_rewrite.c>
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
</IfModule>
..

```

```

# -----
# | Expires headers |
# -----
# BEGIN Expire headers
<IfModule mod_expires.c>
ExpiresActive on
ExpiresDefault "access plus 1 month"
# CSS
ExpiresByType text/css "access plus 1 year"
# Data interchange
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rdf+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/ld+json "access plus 0 seconds"
ExpiresByType application/schema+json "access plus 0 seconds"
ExpiresByType application/vnd.geo+json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"
# Favicon (cannot be renamed!) and cursor images
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
ExpiresByType image/x-icon "access plus 1 week"
# HTML
ExpiresByType text/html "access plus 0 seconds"
# JavaScript
ExpiresByType application/javascript "access plus 1 year"
ExpiresByType application/x-javascript "access plus 1 year"
ExpiresByType text/javascript "access plus 1 year"
# Manifest files
ExpiresByType application/manifest+json "access plus 1 year"
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"
# Media files
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/bmp "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType image/webp "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"

```

```

ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
# Web fonts
# Embedded OpenType (EOT)
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType font/eot "access plus 1 month"
# OpenType
ExpiresByType font/opentype "access plus 1 month"
# TrueType
ExpiresByType application/x-font-ttf "access plus 1 month"
# Web Open Font Format (WOFF) 1.0
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType font/woff "access plus 1 month"
# Web Open Font Format (WOFF) 2.0
ExpiresByType application/font-woff2 "access plus 1 month"
# Other
ExpiresByType text/x-cross-domain-policy "access plus 1 week"
</IfModule>
# END Expire headers
# BEGIN Cache-Control Headers
<IfModule mod_headers.c>
  <FilesMatch "\.(ico|jpe?g|png|gif|swf|gz)$">
    Header set Cache-Control "max-age=2592000, public"
  </FilesMatch>
  <FilesMatch "\.(css)$">
    Header set Cache-Control "max-age=604800, public"
  </FilesMatch>
  <FilesMatch "\.(js)$">
    Header set Cache-Control "max-age=2592000, private"
  </FilesMatch>
  <FilesMatch "\.(x?html?)$">
    Header set Cache-Control "max-age=604800, public"
    #Header set Pragma "cache"
  </FilesMatch>
  <FilesMatch "\.(php)$">
    #Header set Cache-Control "max-age=600, private, must-revalidate"
    Header unset Cache-Control
    #Header set Pragma "no-cache"
  </FilesMatch>
</IfModule>

```

```

# END Cache-Control Headers
# BEGIN Turn ETags Off
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
    FileETag None
# END Turn ETags Off
# <IfModule mod_headers.c>
# BEGIN Remove Last-Modified Header
# Header unset Last-Modified
# </IfModule>
# END Remove Last-Modified Header
# BEGIN Compress text files
<IfModule mod_deflate.c>
    #DeflateCompressionLevel 1
    <FilesMatch "\.(css|js|x?html?|php)$">
        SetOutputFilter DEFLATE
    </FilesMatch>
    AddOutputFilterByType DEFLATE text/xml
    AddOutputFilterByType DEFLATE text/css
    AddOutputFilterByType DEFLATE text/javascript
    AddOutputFilterByType DEFLATE text/html
    AddOutputFilterByType DEFLATE text/plain
    AddOutputFilterByType DEFLATE application/xml
    AddOutputFilterByType DEFLATE application/xhtml+xml
    AddOutputFilterByType DEFLATE application/rss+xml
    AddOutputFilterByType DEFLATE application/javascript
    AddOutputFilterByType DEFLATE application/x-javascript
    # Properly handle old browsers that do not support compression
    BrowserMatch ^Mozilla/4 gzip-only-text/html
    BrowserMatch ^Mozilla/4\.0[678] no-gzip
    BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
    # Explicitly exclude binary files from compression just in case
    SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png|pdf|swf|ico|zip)$ no-gzip
    # Below uses mod_deflate to compress text files. Never compress binary files.
    <IfModule mod_headers.c>
        # Make sure proxies don't deliver the wrong content
        Header append Vary User-Agent env=!dont-vary
        # set cache control to private to ignore proxies and avoid edge cases
        Header append Cache-Control "private"
        # Remove the vary header for MSIE

```

```

    BrowserMatch "MSIE" force-no-vary
</IfModule>
</IfModule>
# -----
# | Reducing MIME type security risks |
# -----
<IfModule mod_headers.c>
    Header set X-Content-Type-Options "nosniff"
</IfModule>
# END Compress text files
##### Config Global
# -----
# | Character encodings |
# -----
AddDefaultCharset utf-8
# -----
# Serve the following file types with the media type `charset`
# parameter set to `UTF-8`.
<IfModule mod_mime.c>
    AddCharset utf-8 .atom \
                .bbaw \
                .css \
                .geojson \
                .js \
                .json \
                .jsonld \
                .rdf \
                .rss \
                .topojson \
                .vtt \
                .webapp \
                .xloc \
                .xml
</IfModule>
<IfModule mod_php5.c>
#####
## adjust memory limit
    #php_value memory_limit 128M
    #php_value max_execution_time 18000
#####
## disable magic quotes for php request vars

```

```

    #php_flag magic_quotes_gpc off
#####
## disable automatic session start
## before autoload was initialized
    #php_flag session.auto_start off
#####
# disable user agent verification to not break multiple image upload
    #php_flag suhosin.session.cryptua off
#####
# turn off compatibility with PHP4 when dealing with objects
    #php_flag zend.zel_compatibility_mode Off
</IfModule>
## default index file
    DirectoryIndex index.php
#RewriteCond %{HTTP_HOST} ^localhost
<IfModule mod_rewrite.c>
    RewriteCond %{HTTP_HOST} !^www\.
    RewriteRule ^(.*)$ http://www.%{HTTP_HOST}/$1 [R=301,L]
</IfModule>
# -----
# | REWRITE
# -----
##### Public #####
RewriteCond %{REQUEST_URI} !^(var|faq)
RewriteRule ^([a-zA-Z]{1,3})/(.*)$ /$2?strLangue=$1 [QSA,L]
RewriteRule ^(?:actualites|news|nieuws)/(0,1)$ /news.php [QSA,L]
RewriteRule ^(?:actualites|news|nieuws)/page[/](/[0-9]+)/ (0,1)$ /news.php?page=$1
[QSA,L]
RewriteRule ^(?:actualites|news|nieuws)/(\d{4})/(0,1)$ /news.php?getyear=$1 [QSA,L]
RewriteRule ^(?:actualites|news|nieuws)/(\d{4})/(\d{2})/(0,1)$ /news.php?
getyear=$1&getmonth=$2 [QSA,L]
RewriteRule ^(?:actualites|news|nieuws)/(\d{4}/\d{2}/\d{2})/([-_0-9a-zA-Z]+)/([-_0-9a-zA-
Z]+)/?$ /news.php?getdate=$1&uri_get_news=$2&getnews=$3 [QSA,L]
RewriteRule ^(?:actualites|news|nieuws)/tag/([+_0-9a-zA-Z]+)/ (0,1)$ /news.php?tag=$1
[QSA,L]
RewriteRule ^(?:pages)/([/0-9]+)/[-]([-_0-9a-zA-Z]+)/[/](0,1)$ /cms.php?
getidpage=$1&geturi_page=$2 [QSA,L]
RewriteRule ^(?:pages)/([/0-9]+)/[-]([-_0-9a-zA-Z]+)/[/](/[0-9]+)/[-]([-_0-9a-zA-Z]+)/ (0,1)$
/cms.php?getidpage_p=$1&geturi_page_p=$2&getidpage=$3&geturi_page=$4 [QSA,L]
RewriteRule ^(?:catalogue|catalog)/(0,1)$ /catalog.php
[QSA,L]

```

```

RewriteRule ^(?: catalogue| catalog)[/](/[0-9]+)[-]([-_0-9a-zA-Z]+)/<(0,1)$
/catalog.php?idcl c=$1 &pathcl i belle=$2 [QSA, L]
RewriteRule ^(?: catalogue| catalog)[/](/[0-9]+)[-]([-_0-9a-zA-Z]+)/[/](/[0-9]+)[-]([-_0-9a-
zA-Z]+)/<(0,1)$ /catalog.php?idcl c=$1 &pathcl i belle=$2&i dcl s=$3&pathsl i belle=$4
[QSA, L]
RewriteRule ^(?: catalogue| catalog)[/](/[0-9]+)[-]([-_0-9a-zA-Z]+)/[/]([-_0-9a-zA-Z]+)/[-]
([/0-9]+)/<(0,1)$ /catalog.php?idcl c=$1 &pathcl i belle=$2&url catalog=$3&i dproduct=$4
[QSA, L]
RewriteRule ^(?: catalogue| catalog)[/](/[0-9]+)[-]([-_0-9a-zA-Z]+)/[/](/[0-9]+)[-]([-_0-9a-
zA-Z]+)/[/]([-_0-9a-zA-Z]+)/[-](/[0-9]+)/<(0,1)$ /catalog.php?
idcl c=$1 &pathcl i belle=$2&i dcl s=$3&pathsl i belle=$4&url catalog=$5&i dproduct=$6 [QSA, L]
RewriteRule ^webservice/<(0,1)$ %(ENV: REWRIT EBASE)webservice.php [QSA, L]
RewriteRule ^webservice[/](/[a-zA-Z]+)/<(0,1)$ %(ENV: REWRIT EBASE)webservice.php?
collection=$1 [QSA, L]
RewriteRule ^webservice[/](/[a-zA-Z]+)/[/](/[a-zA-Z]+)/<(0,1)$ %(
ENV: REWRIT EBASE)webservice.php?collection=$1 &retrieve=$2 [QSA, L]
RewriteRule ^webservice[/](/[a-zA-Z]+)/[/](/[a-zA-Z]+)/[/](/[0-9]+)/<(0,1)$ %(
ENV: REWRIT EBASE)webservice.php?collection=$1 &retrieve=$2&i d=$3 [QSA, L]
RewriteRule ^webservice[/](/[a-zA-Z]+)/[/](/[a-zA-Z]+)/[/](/[0-9]+)/[/](/[a-zA-Z]+)/<(0,1)$ %(
ENV: REWRIT EBASE)webservice.php?collection=$1 &retrieve=$2&i d=$3&action=$4 [QSA, L]
RewriteRule ^webservice[/](/[a-zA-Z]+)/[/](/[a-zA-Z]+)/[/](/[0-9]+)/[/](/[a-zA-Z]+)/[/](/[a-zA-
Z]+)/<(0,1)$ %(ENV: REWRIT EBASE)webservice.php?
collection=$1 &retrieve=$2&i d=$3&action=$4&subaction=$5 [QSA, L]
##### Plugins #####
#RewriteRule ^<(admin)>/ - [L]
RewriteCond %(REQUEST_URI) !^<(admin|install|webservice)>
RewriteRule ^<([0-9a-zA-Z]+)>/<(0,1)$ /plugins.php?magi xmod=$1 [QSA, L]
RewriteRule ^<([0-9a-zA-Z]+)/[/](/[0-9]+)/>/<(0,1)$ /plugins.php?magi xmod=$1 &page=$2 [QSA, L]
RewriteRule ^<([0-9a-zA-Z]+)/[/](?: sort)/[/](/[a-zA-Z]+)/>/<(0,1)$ /plugins.php?
magi xmod=$1 &sort=$2 [QSA, L]
##### Additional params #####
RewriteRule ^<([0-9a-zA-Z]+)/[/]([-_0-9a-zA-Z]+)/[-](/[0-9]+)/>/<(0,1)$ /plugins.php?
magi xmod=$1 &pstring1=$2&pnum1=$3 [QSA, L]
RewriteRule ^<([0-9a-zA-Z]+)/[/]([-_0-9a-zA-Z]+)/>/<(0,1)$ /plugins.php?magi xmod=$1 &pstring1=$2
[QSA, L]
RewriteRule ^<([0-9a-zA-Z]+)/[/]([-_0-9a-zA-Z]+)/[/]([-_0-9a-zA-Z]+)/>/<(0,1)$ /plugins.php?
magi xmod=$1 &pstring1=$2&pstring2=$3 [QSA, L]
RewriteRule ^<([0-9a-zA-Z]+)/[/](\d{4}/\d{2}/\d{2})[/]([-_0-9a-zA-Z]+)/[-](/[0-9]+)/>/<(0,1)$
/plugins.php?magi xmod=$1 &pdate=$2&pstring1=$3&pnum1=$4 [QSA, L]
RewriteRule ^<([0-9a-zA-Z]+)/[/]([-_0-9a-zA-Z]+)/[-](/[0-9]+)/[/]([-_0-9a-zA-Z]+)/[-](/[0-
9]+)/>/<(0,1)$ /plugins.php?magi xmod=$1 &pstring1=$2&onum1=$3&pstring2=$4&onum2=$5 [QSA, L]

```



```
^([\0-9a-zA-Z]+)/([\0-9a-zA-Z]+)-([\0-9]+)/([\0-9a-zA-Z)+)-([\0-9]+)/([\0-9a-zA-Z)+)-([\0-9]+)/([\0-9a-zA-Z)+)-([\0-9)+)/(\0,1)$ /plugins.php?magixmod=$1&pstring1=$2&pnum1=$3&pstring2=$4&pnum2=$5&pstring3=$6&pnum3=$7 [QSA, L]
```