

```

# Apache Server Configs v2.2.0 | MIT License
# https://github.com/h5bp/server-configs-apache

# (!) Using `.htaccess` files slows down Apache, therefore, if you have access
# to the main server config file (usually called `httpd.conf`), you should add
# this logic there: http://httpd.apache.org/docs/current/howto/htaccess.html.

# Techniques in here adapted from all over, including:
# Kroc Camen: camendesign.com/.htaccess
# perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
# Sample .htaccess file of CMS MODx: modxcms.com

<IfModule mod_rewrite.c>
  Options +FollowSymlinks
  RewriteEngine On

  # -----
  # Adaptive-Images
  # -----

  # Hint: What directory is this .htaccess file saved in?
  RewriteBase /html-template/

  # Add any directories you wish to omit from the Adaptive-Images process on a new line, as
  # RewriteCond %{REQUEST_URI} !some-directory
  # RewriteCond %{REQUEST_URI} !another-directory

  RewriteCond %{REQUEST_URI} !assets

  # Send any GIF, JPG, or PNG request that IS NOT stored inside one of the above directories
  # to adaptive-images.php so we can select appropriately sized versions
  RewriteRule \.(?:jpe?g|gif|png)$ adaptive-images.php

  # -----
  # END Adaptive-Images
  # -----

</IfModule>

# -----
#

```

```

# initializer
# -----

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *every*
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|ogg|m4a|ogv|mp4|m4v|webm|svg|svgz|eot|ttf|otf|woff|ico|webp|appcache|manifest|
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# #####
# # CROSS-ORIGIN RESOURCE SHARING (CORS) #
# #####

# -----
# | Cross-domain AJAX requests |
# -----

# Allow cross-origin AJAX requests.
# http://code.google.com/p/html5security/wiki/CrossOriginRequestSecurity
# http://enable-cors.org/

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# | CORS-enabled images |
# -----

"

```

```
# Send the CORS header for images when browsers request it.
# https://developer.mozilla.org/en-US/docs/HTML/CORS_Enabled_Image
# http://blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# http://hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images
```

```
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    <FilesMatch "\.(curl|gif|ico|jpe?g|png|svgz?|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>
```

```
# -----
# | Web fonts access |
# -----
```

```
# Allow access to web fonts from all domains.
```

```
<IfModule mod_headers.c>
  <FilesMatch "\.(eot|otf|tt[cf]|woff)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>
```

```
# #####
# # ERRORS #
# #####
```

```
# -----
# | 404 error prevention for non-existing redirected folders |
# -----
```

```
# Prevent Apache from returning a 404 error as the result of a rewrite
# when the directory with the same name does not exist.
# http://httpd.apache.org/docs/current/content-negotiation.html#multiviews
# http://www.webmasterworld.com/apache/3808792.htm
```

```
Options -MultiViews
```

```

# -----
# | Custom error messages / pages |
# -----

# Customize what Apache returns to the client in case of an error.
# http://httpd.apache.org/docs/current/mod/core.html#errordocument

# ErrorDocument 404 /404.html

# #####
# # INTERNET EXPLORER #
# #####

# -----
# | Better website experience |
# -----

# Force Internet Explorer to render pages in the highest available mode
# in the various cases when it may not.
# http://hsivonen.iki.fi/doctype/ie-mode.pdf

<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge"
    # `mod_headers` cannot match based on the content-type, however, this
    # header should be send only for HTML pages and not for the other resources
    <FilesMatch "\.(appcache|atom|crx|css|curl|eot|f4[abpv]|flv|gif|html|icol|jpe?g|js|json|ld
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|tt[cf]|vcf|vtt|webapp|web[mp]|woff|xml|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# -----
# | Cookie setting from iframes |
# -----

# Allow cookies to be set from iframes in Internet Explorer.
# http://msdn.microsoft.com/en-us/library/ms537343.aspx
# http://www.w3.org/TR/2000/CR-P3P-20001215/

# <IfModule mod_headers.c>

```

```

# Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
# </IfModule>

# #####
# # MIME TYPES AND ENCODING #
# #####

# -----
# | Proper MIME types for all files |
# -----

<IfModule mod_mime.c>

# Audio
AddType audio/mp4 m4a f4a f4b
AddType audio/ogg oga ogg opus

# Data interchange
AddType application/json json map
AddType application/ld+json jsonld

# JavaScript
# Normalize to standard type.
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript js

# Video
AddType video/mp4 f4v f4p m4v mp4
AddType video/ogg ogv
AddType video/webm webm
AddType video/x-flv flv

# Web fonts
AddType application/font-woff woff
AddType application/vnd.ms-fontobject eot

# Browsers usually ignore the font MIME types and simply sniff the bytes
# to figure out the font type.
# http://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern

# Chrome however, shows a warning if any other MIME types are used for

```

the following fonts.

```
AddType application/x-font-ttf          ttc ttf
AddType font/opentype                   otf
```

Make SVGZ fonts work on the iPad.

<https://twitter.com/FontSquirrel/status/14855840545>

```
AddType    image/svg+xml              svgz
AddEncoding gzip                       svgz
```

Other

```
AddType application/octet-stream      safariextz
AddType application/x-chrome-extension crx
AddType application/x-opera-extension  oex
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall         xpi
AddType application/xml                 atom rdf rss xml
AddType image/webp                      webp
AddType image/x-icon                    cur
AddType text/cache-manifest             appcache manifest
AddType text/vtt                        vtt
AddType text/x-component                htc
AddType text/x-vcard                    vcf
```

</IfModule>

```
# -----
# | UTF-8 encoding |
# -----
```

Use UTF-8 encoding for anything served as `text/html` or `text/plain`.

```
AddDefaultCharset utf-8
```

Force UTF-8 for certain file formats.

<IfModule mod_mime.c>

```
    AddCharset utf-8 .atom .css .js .json .jsonld .rss .vtt .webapp .xml
```

</IfModule>

```
# #####
# # URL REWRITES #
# #####
```

```
# -----
# | Rewrite engine |
# -----

# Turn on the rewrite engine and enable the `FollowSymLinks` option (this is
# necessary in order for the following directives to work).

# If your web host doesn't allow the `FollowSymLinks` option, you may need to
# comment it out and use `Options +SymLinksIfOwnerMatch`, but be aware of the
# performance impact.
# http://httpd.apache.org/docs/current/misc/perf-tuning.html#symlinks

# Also, some cloud hosting services require `RewriteBase` to be set.
# http://www.rackspace.com/knowledge_center/frequently-asked-question/why-is-mod-rewrite-not-working

<IfModule mod_rewrite.c>
    Options +FollowSymLinks
    # Options +SymLinksIfOwnerMatch
    RewriteEngine On
    # RewriteBase /
</IfModule>

# -----
# | Suppressing / Forcing the `www.` at the beginning of URLs |
# -----

# The same content should never be available under two different URLs,
# especially not with and without `www.` at the beginning. This can cause
# SEO problems (duplicate content), and therefore, you should choose one
# of the alternatives and redirect the other one.

# By default `Option 1` (no `www.`) is activated.
# http://no-www.org/faq.php?q=class_b

# If you would prefer to use `Option 2`, just comment out all the lines
# from `Option 1` and uncomment the ones from `Option 2`.

# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----
```

```
# Option 1: rewrite www.example.com + example.com

<IfModule mod_rewrite.c>
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2: rewrite example.com + www.example.com

# Be aware that the following might not be a good idea if you use "real"
# subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#     RewriteCond %{HTTPS} !=on
#     RewriteCond %{HTTP_HOST} !^www\. [NC]
#     RewriteCond %{SERVER_ADDR} !=127.0.0.1
#     RewriteCond %{SERVER_ADDR} !=::1
#     RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# #####
# # SECURITY #
# #####

# -----
# | Clickjacking |
# -----

# Protect website against clickjacking.

# The example below sends the `X-Frame-Options` response header with the value
# `DENY`, informing browsers not to display the web page content in any frame.

# This might not be the best setting for everyone. You should read about the
# other two possible values for `X-Frame-Options`: `SAMEORIGIN` & `ALLOW-FROM`.
# http://tools.ietf.org/html/rfc7034#section-2.1
```

```
# Keep in mind that while you could send the `X-Frame-Options` header for all
# of your site's pages, this has the potential downside that it forbids even
# non-malicious framing of your content (e.g.: when users visit your site using
# a Google Image Search results page).

# Nonetheless, you should ensure that you send the `X-Frame-Options` header for
# all pages that allow a user to make a state changing operation (e.g: pages
# that contain one-click purchase links, checkout or bank-transfer confirmation
# pages, pages that make permanent configuration changes, etc.).

# Sending the `X-Frame-Options` header can also protect your website against
# more than just clickjacking attacks: https://cure53.de/xfo-clickjacking.pdf.

# http://tools.ietf.org/html/rfc7034
# http://blogs.msdn.com/b/ieinternals/archive/2010/03/30/combating-clickjacking-with-x-frame
# https://www.owasp.org/index.php/Clickjacking

# <IfModule mod_headers.c>
#     Header set X-Frame-Options "DENY"
#     <FilesMatch "\.(appcache|atom|crx|css|curl|eot|f4[abpv]|flv|gif|html|ico|jpe?g|js|json|j
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|tt[cf]|vcf|vtt|webapp|web[mp]|woff|xml|xpi)$">
#         Header unset X-Frame-Options
#     </FilesMatch>
# </IfModule>

# -----
# | Content Security Policy (CSP) |
# -----

# Mitigate the risk of cross-site scripting and other content-injection attacks.

# This can be done by setting a `Content Security Policy` which whitelists
# trusted sources of content for your website.

# The example header below allows ONLY scripts that are loaded from the current
# site's origin (no inline scripts, no CDN, etc). This almost certainly won't
# work as-is for your site!

# For more details on how to craft a reasonable policy for your site, read:
# http://html5rocks.com/en/tutorials/security/content-security-policy/ (or the
```

```

# http://www.w3.org/TR/2006/CR-css3-security/Content-Security-Policy.html#the
# specification: http://w3.org/TR/CSP). Also, to make things easier, you can
# use an online CSP header generator such as: http://cspisawesome.com/.

# <IfModule mod_headers.c>
#     Header set Content-Security-Policy "script-src 'self'; object-src 'self'"
#     <FilesMatch "\.(appcache|atom|crx|css|curl|eot|f4[abpw]|flv|gif|htcl|icol|jpe?g|js|json|
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|tt[cf]|vcf|vtt|webapp|web[mp]|woff|xml|xpi)$">
#         Header unset Content-Security-Policy
#     </FilesMatch>
# </IfModule>

# -----
# | File access |
# -----

# Block access to directories without a default document.
# You should leave the following uncommented, as you shouldn't allow anyone to
# surf through every directory on your server (which may includes rather private
# places such as the CMS's directories).

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# -----

# Block access to hidden files and directories.
# This includes directories used by version control systems such as Git and SVN.

<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [F]
</IfModule>

# -----

# Block access to files that can expose sensitive information.
# By default, block access to backup and source files that can be left by some

```

```
# By default, block access to backup and source files that may be left by some
# text editors and can pose a security risk when anyone has access to them.
# http://feross.org/cmsploit/
```

```
# IMPORTANT: Update the `<FilesMatch>` regular expression from below to include
# any files that might end up on your production server and can expose sensitive
# information about your website. These files may include: configuration files,
# files that contain metadata about the project (e.g.: project dependencies),
# build scripts, etc..
```

```
<FilesMatch "(^#.#|\.|(bak|config|dist|fla|in[ci]|log|psd|sh|sql|sw[op])|")$">
```

```
  # Apache < 2.3
```

```
  <IfModule !mod_authz_core.c>
```

```
    Order allow,deny
```

```
    Deny from all
```

```
    Satisfy All
```

```
  </IfModule>
```

```
  # Apache ≥ 2.3
```

```
  <IfModule mod_authz_core.c>
```

```
    Require all denied
```

```
  </IfModule>
```

```
</FilesMatch>
```

```
# -----
# | Reducing MIME type security risks |
# -----
```

```
# Prevent some browsers from MIME-sniffing the response.
```

```
# This reduces exposure to drive-by download attacks and cross-origin data
# leaks, and should be left uncommented, especially if the web server is
# serving user-uploaded content or content that could potentially be treated
# as executable by the browser.
```

```
# http://www.slideshare.net/hasegawayosuke/owasp-hasegawa
```

```
# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-v-comprehensive-protection
```

```
# http://msdn.microsoft.com/en-us/library/ie/gg622941.aspx
```

```
# http://mimesniff.spec.whatwg.org/
```

```
<IfModule mod_headers.c>
    Header set X-Content-Type-Options "nosniff"
</IfModule>

# -----
# | Reflected Cross-Site Scripting (XSS) attacks |
# -----

# (1) Try to re-enable the Cross-Site Scripting (XSS) filter built into the
# most recent web browsers.
#
# The filter is usually enabled by default, but in some cases it may be
# disabled by the user. However, in Internet Explorer for example, it can
# be re-enabled just by sending the `X-XSS-Protection` header with the
# value of `1`.
#
# (2) Prevent web browsers from rendering the web page if a potential reflected
# (a.k.a non-persistent) XSS attack is detected by the filter.
#
# By default, if the filter is enabled and browsers detect a reflected
# XSS attack, they will attempt to block the attack by making the smallest
# possible modifications to the returned web page.
#
# Unfortunately, in some browsers (e.g.: Internet Explorer), this default
# behavior may allow the XSS filter to be exploited, thereby, it's better
# to tell browsers to prevent the rendering of the page altogether, instead
# of attempting to modify it.
#
# http://hackademix.net/2009/11/21/ies-xss-filter-creates-xss-vulnerabilities
#
# IMPORTANT: Do not rely on the XSS filter to prevent XSS attacks! Ensure that
# you are taking all possible measures to prevent XSS attacks, the most obvious
# being: validating and sanitizing your site's inputs.
#
# http://blogs.msdn.com/b/ie/archive/2008/07/02/ie8-security-part-iv-the-xss-filter.aspx
# http://blogs.msdn.com/b/ieinternals/archive/2011/01/31/controlling-the-internet-explorer-;protection-http-header.aspx
# https://www.owasp.org/index.php/Cross-site\_Scripting\_%28XSS%29

# <IfModule mod_headers.c>
```

```
# # (1) (2)
# Header set X-XSS-Protection "1; mode=block"
# <FilesMatch "\.(appcache|atom|crx|css|curl|eot|f4[abpw]|flv|gif|htcl|icol|jpe?g|jsl|json|
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssl|safariextz|svgz?
|swf|tt[cf]|vcf|vtt|webapp|web[mp]|woff|xml|xpi)$">
# Header unset X-XSS-Protection
# </FilesMatch>
# </IfModule>

# -----
# | Secure Sockets Layer (SSL) |
# -----

# Rewrite secure requests properly in order to prevent SSL certificate warnings.
# E.g.: prevent `https://www.example.com` when your certificate only allows
# `https://secure.example.com`.

# <IfModule mod_rewrite.c>
# RewriteCond %{SERVER_PORT} !^443
# RewriteRule ^https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# | HTTP Strict Transport Security (HSTS) |
# -----

# Force client-side SSL redirection.

# If a user types `example.com` in his browser, the above rule will redirect
# him to the secure version of the site. That still leaves a window of
# opportunity (the initial HTTP connection) for an attacker to downgrade or
# redirect the request.

# The following header ensures that browser will ONLY connect to your server
# via HTTPS, regardless of what the users type in the address bar.

# http://tools.ietf.org/html/draft-ietf-websec-strict-transport-sec-14#section-6.1
# http://www.html5rocks.com/en/tutorials/security/transport-layer-security/

# IMPORTANT: Remove the `includeSubDomains` optional directive if the subdomains
# are not using HTTPS.
```

```

# <IfModule mod_headers.c>
#   Header set Strict-Transport-Security "max-age=16070400; includeSubDomains"
# </IfModule>

# -----
# | Server software information                               |
# -----

# Avoid displaying the exact Apache version number, the description of the
# generic OS-type and the information about Apache's compiled-in modules.

# ADD THIS DIRECTIVE IN THE `httpd.conf` AS IT WILL NOT WORK IN THE `.htaccess`!

# ServerTokens Prod

# #####
# # WEB PERFORMANCE                                     #
# #####

# -----
# | Compression                                           |
# -----

<IfModule mod_deflate.c>

# Force compression for mangled headers.
# http://developer.yahoo.com/blogs/ymdn/posts/2010/12/pushing-beyond-gzipping
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-Encoding X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|def
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
<IfModule mod_filter.c>

```

```
AddOutputFilterByType DEFLATE application/atom+xml \
    application/javascript \
    application/json \
    application/ld+json \
    application/rss+xml \
    application/vnd.ms-fontobject \
    application/x-font-ttf \
    application/x-web-app-manifest+json \
    application/xhtml+xml \
    application/xml \
    font/opentype \
    image/svg+xml \
    image/x-icon \
    text/css \
    text/html \
    text/plain \
    text/x-component \
    text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
# -----
# | Content Transformations |
# -----
```

```
# Prevent mobile network providers from modifying the website's content.
# http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9.5.
```

```
# <IfModule mod_headers.c>
#   Header set Cache-Control "no-transform"
# </IfModule>
```

```
# -----
# | ETags |
# -----
```

```
# Remove `ETags` as resources are sent with far-future expires headers.
# http://developer.yahoo.com/performance/rules.html#etags.
```

```
# `FileETag None` doesn't work in all cases.
```

```
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
```

FileETag None

```
# -----
# | Expires headers |
# -----
```

```
# The following expires headers are set pretty far in the future. If you
# don't control versioning with filename-based cache busting, consider
# lowering the cache time for resources such as style sheets and JavaScript
# files to something like one week.
```

```
<IfModule mod_expires.c>
```

```
    ExpiresActive on
    ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
    ExpiresByType text/css "access plus 1 year"
```

```
# Data interchange
```

```
    ExpiresByType application/json "access plus 0 seconds"
```

```
    ExpiresByType application/ld+json "access plus 0 seconds"
```

```
    ExpiresByType application/xml "access plus 0 seconds"
```

```
    ExpiresByType text/xml "access plus 0 seconds"
```

```
# Favicon (cannot be renamed!) and cursor images
```

```
    ExpiresByType image/x-icon "access plus 1 week"
```

```
# HTML components (HTCs)
```

```
    ExpiresByType text/x-component "access plus 1 month"
```

```
# HTML
```

```
    ExpiresByType text/html "access plus 0 seconds"
```

```
# JavaScript
```

```
    ExpiresByType application/javascript "access plus 1 year"
```

Manifest files

```
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

Media

```
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

Web feeds

```
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"
```

Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
```

</IfModule>

```
# -----
# | Filename-based cache busting |
# -----
```

```
# If you're not using a build process to manage your filename version revving,
# you might want to consider enabling the following directives to route all
# requests such as /css/style.12345.css to /css/style.css.
```

```
# To understand why this is important and a better idea than *.css?v231, read:
# http://stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring
```

```
# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpe?g|gif)$ $1.$3 [L]
# </IfModule>
```

```
.. -----  
  
# -----  
# | File concatenation |  
# -----  
  
# Allow concatenation from within specific style sheets and JavaScript files.  
  
# e.g.:  
#  
# If you have the following content in a file  
#  
# <!--#include file="libs/jquery.js" -->  
# <!--#include file="plugins/jquery.timer.js" -->  
#  
# Apache will replace it with the content from the specified files.  
  
# <IfModule mod_include.c>  
# <FilesMatch "\.combined\.js$">  
# Options +Includes  
# AddOutputFilterByType INCLUDES application/javascript application/json  
# SetOutputFilter INCLUDES  
# </FilesMatch>  
# <FilesMatch "\.combined\.css$">  
# Options +Includes  
# AddOutputFilterByType INCLUDES text/css  
# SetOutputFilter INCLUDES  
# </FilesMatch>  
# </IfModule>
```