

```

# BEGIN HTML5 Boilerplate

###
### This contains the HTML5 Boilerplate .htaccess that can be found at:
### https://github.com/h5bp/server-configs/blob/master/apache/.htaccess
###
### Added:
### Block access to WordPress files that reveal version information.
###
### Removed:
### Expires headers:      Use W3 Total Cache
### ETag removal:        Use W3 Total Cache
### Start rewrite engine: Handled by WordPress
### Suppress/force www:  Handled by WordPress
### Custom 404 page:      Handled by WordPress
###
### Commented out by default:
### Options -MultiViews:  Causes a server 500 error on most shared hosts
###
### Anytime you update this file the .htaccess file in the root of your
### WordPress install is automatically updated with the changes whenever
### the permalinks are flushed or set (see lib/htaccess.php)
###

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *ever!
  <FilesMatch "\.(appcache|crx|css|eot|gif|html|ico|jpe?
gl|js|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogv|otf|pdf|png|safariextz|svg|svgz|tfl|vcf|webm|webp|
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

```

```

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
# Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# CORS-enabled images (@crossorigin)
# -----

# Send CORS headers if browsers request them; enabled by default for images.
# developer.mozilla.org/en/CORS_Enabled_Image
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    # mod_headers, y u no match by Content-Type?!
    <FilesMatch "\.(gif|ico|jpe?g|png|svg|svgz|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

```

```
<IfModule mod_headers.c>
  <FilesMatch "\.(eot|font\.css|otf|ttc|ttf|woff)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js jsonp
AddType application/json            json

# Audio
AddType audio/mp4                   m4a f4a f4b
AddType audio/ogg                    oga ogg

# Video
AddType video/mp4                    mp4 m4v f4v f4p
AddType video/ogg                     ogv
AddType video/webm                     webm
AddType video/x-flv                     flv

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml                svg svgz
AddEncoding gzip                      svgz

# Webfonts
AddType application/font-woff         woff
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf        ttf ttc
AddType font/opentype                 otf

# Assorted types
AddType application/octet-stream      safariextz
AddType application/x-chrome-extension crx
```

```
AddType application/x-opera-extension      oex
AddType application/x-shockwave-flash     swf
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall           xpi
AddType application/xml                   rss atom xml rdf
AddType image/webp                        webp
AddType image/x-icon                      ico
AddType text/cache-manifest               appcache manifest
AddType text/vtt                          vtt
AddType text/x-component                  htc
AddType text/x-vcard                      vcf
```

```
# -----
# Allow concatenation from within specific js and css files
# -----
```

```
# e. g. Inside of script.combined.js you could have
# <!--#include file="libs/jquery-1.5.0.min.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.
```

```
# This is not in use in the boilerplate as it stands. You may
# choose to use this technique if you do not have a build process.
```

```
<FilesMatch "\.combined\.js$" >
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
</FilesMatch>
```

```
<FilesMatch "\.combined\.css$" >
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
</FilesMatch>
```

```
# -----
# Gzip compression
# -----
```

```
<IfModule mod_deflate.c>
```

```

# Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-bu
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\
(4,13)$ HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines as
# `AddOutputFilterByType` is still in the core directives)
<IfModule mod_filter.c>
  AddOutputFilterByType DEFLATE application/atom+xml \
                                application/javascript \
                                application/json \
                                application/rss+xml \
                                application/vnd.ms-fontobject \
                                application/x-font-ttf \
                                application/xhtml+xml \
                                application/xml \
                                font/opentype \
                                image/svg+xml \
                                image/x-icon \
                                text/css \
                                text/html \
                                text/plain \
                                text/x-component \
                                text/xml

</IfModule>

</IfModule>

# -----
# Prevent mobile network providers from modifying your site
# -----

# The following header prevents modification of your code over 3G on some
# European providers.

```

```
# This is the official 'bypass' suggested by O2 in the UK.

# <IfModule mod_headers.c>
# Header set Cache-Control "no-transform"
# </IfModule>

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above).

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
# Set Keep-Alive Header
# -----

# Keep-Alive allows the server to send multiple requests through one
# TCP-connection. Be aware of possible disadvantages of this setting. Turn on
# if you serve a lot of static content.

# <IfModule mod_headers.c>
# Header set Connection Keep-Alive
# </IfModule>

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, specify a path or regex in the Location directive.

# <IfModule mod_headers.c>
# Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
OUR IND CNT\""
# </IfModule>
```

```
# -----  
# Built-in filename-based cache busting  
# -----  
  
# If you're not using the build script to manage your filename version rewving,  
# you might want to consider enabling this, which will route requests for  
# `/css/style.20110203.css` to `/css/style.css`.  
  
# To understand why this is important and a better idea than all.css?v1231,  
# please refer to the bundled documentation about `.htaccess`.  
  
# <IfModule mod_rewrite.c>  
# RewriteCond %{REQUEST_FILENAME} !-f  
# RewriteCond %{REQUEST_FILENAME} !-d  
# RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1.$3 [L]  
# </IfModule>  
  
# -----  
# Prevent SSL cert warnings  
# -----  
  
# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent  
# https://www.example.com when your cert only allows https://secure.example.com  
  
# <IfModule mod_rewrite.c>  
# RewriteCond %{SERVER_PORT} !^443  
# RewriteRule ^https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]  
# </IfModule>  
  
# -----  
# Force client-side SSL redirection  
# -----  
  
# If a user types "example.com" in her browser, the above rule will redirect her  
# to the secure version of the site. That still leaves a window of opportunity  
# (the initial HTTP connection) for an attacker to downgrade or redirect the  
# request. The following header ensures that browser will **only** connect to  
# your server via HTTPS, regardless of what users type in the address bar.  
  
# <IfModule mod_headers.c>
```

```
# Header set Strict-Transport-Security max-age=16070400;
# </IfModule>

# -----
# Prevent 404 errors for non-existing redirected folders
# -----

# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the
# same name does not exist.
# webmasterworld.com/apache/3808792.htm

# Options -MultiViews

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml

# -----
# A little more security
# -----

# To avoid displaying the exact version number of Apache being used, add the
# following to httpd.conf (it will not work in .htaccess):
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a
# default document Usually you should leave this activated, because you
# shouldn't allow everybody to surf through every folder on your server (which
# includes rather private places like CMS system folders).
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a
# period. This includes directories used by version control systems such as
```



```
-----
# Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
</IfModule>

# Block access to backup and source files. These files may be left by some
# text/html editors and pose a great security danger, when anyone can access
# them.
<FilesMatch "(\\. (bak| config| dist| fl| incl| ini| log| psd| sh| sql| swp)| (^)$">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS:
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Rename session cookie to something else, than PHPSESSID
# php_value session.name sid

# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of )
# php_flag magic_quotes_gpc Off

# Do not show you are using PHP
# Note: Move this line to php.ini since it won't work in .htaccess
```

```
# INSTRUCTIONS: THIS FILE IS FOR PHP 5.4. ONLY! DO NOT WORK WITH PHP 5.3!  
# php_flag expose_php Off  
  
# Level of log detail - log all errors  
# php_value error_reporting -1  
  
# Write errors to log file  
# php_flag log_errors On  
  
# Do not display errors in browser (production - Off, development - On)  
# php_flag display_errors Off  
  
# Do not display startup errors (production - Off, development - On)  
# php_flag display_startup_errors Off  
  
# Format errors in plain text  
# Note: Leave this setting 'On' for xdebug's var_dump() output  
# php_flag html_errors Off  
  
# Show multiple occurrence of error  
# php_flag ignore_repeated_errors Off  
  
# Show same errors from different sources  
# php_flag ignore_repeated_source Off  
  
# Size limit for error messages  
# php_value log_errors_max_len 1024  
  
# Don't precede error with string (doesn't accept empty string, use whitespace if you need)  
# php_value error_prepend_string " "  
  
# Don't prepend to error (doesn't accept empty string, use whitespace if you need)  
# php_value error_append_string " "  
  
# Increase cookie security  
<IfModule mod_php5.c>  
    php_value session.cookie_httponly true  
</IfModule>  
  
# END HTML5 Boilerplate  
  
# BEGIN HEADERS
```

```
# BEGIN WORDPRESS
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine On
```

```
RewriteBase /
```

```
RewriteRule ^index\.php$ - [L]
```

```
RewriteRule ^assets/css/(.*) /wp-content/themes/roots/assets/css/$1 [QSA,L]
```

```
RewriteRule ^assets/js/(.*) /wp-content/themes/roots/assets/js/$1 [QSA,L]
```

```
RewriteRule ^assets/img/(.*) /wp-content/themes/roots/assets/img/$1 [QSA,L]
```

```
RewriteRule ^plugins/(.*) /wp-content/plugins/$1 [QSA,L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule . /index.php [L]
```

```
</IfModule>
```

```
# END WordPress
```