

```
# BULLETPROOF .52 >>>>>> SECURE .HTACCESS

# PHP/PHP.INI HANDLER/CACHE CODE
# Use BPS Custom Code to add php/php.ini Handler and Cache htaccess code and to save it permi
# Most Hosts do not have/use/require php/php.ini Handler htaccess code

# TURN OFF YOUR SERVER SIGNATURE
# Suppresses the footer line server version number and ServerName of the serving virtual ho:
ServerSignature Off

# DO NOT SHOW DIRECTORY LISTING
# Disallow mod_autoindex from displaying a directory listing
# If a 500 Internal Server Error occurs when activating Root BulletProof Mode
# copy the entire DO NOT SHOW DIRECTORY LISTING and DIRECTORY INDEX sections of code
# and paste it into BPS Custom Code and comment out Options -Indexes
# by adding a # sign in front of it.
# Example: #Options -Indexes
Options -Indexes

# DIRECTORY INDEX FORCE INDEX.PHP
# Use index.php as default directory index file. index.html will be ignored.
# If a 500 Internal Server Error occurs when activating Root BulletProof Mode
# copy the entire DO NOT SHOW DIRECTORY LISTING and DIRECTORY INDEX sections of code
# and paste it into BPS Custom Code and comment out DirectoryIndex
# by adding a # sign in front of it.
# Example: #DirectoryIndex index.php index.html /index.php
DirectoryIndex index.php index.html /index.php

# BRUTE FORCE LOGIN PAGE PROTECTION
# PLACEHOLDER ONLY
# Use BPS Custom Code to add Brute Force Login protection code and to save it permanently.
# See this link: http://forum.ait-pro.com/forums/topic/protect-login-page-from-brute-force-1
# for more information.

# BPS ERROR LOGGING AND TRACKING
# Use BPS Custom Code to modify/edit/change this code and to save it permanently.
# BPS has premade 403 Forbidden, 400 Bad Request, 410 Gone and 404 Not Found files that are
# to track and log 403, 400, 410 and 404 errors that occur on your website. When a hacker at
# hack your website the hackers IP address, Host name, Request Method, Referering link, the
# requested resource, the user agent of the hacker and the query string used in the hack at:
# 011 BPS has files for htaccess protected so that only you can view them
```

```
# All BPS log files are ntaccess protected so that only you can view them.
# The 400.php, 403.php, 404.php and 410.php files are located in /wp-content/plugins/bulletproof-security/
# The 400, 410 and 403 Error logging files are already set up and will automatically start logging
# after you install BPS and have activated BulletProof Mode for your Root folder.
# If you would like to log 404 errors you will need to copy the logging code in the BPS 404.php
# to your Theme's 404.php template file. Simple instructions are included in the BPS 404.php
# You can open the BPS 404.php file using the WP Plugins Editor.
# NOTE: By default WordPress automatically looks in your Theme's folder for a 404.php Theme
```

```
ErrorDocument 400 /wp-content/plugins/bulletproof-security/400.php
ErrorDocument 401 default
ErrorDocument 403 /wp-content/plugins/bulletproof-security/403.php
ErrorDocument 404 /404.php
ErrorDocument 410 /wp-content/plugins/bulletproof-security/410.php
```

```
# DENY ACCESS TO PROTECTED SERVER FILES AND FOLDERS
```

```
# Use BPS Custom Code to modify/edit/change this code and to save it permanently.
# Files and folders starting with a dot: .htaccess, .htpasswd, .errordocs, .logs
RedirectMatch 403 \.(htaccess|htpasswd|errordocs|logs)$
```

```
# WP-ADMIN/INCLUDES
```

```
# Use BPS Custom Code to remove this code permanently.
```

```
RewriteEngine On
RewriteBase /
RewriteRule ^wp-admin/includes/ - [F]
RewriteRule !^wp-includes/ - [S=3]
RewriteRule ^wp-includes/[^\.]+\.\php$ - [F]
RewriteRule ^wp-includes/js/tinymce/langs/.+\.\php - [F]
RewriteRule ^wp-includes/theme-compat/ - [F]
```

```
# WP REWRITE LOOP START
```

```
RewriteEngine On
RewriteBase /
RewriteRule ^index\.\php$ - [L]
```

```
# REQUEST METHODS FILTERED
```

```
# If you want to allow HEAD Requests use BPS Custom Code and
# remove/delete HEAD from the Request Method filter.
```

```
# Example: RewriteCond %{REQUEST_METHOD} ^(TRACE|DELETE|TRACK|DEBUG) [NC]
```

```
# The TRACE, DELETE, TRACK and DEBUG Request methods should never be removed.
```

```
RewriteCond %{REQUEST_METHOD} ^(HEAD|TRACE|DELETE|TRACK|DEBUG) [NC]
```

```
#####
```

```
RewriteRule ^(.*)$ - [F]
```

```
# PLUGINS/THEMES AND VARIOUS EXPLOIT FILTER SKIP RULES
```

```
# To add plugin/theme skip/bypass rules use BPS Custom Code.
```

```
# The [S] flag is used to skip following rules. Skip rule [S=12] will skip 12 following Rew
```

```
# The skip rules MUST be in descending consecutive number order: 12, 11, 10, 9...
```

```
# If you delete a skip rule, change the other skip rule numbers accordingly.
```

```
# Examples: If RewriteRule [S=5] is deleted than change [S=6] to [S=5], [S=7] to [S=6], etc.
```

```
# If you add a new skip rule above skip rule 12 it will be skip rule 13: [S=13]
```

```
# Adminer MySQL management tool data populate
```

```
RewriteCond %{REQUEST_URI} ^/wp-content/plugins/adminer/ [NC]
```

```
RewriteRule . - [S=12]
```

```
# Comment Spam Pack MU Plugin - CAPTCHA images not displaying
```

```
RewriteCond %{REQUEST_URI} ^/wp-content/mu-plugins/custom-anti-spam/ [NC]
```

```
RewriteRule . - [S=11]
```

```
# Peters Custom Anti-Spam display CAPTCHA Image
```

```
RewriteCond %{REQUEST_URI} ^/wp-content/plugins/peters-custom-anti-spam-image/ [NC]
```

```
RewriteRule . - [S=10]
```

```
# Status Updater plugin fb connect
```

```
RewriteCond %{REQUEST_URI} ^/wp-content/plugins/fb-status-updater/ [NC]
```

```
RewriteRule . - [S=9]
```

```
# Stream Video Player - Adding FLV Videos Blocked
```

```
RewriteCond %{REQUEST_URI} ^/wp-content/plugins/stream-video-player/ [NC]
```

```
RewriteRule . - [S=8]
```

```
# XCloner 404 or 403 error when updating settings
```

```
RewriteCond %{REQUEST_URI} ^/wp-content/plugins/xcloner-backup-and-restore/ [NC]
```

```
RewriteRule . - [S=7]
```

```
# BuddyPress Logout Redirect
```

```
RewriteCond %{QUERY_STRING} action=logout&redirect_to=http%3A%2F%2F(.*) [NC]
```

```
RewriteRule . - [S=6]
```

```
# redirect_to=
```

```
RewriteCond %{QUERY_STRING} redirect_to=(.*) [NC]
```

```
RewriteRule . - [S=5]
```

```
# Login Plugins Password Reset And Redirect 1
```

```
RewriteCond %{QUERY_STRING} action=resetpass&key=(.*) [NC]
```

```
RewriteRule . - [S=4]
```

```
# Login Plugins Password Reset And Redirect 2
```

```
RewriteCond %{QUERY_STRING} action=rp&key=(.*) [NC]
```

```
RewriteRule . - [S=3]
```



```

RewriteCond %{QUERY_STRING} http\ : [NC,OR]
RewriteCond %{QUERY_STRING} https\ : [NC,OR]
RewriteCond %{QUERY_STRING} \=| | | [NC,OR]
RewriteCond %{QUERY_STRING} ^(\. *) /self /(\. *) $ [NC,OR]
RewriteCond %{QUERY_STRING} ^(\. *) cPath=http: //(\. *) $ [NC,OR]
RewriteCond %{QUERY_STRING} (\<| %3C) . *script. *(\>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<| %3C)( [^s] *s) +cript. *(>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} (\<| %3C) . *embed. *(\>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<| %3C)( [^e] *e) +mbed. *(>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} (\<| %3C) . *object. *(\>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<| %3C)( [^o] *o) +bject. *(>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} (\<| %3C) . *iframe. *(\>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<| %3C)( [^i] *i) +frame. *(>| %3E) [NC,OR]
RewriteCond %{QUERY_STRING} base64_encode. * \(\. *) [NC,OR]
RewriteCond %{QUERY_STRING} base64_(en|de)code[ ^() * \([ ^ ] * \) ] [NC,OR]
RewriteCond %{QUERY_STRING} GLOBALS(= \[ | \[ %0-9A-Z ] (0,2) ) [OR]
RewriteCond %{QUERY_STRING} _REQUEST(= \[ | \[ %0-9A-Z ] (0,2) ) [OR]
RewriteCond %{QUERY_STRING} ^. * \(\(| \)| <| >| %3c| %3e) . * [NC,OR]
RewriteCond %{QUERY_STRING} ^. * \(\x00| \x04| \x08| \x0d| \x1b| \x20| \x3c| \x3e| \x7f) . * [NC,OR]
RewriteCond %{QUERY_STRING} (NULL|OUTFILE|LOAD_FILE) [OR]
RewriteCond %{QUERY_STRING} (\. (1, ) /) +(motd| etc| bin) [NC,OR]
RewriteCond %{QUERY_STRING} (localhost| loopback| 127\ . 0\ . 0\ . 1) [NC,OR]
RewriteCond %{QUERY_STRING} (<| >| ' | %0A| %0D| %27| %3C| %3E| %00) [NC,OR]
RewriteCond %{QUERY_STRING} concat[ ^ \() * \[ [NC,OR]
RewriteCond %{QUERY_STRING} union([ ^s] *s) +elect [NC,OR]
RewriteCond %{QUERY_STRING} union([ ^a] *a) +ll([ ^s] *s) +elect [NC,OR]
RewriteCond %{QUERY_STRING} \-[sdcrl]. *(allow_url_includel allow_url_fopenl safe_model_disable_f
RewriteCond %{QUERY_STRING} (;| <| >| ' | " | \)| %0A| %0D| %22| %27| %3C| %3E| %00) . *
(& /\*| union| select| insert| drop| delete| update| cast| create| char| convert| alter| declare| order| scr
RewriteCond %{QUERY_STRING} (sp_executesql) [NC]
RewriteRule ^(\. *) $ - [F]
# END BPSQSE BPS QUERY STRING EXPLOITS
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
# WP REWRITE LOOP END

# DENY BROWSER ACCESS TO THESE FILES
# Use BPS Custom Code to modify/edit/change this code and to save it permanently.
# wp-config.php, bb-config.php, php.ini, php5.ini, readme.html
# Replace 88. 77. 66. 55 with your current IP address and remove the

```

*# pound sign # in front of the Allow from line of code below to be able to access
any of these files directly from your Browser.*

```
<FilesMatch "^(wp-config\.php|php\.ini|php5\.ini|readme\.html|bb-config\.php)">
```

```
Order Allow,Deny
```

```
Deny from all
```

```
#Allow from 88.77.66.55
```

```
</FilesMatch>
```

```
# HOTLINKING/FORBID COMMENT SPAMMERS/BLOCK BOTS/BLOCK IP/REDIRECT CODE
```

```
# PLACEHOLDER ONLY
```

```
# Use BPS Custom Code to add custom code and save it permanently here.
```

```
# BEGIN W3TC Browser Cache
```

```
<IfModule mod_deflate.c>
```

```
    <IfModule mod_headers.c>
```

```
        Header append Vary User-Agent env=!dont-vary
```

```
    </IfModule>
```

```
    AddOutputFilterByType DEFLATE text/css text/x-component application/x-javascript app  
text/html text/richtext image/svg+xml text/plain text/xsd text/xsl text/xml image/x-icon app
```

```
    <IfModule mod_mime.c>
```

```
        # DEFLATE by extension
```

```
        AddOutputFilter DEFLATE js css htm html xml
```

```
    </IfModule>
```

```
</IfModule>
```

```
# END W3TC Browser Cache
```

```
# BEGIN W3TC Page Cache core
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine On
```

```
    RewriteBase /
```

```
    RewriteCond %{HTTP:Accept-Encoding} gzip
```

```
    RewriteRule .* - [E=W3TC_ENC:_gzip]
```

```
    RewriteCond %{HTTP_COOKIE} w3tc_preview [NC]
```

```
    RewriteRule .* - [E=W3TC_PREVIEW:_preview]
```

```
    RewriteCond %{REQUEST_METHOD} !=POST
```

```
    RewriteCond %{QUERY_STRING} ="
```

```
    RewriteCond %{REQUEST_URI} \/$
```

```
    RewriteCond %{HTTP_COOKIE} !(comment_author|wp\-postpass|w3tc_logged_out|wordpress_logg
```

```
    RewriteCond "%{DOCUMENT_ROOT}/wp-content/cache/page_enhanced/%{HTTP_HOST}/%{REQUEST_URI}
```

```
    RewriteRule .* "/wp-content/cache/page_enhanced/%{HTTP_HOST}/%{REQUEST_URI}/_index%{ENV:
```

```
</IfModule>
```

```
# END W3TC Page Cache core
```

