

```
# Use PHP5.5 as default
# AddHandler application/x-httpd-php55 .php
# php_flag session.auto_start 0

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and features.
# FollowSymLinks must be enabled for this to work.

Options +FollowSymLinks

# Disable directory browsing
Options -Indexes

RewriteEngine on

# Convert index.php?request=controller/action/params to controller/action/params
RewriteRule ^([a-zA-Z0-9_-]+)$ index.php?request=$1

# Direct all requests to index.php
RewriteCond %{REQUEST_FILENAME} -s
RewriteRule ^.*$ - [NC,L]
RewriteRule ^.*$ index.php [NC,L]

# Protect .htaccess and .htpasswd files
<FilesMatch "^\.ht">
    Order allow,deny
    Deny from all
</FilesMatch>

# Protect config.* files
<FilesMatch "^config(\.)*.*$">
    Order deny,allow
    Deny from all
</FilesMatch>

# Protect files depending on extension
<FilesMatch "^(.*)\.(incl|inc|.php|tpl|tpl|.php|sql|txt|dat|csv|excel|dll)$">
    Order deny,allow
```

```
order deny, allow
Deny from all
</FilesMatch>

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *ev
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|oggl|m4al|ogvl|mp4l|m4vl|webml|svg|svgz|eot|ttf|otf|woff|icol|webpl|appcache|manifest|
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain ajax requests, disabled.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".
```

```

<FilesMatch "\.(ttf|ttd|otf|eot|woff|font. css)$">
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</FilesMatch>

# -----
# Proper MIME type for all files
# -----

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js

# Audio
AddType audio/ogg                   oga ogg
AddType audio/mp4                    m4a

# Video
AddType video/ogg                    ogv
AddType video/mp4                    mp4 m4v
AddType video/webm                   webm

# SVG.
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml                svg svgz
AddEncoding gzip                     svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf        ttf ttc
AddType font/opentype                 otf
AddType application/x-font-woff       woff

# Assorted types
AddType image/x-icon                  ico
AddType image/webp                    webp
AddType text/cache-manifest           appcache manifest

```

```

AddType text/x-component          htc
AddType application/x-chrome-extension crx
AddType application/x-xpinstall   xpi
AddType application/octet-stream  safariextz
AddType text/x-vcard              vcf

# -----
# Gzip compression
# -----

# Force deflate for mangled headers developer, yahoo.com/blogs/ydn/posts/2010/12/pushing-bey
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$ ^((gzip|deflate)\s)
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

<IfModule mod_gzip.c>
mod_gzip_on Yes
mod_gzip_dechunk Yes
mod_gzip_item_include file .(html?|txt|css|js|php|pl)$
mod_gzip_item_include handler ^cgi-script$
mod_gzip_item_include mime ^text/. *
mod_gzip_item_include mime ^application/x-javascript.*
mod_gzip_item_exclude mime ^image/. *
mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.*
</ifModule>

# HTML, TXT, CSS, JavaScript, JSON, XML, HTC:
<IfModule filter_module.c>
  FilterDeclare    COMPRESS
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/html
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/css
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/plain
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/xml
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $text/x-component
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/javascript
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/json
  FilterProvider   COMPRESS DEFLATE resp=Content-Type $application/xml

```

```

FilterProvider COMPRESS DEFLATE resp=Content-Type $application/xhtml+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/rss+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/atom+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/vnd.ms-fontobject
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/svg+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/x-icon
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/x-font-ttf
FilterProvider COMPRESS DEFLATE resp=Content-Type $font/opentype
FilterChain COMPRESS
FilterProtocol COMPRESS DEFLATE change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
    # Legacy versions of Apache
    #AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
    #AddOutputFilterByType DEFLATE application/javascript
    #AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
    #AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml application/atom-
    #AddOutputFilterByType DEFLATE image/x-icon image/svg+xml application/vnd.ms-fontobject a
font/opentype
</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with cachebusting query params like
# <script src="application.js?20100608">
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week" or so.

<IfModule mod_expires.c>
    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault "access plus 1 month"

```

cache, apache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")

ExpiresByType text/cache-manifest "access plus 0 seconds"

Your document html

ExpiresByType text/html "access plus 0 seconds"

Data

ExpiresByType text/xml "access plus 0 seconds"

ExpiresByType application/xml "access plus 0 seconds"

ExpiresByType application/json "access plus 0 seconds"

Feed

ExpiresByType application/rss+xml "access plus 1 hour"

ExpiresByType application/atom+xml "access plus 1 hour"

Favicon (cannot be renamed)

ExpiresByType image/x-icon "access plus 1 week"

Media: images, video, audio

ExpiresByType image/gif "access plus 1 month"

ExpiresByType image/png "access plus 1 month"

ExpiresByType image/jpg "access plus 1 month"

ExpiresByType image/jpeg "access plus 1 month"

ExpiresByType video/ogg "access plus 1 month"

ExpiresByType audio/ogg "access plus 1 month"

ExpiresByType video/mp4 "access plus 1 month"

ExpiresByType video/webm "access plus 1 month"

HTC files (css3pie)

ExpiresByType text/x-component "access plus 1 month"

Webfonts

ExpiresByType font/truetype "access plus 1 month"

ExpiresByType font/opentype "access plus 1 month"

ExpiresByType application/x-font-woff "access plus 1 month"

ExpiresByType image/svg+xml "access plus 1 month"

ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

CSS and JavaScript

ExpiresByType text/css "access plus 1 year"

ExpiresByType application/javascript "access plus 1 year"

```
<IfModule mod_headers.c>
  Header append Cache-Control "public"
</IfModule>

</IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above). If
# needed, un-comment the following rules.

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, uncomment and specify a path or regex in the Location directive
```

```
# <IfModule mod_headers.c>
#   <Location />
#     Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IW
CNT\""
#   </Location>
# </IfModule>

# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs - especially not with
# without "www." at the beginning, since this can cause SEO problems (duplicate content).
# That's why you should choose one of the alternatives and redirect the other one.

# By default option 1 (no "www.") is activated. Remember: Shorter URLs are sexier.
# no-www.org/faq.php?q=class_b

# If you rather want to use option 2, just comment out all option 1 lines
# and uncomment option 2.
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----

# Option 1:
# Rewrite "www.example.com -> example.com"

<IfModule mod_rewrite.c>
  SetEnv HTTP_MOD_REWRITE php
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+\)$ [NC]
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2:
# To rewrite "example.com -> www.example.com" uncomment the following lines.
# Be aware that the following rule might not be a good idea if you
# use "real" subdomains for certain parts of your website.
```

```
# <IfModule mod_rewrite.c>
# RewriteCond %{HTTPS} !=on
# RewriteCond %{HTTP_HOST} !^www\.+$ [NC]
# RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version revving,
# you might want to consider enabling this, which will route requests for
# /css/style.20110203.css to /css/style.css

# To understand why this is important and a better idea than all.css?v1231,
# read: github.com/paulirish/html5-boilerplate/wiki/Version-Control-with-Cachebusting

# Uncomment to enable.
<IfModule mod_rewrite.c>
  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteCond %{REQUEST_FILENAME} !-d
  RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1.$3 [L]
</IfModule>

# -----
# Prevent SSL cert warnings
# -----

# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.example.com when your cert only allows https://secure.example.com
# Uncomment the following lines to use this feature.

#<IfModule mod_rewrite.c>
#RewriteCond %{SERVER_PORT} !=443
#RewriteRule ^ https://brightideassoftwaresolutions.com%{REQUEST_URI} [R=301,L]
#</IfModule>

# -----
# Prevent 404 errors for non-existing redirected folders
# -----
```

```
# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name does
# e.g. /blog/hello : webmasterworld.com/apache/3808792.htm
```

Options -MultiViews

```
# -----
# Custom 404 page
# -----
```

```
# You can add custom pages to handle 500 or 403 pretty easily, if you like.
```

```
ErrorDocument 404 /404.html
```

```
ErrorDocument 403 /403.html
```

```
# -----
# UTF-8 encoding
# -----
```

```
# Use UTF-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

```
# Force UTF-8 for a number of file formats
```

```
AddCharset utf-8 .html .css .js .xml .json .rss .atom
```

```
# -----
# A little more security
# -----
```

```
# Do we want to advertise the exact version number of Apache we're running?
```

```
# Probably not.
```

```
## This can only be enabled if used in httpd.conf - It will not work in .htaccess
```

```
# ServerTokens Prod
```

```
# "-Indexes" will have Apache block users from browsing folders without a default document
```

```
# Usually you should leave this activated, because you shouldn't allow everybody to surf through
```

```
# every folder on your server (which includes rather private places like CMS system folders).
```

```
<IfModule mod_autoindex.c>
```

```
Options -Indexes
```

```
</IfModule>
```

```
# Block access to "hidden" directories whose names begin with a period. This
```

```
# includes directories used by mailer control systems such as Sendmail or Postfix.
```

Includes directories used by version control systems such as Subversion or Git.

```
<IfModule mod_rewrite.c>
```

```
    RewriteRule "(^/)\$" - [F]
```

```
</IfModule>
```

*# If your server is not already configured as such, the following directive
should be uncommented in order to set PHP's register_globals option to OFF.
This closes a major security hole that is abused by most XSS (cross-site
scripting) attacks. For more information: http://php.net/register_globals
#*

IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS :

#

*# Your server does not allow PHP directives to be set via .htaccess. In that
case you must make this change in your php.ini file instead. If you are
using a commercial web host, contact the administrators for assistance in
doing this. Not all servers allow local php.ini files, and they should
include all PHP configurations (not just this one), or you will effectively
reset everything to PHP defaults. Consult www.php.net for more detailed
information about setting PHP directives.*

```
# php_flag register_globals Off
```

```
# Rename session cookie to something else, than PHPSESSID
```

```
# php_value session.name sid
```

```
# Do not show you are using PHP
```

```
# Note: Move this line to php.ini since it won't work in .htaccess
```

```
# php_flag expose_php Off
```

```
# Level of log detail - log all errors
```

```
# php_value error_reporting -1
```

```
# Write errors to log file
```

```
# php_flag log_errors On
```

```
# Do not display errors in browser (production - Off, development - On)
```

```
# php_flag display_errors Off
```

```
# Do not display startup errors (production - Off, development - On)
```

```
# php_flag display_startup_errors Off
```

```
.. - . . . . .
```

```
# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

# -----
# Mobile specific server config
# -----

# blackberry types - http://goo.gl/A696I
AddType application/x-bb-appworld      bbaw
AddType text/vnd.rim.location.xloc     xloc
AddType text/x-vcard                   vcf

# nokia types - http://goo.gl/LU1bM
# http://wiki.forum.nokia.com/index.php/How_to_enable_OTA_(Over_The_Air)_SIS_install_from_y
AddType application/octet-stream       six
AddType application/vnd.symbian.install sis

# prevent mobile transcoding -
# <FilesMatch "\.(php|cgi|pl)$">
#   <IfModule mod_headers.c>
```

```

# Header append Cache-Control "no-transform"
# Header append Vary "User-Agent, Accept"
# </IfModule>
# </FilesMatch>

# Mobile Redirection Script is used to detect if user is viewing the site
# from mobile device. If the script detects the user is viewing from
# mobile phone, they will be redirected to the mobile version of the site.
# One thing to note is that if you want to allow the user on the mobile version
# of your site to have the option to switch to desktop version, you may consider
# using other methods like JavaScript or PHP at http://detectmobilebrowser.com/
#
# To use the script, first, uncomment the lines below,
# second, change 'http://www.example.com/mobile' to the URL of your mobile site.

# RewriteCond %{HTTP_USER_AGENT}
android|avantgo|blackberry|blazer|compal|elaine|fennec|hiptop|iemobile|ip(hone|od)|iris|kindle
|maemo|mipd|mmp|opera\ m(ob|in)i|palm(\ os)?|phone|p(ixi|re)\|plucker|pocket|psp|symbian|t(
|browser|link)|vodafone|wap|windows\ (cel|phone)|xda|xiino [NC,OR]
# RewriteCond %{HTTP_USER_AGENT} ^^(1207| 6310| 6590| 3gsol 4thpl 50[1-6]i| 770s| 802s| a\ wal abac| ai
)| ai(kol|rn)| al(av|cal|co)| amoi| an(ex|ny|yu)| aptul| ar(ch|go)| as(tel|us)| attw| au(d|l|-ml|r\ |s\
)| avan| be(ck|ll|nq)| bi(1bl|rd)| bl(ack|az)| br(el|v)w| bumb| bu\-(n|w)| c55\| capi| ccual| cdm\|-| cel|ll|
| co(mpl|nd)| crawl| da(it|ll|ng)| dbtel| dc\|-|s| devil| di|cal| dmobl| do(cl|p)| ol| ds(12| \-d)| el(49| ai)| em(12|
| 7)0| os| wal| ze)| fet|cl| fly(\-|_|)g| \ |ul| g560| genel| gf\|-|s| g\|-|mol| go(\. |w|od)| gr(ad|un)| hai| el| hci| ti| hd\
| il| ip)| hs\|-|cl| ht(c(\-| | |_)al| gl| pl| sl| t)| tp)| hu(aw|tc)| i\-(20| gol| ma)| i230| iac(\ | \-
| \)| ibrol| ideal| ig01| ikom| im1k| innol| ipaq| irisl| ja(ct|v)| al| jbro| jemul| jigs| kddi| keji| kgt(\ | \)| ki
| kyo(cl|k)| le(nol|xi)| lg(\ |gl| \|(kl|ll|w)| 50| 54| e\|-|e|\ | \-[a-w])| libw| lynx| ml\|-|w| m3gal| m50\| ma(ct|
|crl|me(d|l|rc|ri)| mi(o|l|oal|ts)| mme| mo(0|1|02| bil| del| dol| t(\-| \ | ol|v)| zz)| mt(50| pl| v\ |)| mubpl| myu
| 3| n30(0| 2)| n50(0| 2| 5)| n7(0(0| 1)| 10)| ne((cl|m)\-
| onl| tf| wf| wgl| wt)| nok(6| i)| nzph| o2i| ml| op(ct|il|wv)| oran| owg| p800| pan(al| dl| t)| pdx| gl| pg(13| \-([1-
| 8]| c))| phi|l| pi|rel| pl(ay| uc)| pn\|-2| po(ck| r|tl| se)| prox| psi| ol| pt\|-gl| qa\|-al| qc(07| 12| 21| 32| 60| \-[2-
)| qtek| r380| r600| raxl| rim9| ro(vel| zo)| s55\| sa(ge| mal| mml| msl| nyl| va)| sc(01| h\|-| ool| p\|-)| sdk\| se
| shar| sie(\-| m)| sk\|-0| sl(45| id)| sm(a|l| ar| b3| it| t5)| so(ft| ny)| sp(01| h\|-| v\|-| v\
)| sy(01| mb)| t2(18| 50)| t6(00| 10| 18)| ta(gt|lk)| tc\|-| tdg\|-| tel(il| m)| tim\|-| t\|-mol| to(pl| sh)| ts(
| m3| m5)| tx\|-9| up(\. |bl| gl| si)| utst| v400| v750| veril| vi(rg| te)| vk(40| 5[0-3]| \-
|v)| vm40| vodal| vul| cl| vx(52| 53| 60| 61| 70| 80| 81| 83| 85| 98)| w3c(\-| \ |)| webcl| whi| ti| wi(g\ | l| ncl| nw)| um| bl
| your| zet| ol| zte\|-) [NC]
# RewriteRule ^$ http://www.example.com/mobile [R,L]

```