```
# BEGIN WPSuperCache
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
#If you serve pages from behind a proxy you may want to change 'RewriteCond %{HTTPS} on' to
AddDefaultCharset UTF-8
RewriteCond %{REQUEST_URI} !^.*[^/]$
RewriteCond %{REQUEST_URI} !^.*//.*$
RewriteCond %{REQUEST_METHOD} !POST
RewriteCond %{QUERY_STRING} !.*=.*
RewriteCond %{HTTP:Cookie} !^.*(comment_author_|wordpress_logged_in|wp-postpass_).*$
RewriteCond %{HTTP:X-Wap-Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP:Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP_USER_AGENT} !^.*(2.0\ MMP|240x320|400X240|AvantGo|BlackBerry|Blazer|Cellp
RewriteCond %{HTTP_user_agent} !^(w3c\ |w3c-|acs-|alav|alca|amoi|audi|avan|benq|bird|blac|bl
RewriteCond %{HTTP:Accept-Encoding} gzip
RewriteCond %{HTTPS} on
RewriteCond %{DOCUMENT_ROOT}/wp-content/cache/supercache/%{SERVER_NAME}/$1/index-https.html.
RewriteRule ^(.*) "/wp-content/cache/supercache/%{SERVER_NAME}/$1/index-https.html.gz" [L]

RewriteCond %{REQUEST_URI} !^.*[^/]$
RewriteCond %{REQUEST_URI} !^.*//.*$
RewriteCond %{REQUEST_METHOD} !POST
RewriteCond %{QUERY_STRING} !.*=.*
RewriteCond %{HTTP:Cookie} !^.*(comment_author_|wordpress_logged_in|wp-postpass_).*$
RewriteCond %{HTTP:X-Wap-Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP:Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP_USER_AGENT} !^.*(2.0\ MMP|240x320|400X240|AvantGo|BlackBerry|Blazer|Cellp
RewriteCond %{HTTP_user_agent} !^(w3c\ |w3c-|acs-|alav|alca|amoi|audi|avan|benq|bird|blac|bl
RewriteCond %{HTTP:Accept-Encoding} gzip
RewriteCond %{HTTPS} !on
RewriteCond %{DOCUMENT_ROOT}/wp-content/cache/supercache/%{SERVER_NAME}/$1/index.html.gz -f
RewriteRule ^(.*) "/wp-content/cache/supercache/%{SERVER_NAME}/$1/index.html.gz" [L]

RewriteCond %{REQUEST_URI} !^.*[^/]$
RewriteCond %{REQUEST_URI} !^.*//.*$
RewriteCond %{REQUEST_METHOD} !POST
RewriteCond %{QUERY_STRING} !.*=.*
RewriteCond %{HTTP:Cookie} !^.*(comment_author_|wordpress_logged_in|wp-postpass_).*$
RewriteCond %{HTTP:X-Wap-Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP:Profile} !^[a-z0-9\"]+ [NC]
```

```
RewriteCond %{HTTP:Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP_USER_AGENT} !^.*(2.0\ MMP| 240x320| 400X240| AvantGo| BlackBerry| Blazer| Cellp
RewriteCond %{HTTP_user_agent} !^(w3c\ |w3c-|acs-|alav|alca|amoi|audi|avan|benq|bird|blac|bl
RewriteCond %{HTTPS} on
RewriteCond %{DOCUMENT_ROOT}/wp-content/cache/supercache/%{SERVER_NAME}/$1/index-https.html
RewriteRule ^(.*) "/wp-content/cache/supercache/%{SERVER_NAME}/$1/index-https.html" [L]

RewriteCond %{REQUEST_URI} !^.*[^/]$
RewriteCond %{REQUEST_URI} !^.*//.*$
RewriteCond %{REQUEST_METHOD} !POST
RewriteCond %{QUERY_STRING} !.*=.*
RewriteCond %{HTTP:Cookie} !^.*(comment_author_| wordpress_logged_in| wp-postpass_).*$
RewriteCond %{HTTP:X-Wap-Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP:Profile} !^[a-z0-9\"]+ [NC]
RewriteCond %{HTTP_USER_AGENT} !^.*(2.0\ MMP| 240x320| 400X240| AvantGo| BlackBerry| Blazer| Cellp
RewriteCond %{HTTP_user_agent} !^(w3c\ |w3c-|acs-|alav|alca|amoi|audi|avan|benq|bird|blac|bl
RewriteCond %{HTTPS} !on
RewriteCond %{DOCUMENT_ROOT}/wp-content/cache/supercache/%{SERVER_NAME}/$1/index.html -f
RewriteRule ^(.*) "/wp-content/cache/supercache/%{SERVER_NAME}/$1/index.html" [L]
</IfModule>

# END WPSuperCache

# BEGIN Better WP Security
Options -Indexes

<files .htaccess>
Order allow,deny
Deny from all
</files>

<files readme.html>
Order allow,deny
Deny from all
</files>

<files readme.txt>
Order allow,deny
Deny from all
</files>
```

```
<files install.php>
Order allow,deny
Deny from all
</files>

<files wp-config.php>
Order allow,deny
Deny from all
</files>

<IfModule mod_rewrite.c>
RewriteEngine On

RewriteRule ^wp-admin/includes/ - [F,L]
RewriteRule !^wp-includes/ - [S=3]
RewriteCond %{SCRIPT_FILENAME} !^(.*)wp-includes/ms-files.php
RewriteRule ^wp-includes/[^/]+\.php$ - [F,L]
RewriteRule ^wp-includes/js/tinymce/langs/.+\.php - [F,L]
RewriteRule ^wp-includes/theme-compat/ - [F,L]

RewriteCond %{REQUEST_METHOD} ^(TRACE|DELETE|TRACK) [NC]
RewriteRule ^(.*)$ - [F,L]

RewriteRule ^login/?$ /wp-login.php?5o4gite1dqbnodm2csmhl [R,L]

RewriteCond %{HTTP_COOKIE} !^.*wordpress_logged_in_.*$
RewriteRule ^admin/?$ /wp-login.php?5o4gite1dqbnodm2csmhl&redirect_to=/wp-admin/ [R,L]

RewriteRule ^admin/?$ /wp-admin/?5o4gite1dqbnodm2csmhl [R,L]

RewriteRule ^register/?$ /wp-login.php?5o4gite1dqbnodm2csmhl&action=register [R,L]

RewriteCond %{SCRIPT_FILENAME} !^(.*)admin-ajax\.php
RewriteCond %{HTTP_REFERER} !^(.*)tappmd.com/wp-admin
RewriteCond %{HTTP_REFERER} !^(.*)tappmd.com/wp-login\.php
RewriteCond %{HTTP_REFERER} !^(.*)tappmd.com/login
RewriteCond %{HTTP_REFERER} !^(.*)tappmd.com/admin
RewriteCond %{HTTP_REFERER} !^(.*)tappmd.com/register
RewriteCond %{QUERY_STRING} !^5o4gite1dqbnodm2csmhl
RewriteCond %{QUERY_STRING} !^action=logout
RewriteCond %{QUERY_STRING} !^action=rp
```

```
RewriteCond %{QUERY_STRING} !^action=register
RewriteCond %{QUERY_STRING} !^action=postpass
RewriteCond %{HTTP_COOKIE} !^.*wordpress_logged_in_.*$
RewriteRule ^.*wp-admin/?|^.*wp-login\.php /not_found [R,L]

RewriteCond %{QUERY_STRING} ^loggedout=true
RewriteRule ^.*$ /wp-login.php?5o4gite1dqbnodm2csmh1 [R,L]
</IfModule>
# END Better WP Security

<files wp-config.php>
order allow,deny
deny from all
</files>

<IfModule mod_deflate.c>
  AddOutputFilterByType DEFLATE text/css text/x-component application/x-javascript applicati
</IfModule>

<IfModule mod_mime.c>
  AddType text/css .css
  AddType text/x-component .htc
  AddType application/x-javascript .js
  AddType application/javascript .js2
  AddType text/javascript .js3
  AddType text/x-js .js4
  AddType text/html .html .htm
  AddType text/richtext .rtf .rtx
  AddType image/svg+xml .svg .svgz
  AddType text/plain .txt
  AddType text/xsd .xsd
  AddType text/xsl .xsl
  AddType text/xml .xml
  AddType video/asf .asf .asx .wax .wmv .wmx
  AddType video/avi .avi
  AddType image/bmp .bmp
  AddType application/java .class
  AddType video/divx .divx
  AddType application/msword .doc .docx
  AddType application/vnd.ms-fontobject .eot
  AddType application/x-msdownload .exe
```

```
    AddType image/gif .gif
    AddType application/x-gzip .gz .gzip
    AddType image/x-icon .ico
    AddType image/jpeg .jpg .jpeg .jpe
    AddType application/json .json
    AddType application/vnd.ms-access .mdb
    AddType audio/midi .mid .midi
    AddType video/quicktime .mov .qt
    AddType audio/mpeg .mp3 .m4a
    AddType video/mp4 .mp4 .m4v
    AddType video/mpeg .mpeg .mpg .mpe
    AddType application/vnd.ms-project .mpp
    AddType application/x-font-otf .otf
    AddType application/vnd.oasis.opendocument.database .odb
    AddType application/vnd.oasis.opendocument.chart .odc
    AddType application/vnd.oasis.opendocument.formula .odf
    AddType application/vnd.oasis.opendocument.graphics .odg
    AddType application/vnd.oasis.opendocument.presentation .odp
    AddType application/vnd.oasis.opendocument.spreadsheet .ods
    AddType application/vnd.oasis.opendocument.text .odt
    AddType audio/ogg .ogg
    AddType application/pdf .pdf
    AddType image/png .png
    AddType application/vnd.ms-powerpoint .pot .pps .ppt .pptx
    AddType audio/x-realaudio .ra .ram
    AddType application/x-shockwave-flash .swf
    AddType application/x-tar .tar
    AddType image/tiff .tif .tiff
    AddType application/x-font-ttf .ttf .ttc
    AddType audio/wav .wav
    AddType audio/wma .wma
    AddType application/vnd.ms-write .wri
    AddType application/vnd.ms-excel .xla .xls .xlsx .xlt .xlw
    AddType application/zip .zip
</IfModule>
<IfModule mod_expires.c>
    ExpiresActive On
    ExpiresByType text/css A31536000
    ExpiresByType text/x-component A31536000
    ExpiresByType application/x-javascript A31536000
    ExpiresByType application/javascript A31536000
```

```
ExpiresByType text/javascript A31536000
ExpiresByType text/x-js A31536000
ExpiresByType text/html A3600
ExpiresByType text/richtext A3600
ExpiresByType image/svg+xml A3600
ExpiresByType text/plain A3600
ExpiresByType text/xsd A3600
ExpiresByType text/xsl A3600
ExpiresByType text/xml A3600
ExpiresByType video/asf A31536000
ExpiresByType video/avi A31536000
ExpiresByType image/bmp A31536000
ExpiresByType application/java A31536000
ExpiresByType video/divx A31536000
ExpiresByType application/msword A31536000
ExpiresByType application/vnd.ms-fontobject A31536000
ExpiresByType application/x-msdownload A31536000
ExpiresByType image/gif A31536000
ExpiresByType application/x-gzip A31536000
ExpiresByType image/x-icon A31536000
ExpiresByType image/jpeg A31536000
ExpiresByType application/json A31536000
ExpiresByType application/vnd.ms-access A31536000
ExpiresByType audio/midi A31536000
ExpiresByType video/quicktime A31536000
ExpiresByType audio/mpeg A31536000
ExpiresByType video/mp4 A31536000
ExpiresByType video/mpeg A31536000
ExpiresByType application/vnd.ms-project A31536000
ExpiresByType application/x-font-otf A31536000
ExpiresByType application/vnd.oasis.opendocument.database A31536000
ExpiresByType application/vnd.oasis.opendocument.chart A31536000
ExpiresByType application/vnd.oasis.opendocument.formula A31536000
ExpiresByType application/vnd.oasis.opendocument.graphics A31536000
ExpiresByType application/vnd.oasis.opendocument.presentation A31536000
ExpiresByType application/vnd.oasis.opendocument.spreadsheet A31536000
ExpiresByType application/vnd.oasis.opendocument.text A31536000
ExpiresByType audio/ogg A31536000
ExpiresByType application/pdf A31536000
ExpiresByType image/png A31536000
ExpiresByType application/vnd.ms-powerpoint A31536000
```

```
        ExpiresByType audio/x-realaudio A31536000

        ExpiresByType image/svg+xml A31536000

        ExpiresByType application/x-shockwave-flash A31536000

        ExpiresByType application/x-tar A31536000

        ExpiresByType image/tiff A31536000

        ExpiresByType application/x-font-ttf A31536000

        ExpiresByType audio/wav A31536000

        ExpiresByType audio/wma A31536000

        ExpiresByType application/vnd.ms-write A31536000

        ExpiresByType application/vnd.ms-excel A31536000

        ExpiresByType application/zip A31536000

</IfModule>
<IfModule mod_deflate.c>
    <IfModule mod_headers.c>
        Header append Vary User-Agent env=!dont-vary
    </IfModule>
        AddOutputFilterByType DEFLATE text/css text/x-component application/x-javascript applica
    <IfModule mod_mime.c>
        # DEFLATE by extension
        AddOutputFilter DEFLATE js css htm html xml
    </IfModule>
</IfModule>
<FilesMatch "\.(css|htc|js|js2|js3|js4|CSS|HTC|JS|JS2|JS3|JS4)$">
    FileETag MTime Size
    <IfModule mod_headers.c>
        Header set Pragma "public"
        Header append Cache-Control "public, must-revalidate, proxy-revalidate"
    </IfModule>
</FilesMatch>
<FilesMatch "\.(html|html|rtf|rtx|svg|svgz|txt|xsd|xsl|xml|HTML|HTM|RTF|RTX|SVG|SVGZ|TXT|XSD
    FileETag MTime Size
    <IfModule mod_headers.c>
        Header set Pragma "public"
        Header append Cache-Control "public, must-revalidate, proxy-revalidate"
    </IfModule>
</FilesMatch>
<FilesMatch "\.
(asf|asx|wax|wmv|wmx|avi|bmp|class|divx|doc|docx|eot|exe|gif|gz|gzip|ico|jpg|jpeg|jpe|json|
    FileETag MTime Size
    <IfModule mod_headers.c>
        Header set Pragma "public"
```

```
        Header append Cache-Control "public, must-revalidate, proxy-revalidate"
    </IfModule>
</FilesMatch>

<IfModule mod_gzip.c>
mod_gzip_on Yes
mod_gzip_dechunk Yes
mod_gzip_item_include file .(html?|txt|css|js|php|pl)$
mod_gzip_item_include handler ^cgi-script$
mod_gzip_item_include mime ^text/.*
mod_gzip_item_include mime ^application/x-javascript.*
mod_gzip_item_exclude mime ^image/.*
mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.*
</IfModule>

# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
</IfModule>

# END WordPress
```