

```

# Apache configuration file
# httpd.apache.org/docs/2.2/mod/quickreference.html

# Note .htaccess files are an overhead, this logic should be in your Apache
# config if possible: httpd.apache.org/docs/2.2/howto/htaccess.html

# Techniques in here adapted from all over, including:
#   Kroc Camen: camendesign.com/.htaccess
#   perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
#   Sample .htaccess file of CMS MODx: modx.com

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *every*
  <FilesMatch "\.(appcache|crx|css|eot|gif|html|ico|jpe?
gl|js|m4a|m4v|manifest|mp4|ogg|ogv|otf|pdf|png|safariextz|svg|svgz|ttf|vcl|webm|webp|
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>


```

```

# -----
# CORS-enabled images (@crossorigin)
# -----

# Send CORS headers if browsers request them; enabled by default for images.
# developer.mozilla.org/en/CORS_Enabled_Image
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute

<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        # mod_headers, y u no match by Content-Type?!
        <FilesMatch "\.(gif|ico|jpe?g|png|svg|svgz|webp)$">
            SetEnvIf Origin ":" IS_CORS
            Header set Access-Control-Allow-Origin "*" env=IS_CORS
        </FilesMatch>
    </IfModule>
</IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

<IfModule mod_headers.c>
    <FilesMatch "\.(eot|font.css|otf|ttf|woff)$">
        Header set Access-Control-Allow-Origin "*"
    </FilesMatch>
</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
#   Normalize to standard type (it's sniffed in IE anyways)
#   tools.ietf.org/html/rfc4329#section-7.2

```

```
AddType application/javascript js jsonp
AddType application/json json
```

Audio

```
AddType audio/mp4 m4a f4a f4b
AddType audio/ogg oga ogg
```

Video

```
AddType video/mp4 mp4 m4v f4v f4p
AddType video/ogg ogv
AddType video/webm webm
AddType video/x-flv flv
```

SVG

Required for svg webfonts on iPad

twitter.com/FontSquirrel/status/14855840545

```
AddType image/svg+xml svg svgz
AddEncoding gzip svgz
```

Webfonts

```
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf ttf ttc
AddType application/x-font-woff woff
AddType font/opentype otf
```

Assorted types

```
AddType application/octet-stream safariextz
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-shockwave-flash swf
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall xpi
AddType application/xml rss atom xml rdf
AddType image/webp webp
AddType image/x-icon ico
AddType text/cache-manifest appcache manifest
AddType text/vtt vtt
AddType text/x-component htc
AddType text/x-vcard vcf
```

-----

```

# Allow concatenation from within specific js and css files
# -----

# e.g. Inside of script.combined.js you could have
# <!--#include file="libs/jquery-1.5.0.min.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# This is not in use in the boilerplate as it stands. You may
# choose to use this technique if you do not have a build process.

<FilesMatch "\.combined\.js$">
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
</FilesMatch>

<FilesMatch "\.combined\.css$">
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
</FilesMatch>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

# Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-bi
<IfModule mod_setenvif.c>
<IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-Encoding X-cept-Encoding X(15)|^(15)|-(15))$ ^((gzip|deflate)\
(4,13))$ HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines as

```

```

# `AddOutputFilterByType` is still in the core directives)
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
                           application/javascript \
                           application/json \
                           application/rss+xml \
                           application/vnd.ms-fontobject \
                           application/x-font-ttf \
                           application/xhtml+xml \
                           application/xml \
                           font/opentype \
                           image/svg+xml \
                           image/x-icon \
                           text/css \
                           text/html \
                           text/plain \
                           text/x-component \
                           text/xml

</IfModule>

</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week".

<IfModule mod_expires.c>

    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault                "access plus 1 month"

```

cache, appcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")

ExpiresByType text/cache-manifest "access plus 0 seconds"

Your document html

ExpiresByType text/html "access plus 0 seconds"

Data

ExpiresByType application/json "access plus 0 seconds"

ExpiresByType application/xml "access plus 0 seconds"

ExpiresByType text/xml "access plus 0 seconds"

Feed

ExpiresByType application/atom+xml "access plus 1 hour"

ExpiresByType application/rss+xml "access plus 1 hour"

Favicon (cannot be renamed)

ExpiresByType image/x-icon "access plus 1 week"

Media: images, video, audio

ExpiresByType audio/ogg "access plus 1 month"

ExpiresByType image/gif "access plus 1 month"

ExpiresByType image/jpeg "access plus 1 month"

ExpiresByType image/png "access plus 1 month"

ExpiresByType video/mp4 "access plus 1 month"

ExpiresByType video/ogg "access plus 1 month"

ExpiresByType video/webm "access plus 1 month"

HTC files (css3pie)

ExpiresByType text/x-component "access plus 1 month"

Webfonts

ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

ExpiresByType application/x-font-ttf "access plus 1 month"

ExpiresByType application/x-font-woff "access plus 1 month"

ExpiresByType font/opentype "access plus 1 month"

ExpiresByType image/svg+xml "access plus 1 month"

CSS and JavaScript

ExpiresByType application/javascript "access plus 1 year"

ExpiresByType text/css "access plus 1 year"

```
</IfModule>
```

```
# -----  
# Prevent mobile network providers from modifying your site  
# -----
```

```
# The following header prevents modification of your code over 3G on some  
# European providers.  
# This is the official 'bypass' suggested by O2 in the UK.
```

```
# <IfModule mod_headers.c>  
# Header set Cache-Control "no-transform"  
# </IfModule>
```

```
# -----  
# ETag removal  
# -----
```

```
# FileETag None is not enough for every server.
```

```
<IfModule mod_headers.c>
```

```
Header unset ETag
```

```
</IfModule>
```

```
# Since we're sending far-future expires, we don't need ETags for  
# static content.
```

```
# developer.yahoo.com/performance/rules.html#etags
```

```
FileETag None
```

```
# -----  
# Stop screen flicker in IE on CSS rollovers  
# -----
```

```
# The following directives stop screen flicker in IE on CSS rollovers - in  
# combination with the "ExpiresByType" rules for images (see above).
```

```
# BrowserMatch "MSIE" brokenvary=1  
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1  
# BrowserMatch "Opera" !brokenvary  
# SetEnvIf brokenvary 1 force-no-vary
```

```
# -----
```

```

# Set Keep-Alive Header
# -----

# Keep-Alive allows the server to send multiple requests through one
# TCP-connection. Be aware of possible disadvantages of this setting. Turn on
# if you serve a lot of static content.

# <IfModule mod_headers.c>
#   Header set Connection Keep-Alive
# </IfModule>

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, specify a path or regex in the Location directive.

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\"", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IVAi
OUR IND CNT\""
# </IfModule>

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and
# features. FollowSymLinks must be enabled for this to work.

# Some cloud hosting services require RewriteBase to be set: goo.gl/H0cPN
# If using the h5bp in a subdirectory, use `RewriteBase /foo` instead where
# 'foo' is your directory.

# If your web host doesn't allow the FollowSymLinks option, you may need to
# comment it out and use `Options +SymLinksIfOwnerMatch`, but be aware of the
# performance impact: http://goo.gl/M1uzd

<IfModule mod_rewrite.c>
# For security reasons, Option followsymlinks cannot be overridden.
# Options +FollowSumlinks

```

```

# -----
Options +SymLinksIfOwnerMatch
# Options +SymLinksIfOwnerMatch
RewriteEngine On
# RewriteBase /
</IfModule>

# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs -
# especially not with and without "www." at the beginning, since this can cause
# SEO problems (duplicate content). That's why you should choose one of the
# alternatives and redirect the other one.

# By default option 1 (no "www.") is activated.
# no-www.org/faq.php?q=class_b

# If you'd prefer to use option 2, just comment out all option 1 lines
# and uncomment option 2.

# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----

# Option 1:
# Rewrite "www.example.com -> example.com".

<IfModule mod_rewrite.c>
    RewriteCond %{HTTPS} !=on
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2:
# Rewrite "example.com -> www.example.com".
# Be aware that the following rule might not be a good idea if you use "real"
# subdomains for certain parts of your website.

```

```

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\.+$ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version revving,
# you might want to consider enabling this, which will route requests for
# `/css/style.20110203.css` to `/css/style.css`.

# To understand why this is important and a better idea than all.css?v1231,
# please refer to the bundled documentation about `.htaccess`.

# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1. $3 [L]
# </IfModule>

# -----
# Prevent SSL cert warnings
# -----

# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.example.com when your cert only allows https://secure.example.com

# <IfModule mod_rewrite.c>
#   RewriteCond %{SERVER_PORT} !^443
#   RewriteRule ^ https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Force client-side SSL redirection
# -----

# If a user types "example.com" in her browser, the above rule will redirect her
# to the secure version of the site. That still leaves a danger of redirects to

```

```
# to the secure version of the site, that still leaves a window of opportunity
# (the initial HTTP connection) for an attacker to downgrade or redirect the
# request. The following header ensures that browser will **only** connect to
# your server via HTTPS, regardless of what users type in the address bar.
```

```
# <IfModule mod_headers.c>
#   Header set Strict-Transport-Security max-age=16070400;
# </IfModule>
```

```
# -----
# Prevent 404 errors for non-existing redirected folders
# -----
```

```
# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the
# same name does not exist.
# webmasterworld.com/apache/3808792.htm
```

Options -MultiViews

```
# -----
# Custom 404 page
# -----
```

```
# You can add custom pages to handle 500 or 403 pretty easily, if you like.
# If you are hosting your site in subdirectory, adjust this accordingly
#   e.g. ErrorDocument 404 /subdir/404.html
```

```
ErrorDocument 404 /404.html
```

```
# -----
# UTF-8 encoding
# -----
```

```
# Use UTF-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

```
# Force UTF-8 for a number of file formats
```

```
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml
```

```
# -----
# A little more security
# -----
```

```
# To avoid displaying the exact version number of Apache being used, add the
# following to httpd.conf (it will not work in .htaccess):
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a
# default document. Usually you should leave this activated, because you
# shouldn't allow everybody to surf through every folder on your server (which
# includes rather private places like CMS system folders).
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a
# period. This includes directories used by version control systems such as
# Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [F]
</IfModule>

# Block access to backup and source files. These files may be left by some
# text/html editors and pose a great security danger, when anyone can access
# them.
<FilesMatch "(\\. (bak|config|dist|fla|inc|ini|log|psd|shl|sql|swp)|\\.")$">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS:
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
```

```
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Rename session cookie to something else, than PHPSESSID
# php_value session.name sid

# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of )
# php_flag magic_quotes_gpc Off

# Do not show you are using PHP
# Note: Move this line to php.ini since it won't work in .htaccess
# php_flag expose_php Off

# Level of log detail - log all errors
# php_value error_reporting -1

# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024
```

```

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule mod_php5.c>
    php_value session.cookie_httponly true
</IfModule>

# -----
# Mobile specific server config
# -----

# Blackberry types - http://goo.gl/A696I
AddType application/x-bb-appworld      bbaw
AddType text/vnd.rim.location.xloc      xloc

# Nokia types - http://goo.gl/LU1bM
# http://wiki.forum.nokia.com/index.php/How_to_enable_OTA_(Over_The_Air)_SIS_install_from_y
AddType application/octet-stream        six
AddType application/vnd.symbian.install sis

# Prevent mobile transcoding
# <FilesMatch "\.(php|cgi|pl)$">
#     <IfModule mod_headers.c>
#         Header append Cache-Control "no-transform"
#         Header append Vary "User-Agent, Accept"
#     </IfModule>
# </FilesMatch>

# Mobile Redirection Script is used to detect if user is viewing the site
# from mobile device. If the script detects the user is viewing from
# mobile phone, they will be redirected to the mobile version of the site.
# One thing to note is that if you want to allow the user on the mobile version
# of your site to have the option to switch to desktop version, you may consider
# using other methods like JavaScript or PHP at http://detectmobilebrowser.com/
#
# To use the script, first, uncomment the lines below,

```

second, change 'http://www.example.com/mobile' to the URL of your mobile site.

#RewriteEngine On

#RewriteBase /

#RewriteCond %{HTTP_USER_AGENT}

android|avantgo|blackberryl|blazer|compal|elaine|fennec|hiptop|iemobile|ip(hone|od)|iris|kindle|maemo|midp|mmp|opera\ m(ob|in)i|palm(\ os)?|phone|p(ixi|re)\|plucker|pocket|psp|symbian|t(-mobile)|webos|windows\ ce|xda|xiino [NC,OR]

#RewriteCond %{HTTP_USER_AGENT} ^(1207|6310|6590|3gso|4thp|50[1-6]i|770s|802s|a\ wal|aba|ac|ai(kolrn)|al(av|cal co)|amoi|an(ex|nyl yw)|aptu|ar(ch|go)|as(tel us)|attw|au(di|l\ -m|r\ |s)|avan|be(c|k|l|l|nq)|bi(1bl rd)|bl(ac|az)|br(el v)|bumbl bw|-(n|u|c55\|capil ccwal cdm|-|cell|l co(mpl nd)|craw|da(it|l|l|ng)|dbtel dc|-sl devil|dical dmobl do(cl p)|ol ds(12l |-d)|el(49l ai)|em(12l u|)|er(icl k0)|esl8|ez([4-7]0|osl wal ze)|fetc|fly(\ -|_)|gl\ ul g560|genel gf|mol go(\. ul od)|gr(ad|un)|hai|el hc|itl hd|-(m|pl t)|hei|-|hi(ptl ta)|hp(\ il ip)|hs|-cl ht(cc|-|_|_|al gl pl sl t)|tp)|hu(aw|tc)|i|-|(20|gol ma)|i230|iac(\ | \ -| \\/)|librol ideal|ig01|ikom|im1k|innol|ipaql|iris|ja(ctl v)|al jbro|jemul|jigsl|kddil|keji|kgt(\ | \\/)|k|kyo(cl k)|le(nol xi)|lg(\ gl \\/(k|l|u|50|54|e|-|e\| \ -[a-w])|libw|lynx|m1|-

ul m3gal m50\|ma(tel uil xo)|mc(01|21|ca)|m\ -crl me(dil rcl ri)|mi(o8|oal ts)|mme|mo(01|02|bil del |ol v)|zz)|mt(50|p1|v\)|mubpl mywal n10(0-2)|n20(2-3)|n30(0|2)|n50(0|2|5)|n7(0(0|1)|10)|ne(cc|lonl tfl wfl wgl wt)|nok(6|i)|nzph|o2i|ml op(til uv)|oran|owg1|p800|pan(al dl t)|pdxgl pg(13l \ -([1-8]|c))|phil|pirel pl(ayl uc)|pn\ -2|po(ckl rtl se)|prox|psi ol pt\ -gl qa\ -al qc(07|12|21|32|60l \ -[2-7]|)|qtek|r380|r600|raksl rim9l ro(vel zo)|s55\|sa(gel mal mml msl nyl va)|sc(01|h\ -|ool p\ -)|sdk\|se(l|l|1)|47l mcl ndl ri|sgh\ -|sharl sie(\ -|m)|sk\ -0|sl(45l id)|sm(al|arl b3l itl t5)|so(ftl ny)|sp(01l |)|sy(01l mb)|t2(18l 50)|t6(00l 10l 18)|ta(gt|lk)|tcl\ -|tdg\ -|tel(il m)|tim\ -|t\ -mol to(pl sh)|ts(l m3l m5)|tx\ -9l up(\. bl gl si)|utstl v400l v750l veril vi(rgl te)|vk(40l 5[0-3]l \ -

v)|vm40l vodal vul cl vx(52l 53l 60l 61l 70l 80l 81l 83l 85l 98)|w3c(\ -| \)|webcl whi tl wi(g\ |ncl nw)|wm1bl |2l g)|yas\ -|yourl zetol zte\ -) [NC]

#RewriteRule ^\$ http://www.example.com/mobile [R,L]