

```
# Apache configuration file
# httpd.apache.org/docs/2.2/mod/quickreference.html

# Note .htaccess files are an overhead, this logic should be in your Apache
# config if possible: httpd.apache.org/docs/2.2/howto/htaccess.html

# Techniques in here adapted from all over, including:
# Kroc Camen: camendesign.com/.htaccess
# perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
# Sample .htaccess file of CMS MODx: modxcms.com

# -----
# Better website experience for IE users
# -----


# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  # mod_headers can't match by content-type, but we don't want to send this header on *every*
  <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|ogg|m4al|ogv|mp4l|m4vl|webml|svg|svgz|eot|ttf|otf|woff|icol|webp|appcache|manifest|)>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----


# Serve cross-domain Ajax requests, disabled by default.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>
```

```
# -----  
# CORS-enabled images (@crossorigin)  
# -----  
  
# Send CORS headers if browsers request them; enabled by default for images.  
# developer.mozilla.org/en/CORS_Enabled_Image  
# blog.chromium.org/2011/07/using-cross-domain-images-in-webgl-and.html  
# hacks.mozilla.org/2011/11/using-cors-to-load-webgl-textures-from-cross-domain-images/  
# wiki.mozilla.org/Security/Reviews/crossoriginAttribute  
  
<IfModule mod_setenvif.c>  
  <IfModule mod_headers.c>  
    # mod_headers, y u no match by Content-Type?!  
    <FilesMatch "\.(gif|png|jpe?g|svg|svgz|ico|webp)$">  
      SetEnvIf Origin ":" IS_CORS  
      Header set Access-Control-Allow-Origin "*" env=IS_CORS  
    </FilesMatch>  
  </IfModule>  
</IfModule>  
  
# -----  
# Webfont access  
# -----  
  
# Allow access from all domains for webfonts.  
# Alternatively you could only whitelist your  
# subdomains like "subdomain.example.com".  
  
<IfModule mod_headers.c>  
  <FilesMatch "\.(ttf|ttc|otf|eot|woff|font.css)$">  
    Header set Access-Control-Allow-Origin "*"  
  </FilesMatch>  
</IfModule>  
  
# -----  
# Proper MIME type for all files  
# -----  
  
# JavaScript  
# Normalize to standard type (it's sniffed in IE anyways)  
# -----
```

```
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js jsonp
AddType application/json          json

# Audio
AddType audio/ogg                oga ogg
AddType audio/mp4                m4a f4a f4b

# Video
AddType video/ogg                ogv
AddType video/mp4                mp4 m4v f4v f4p
AddType video/webm               webm
AddType video/x-flv              f1v

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml            svg svgz
AddEncoding gzip                  svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf      ttf ttc
AddType font/opentype             otf
AddType application/x-font-woff   woff

# Assorted types
AddType image/x-icon              ico
AddType image/webp                 webp
AddType text/cache-manifest       appcache manifest
AddType text/x-component           htc
AddType application/xml            rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall    xpi
AddType application/octet-stream   safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard               vcf
AddType application/x-shockwave-flash swf
AddType text/vtt                  vtt
```

```
# -----
# Allow concatenation from within specific js and css files
# -----

# e.g. Inside of script.combined.js you could have
#   <!--#include file="libs/jquery-1.5.0.min.js" -->
#   <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# This is not in use in the boilerplate as it stands. You may
# choose to use this technique if you do not have a build process.

<FilesMatch "\.combined\.js\$">
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
</FilesMatch>

<FilesMatch "\.combined\.css\$">
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
</FilesMatch>

# -----
# Gzip compression
# -----


<IfModule mod_deflate.c>

# Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-b
<IfModule mod_setenvif.c>
<IfModule mod_headers.c>
  SetEnvIfNoCase ^Accept-Encoding$ X-cept-Encoding $1 "(15)(1)(15)(1)-(15)$" ^((gzip|deflate)) HAVE_Accept-Encoding
  RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
<IfModule mod_filter.c>
```

```
AddOutputFilterByType DEFLATE application/atom+xml \
                           application/javascript \
                           application/json \
                           application/rss+xml \
                           application/vnd.ms-fontobject \
                           application/x-font-ttf \
                           application/xhtml+xml \
                           application/xml \
                           font/opentype \
                           image/svg+xml \
                           image/x-icon \
                           text/css \
                           text/html \
                           text/plain \
                           text/x-component \
                           text/xml

</IfModule>

</IfModule>

# -----
# Expires headers (for better cache control)
# -----


# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
#   www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week".

<IfModule mod_expires.c>
  ExpiresActive on

  # Perhaps better to whitelist expires rules? Perhaps.
  ExpiresDefault          "access plus 1 month"

  # cache.appcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
  ExpiresByType text/cache-manifest    "access plus 0 seconds"
```

```
# Your document html
ExpiresByType text/html "access plus 0 seconds"

# Data
ExpiresByType text/xml "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"

# Feed
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 week"

# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"

</IfModule>

# -----
```

```
# Prevent mobile network providers from modifying your site
# -----
# The following header prevents modification of your code over 3G on some
# European providers.
# This is the official 'bypass' suggested by 02 in the UK.

# <IfModule mod_headers.c>
# Header set Cache-Control "no-transform"
# </IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above).

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
# Set Keep-Alive Header
# -----
```

```
# Keep-Alive allows the server to send multiple requests through one
# TCP-connection. Be aware of possible disadvantages of this setting. Turn on
# if you serve a lot of static content.

# <IfModule mod_headers.c>
#   Header set Connection Keep-Alive
# </IfModule>

# -----
# Cookie setting from iframes
# -----


# Allow cookies to be set from iframes (for IE only)
# If needed, specify a path or regex in the Location directive.

# <IfModule mod_headers.c>
#   Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVi TAIi PSA PSD IVAi
# </IfModule>

# -----
# Start rewrite engine
# -----


# Turning on the rewrite engine is necessary for the following rules and
# features. FollowSymLinks must be enabled for this to work.

# Some cloud hosting services require RewriteBase to be set: goo.gl/H0cPH
# If using the h5bp in a subdirectory, use 'RewriteBase /foo' instead where
# 'foo' is your directory.

# If your web host doesn't allow the FollowSymLinks option, you may need to
# comment it out and use 'Options +SymLinksIfOwnerMatch', but be aware of the
# performance impact: http://goo.gl/M1uzd

<IfModule mod_rewrite.c>
  Options +FollowSymLinks
# Options +SymLinksIfOwnerMatch
  RewriteEngine On
# RewriteBase /
</IfModule>
```

```
# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs -
# especially not with and without "www." at the beginning, since this can cause
# SEO problems (duplicate content). That's why you should choose one of the
# alternatives and redirect the other one.

# By default option 1 (no "www.") is activated.
# no-www.org/faq.php?q=class_b

# If you'd prefer to use option 2, just comment out all option 1 lines
# and uncomment option 2.

# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----
# Option 1:
# Rewrite "www.example.com -> example.com".

<IfModule mod_rewrite.c>
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+)\$ [NC]
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----
# Option 2:
# Rewrite "example.com -> www.example.com".
# Be aware that the following rule might not be a good idea if you use "real"
# subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\.\.+\$ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>
```

```
# -----
# Built-in filename-based cache busting
# -----



# If you're not using the build script to manage your filename version revving,
# you might want to consider enabling this, which will route requests for
# /css/style.20110203.css to /css/style.css

# To understand why this is important and a better idea than all.css?v1231,
# read: github.com/h5bp/html5-boilerplate/wiki/cachebusting

# <IfModule mod_rewrite.c>
#   RewriteCond %{REQUEST_FILENAME} !-f
#   RewriteCond %{REQUEST_FILENAME} !-d
#   RewriteRule ^(.+)\.(\d+)\.(js|css|png|jpg|gif)$ $1.$3 [L]
# </IfModule>

# -----
# Prevent SSL cert warnings
# -----



# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.example.com when your cert only allows https://secure.example.com

# <IfModule mod_rewrite.c>
#   RewriteCond %{SERVER_PORT} !^443
#   RewriteRule ^ https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Prevent 404 errors for non-existing redirected folders
# -----



# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the
# same name does not exist.
# webmasterworld.com/apache/3808792.htm

Options -MultiViews

# -----
# Prevent 404 -----

```

```
# Custom 404 page
# -----
# You can add custom pages to handle 500 or 403 pretty easily, if you like.
# If you are hosting your site in subdirectory, adjust this accordingly
#   e.g. ErrorDocument 404 /subdir/404.html
ErrorDocument 404 /404.html

# -----
# UTF-8 encoding
# -----
# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml

# -----
# A little more security
# -----
# To avoid displaying the exact version number of Apache being used, add the
# following to httpd.conf (it will not work in .htaccess):
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a
# default document. Usually you should leave this activated, because you
# shouldn't allow everybody to surf through every folder on your server (which
# includes rather private places like CMS system folders).
<IfModule mod_autoindex.c>
  Options -Indexes
</IfModule>

# Block access to "hidden" directories or files whose names begin with a
# period. This includes directories used by version control systems such as
# Subversion or Git.
<IfModule mod_rewrite.c>
  RewriteCond %{SCRIPT_FILENAME} -d [OR]
  RewriteCond %{SCRIPT_FILENAME} -f
  RewriteRule "(^/)\." - [F]
  . . . . .
```

```
</IfModule>

# Block access to backup and source files. These files may be left by some
# text/html editors and pose a great security danger, when anyone can access
# them.
<FilesMatch "(\\.(bak|config|sql|f1|al|psd|ini|log|sh|incl|swp|dist)\\.")$">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS:
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Rename session cookie to something else, than PHPSESSID
# php_value session.name sid

# Disable magic quotes (This feature has been DEPRECATED as of PHP 5.3.0 and REMOVED as of 5.4.0)
# php_flag magic_quotes_gpc Off

# Do not show you are using PHP
# Note: Move this line to php.ini since it won't work in .htaccess
# php_flag expose_php Off

# Level of log detail - log all errors
# php_value error_reporting -1
```

```
# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

RewriteEngine On
RewriteCond %{QUERY_STRING} (.*)\b(http|https|ftp)\b://(.*)
RewriteRule ^(.+)\$ - [F,L]

# -----
# FRONT END
# -----
RewriteRule ^welcome index.php?act=pages.
```

```
# -----
# SHOP
# -----
#RewriteRule ^shop-all$                               index.php?act=shop_
#RewriteRule ^shop-all$                               index.php?act=shop_/
#RewriteRule ^shop/(.*)_$
#RewriteRule ^shop-filter/(.*)/(.*)_$
#RewriteRule ^shop-view/(.*)/(.*)/(.*)/(.*)_$
act=shop_/_shop&shop_cat_id=$1&shop_filter=$2&shop_sort=$3&shop_page=$4&shop_view=$5 [B]
#RewriteRule ^shop-by-(.*)/(.*)_$
#RewriteRule ^shop-by-(.*)/(.*)_$
RewriteRule ^item/(.*)/(.*)/(.*)_$
act=shop/_details/_details&prod_cat=$1&prod_name=$2&prod_type=$3

# RewriteRule ^shop-view/(.*)_-(.*)/(.*)_$
# (shop)/index&shop_cat=$1&shop_sort=$2&shop_record=$3
# RewriteRule ^item/(.*)_type-(.*)_$
# (shop)/details&shop_detail_alias=$1&shop_detail_tname=$2
# RewriteRule ^shop-search/name-(.*)_$
# RewriteRule ^add-to-bag$                           index.php?act=(shop)

# -----
# SEARCH
# -----
RewriteRule ^shop-all$                               index.php?act=shop_
RewriteRule ^search-(.*)_/(.*)_$
RewriteRule ^filter-search-(.*)/(.*)/(.*)_$
act=shop/_search&key=$1&shop_cat_id=$2&filter=$3 [B]

# -----
# NEW ARRIVAL
# -----
RewriteRule ^new-arrival$                           index.php?act=shop_/
RewriteRule ^new-arrival/(.*)_$
RewriteRule ^new-arrival-filter/(.*)/(.*)_$
index.php?act=shop_/

# -----
# SALE
# -----
RewriteRule ^sale$                                index.php?act=shop_/

```

```
RewriteRule ^sale/(.*)&index. php?act=shop.
RewriteRule ^sale-filter/(.*)&index. php?act=shop.
[B]

# -----
# BLOG
# -----
RewriteRule ^news&index. php?act=_blog/
RewriteRule ^news-view/(.*)&index. php?act=_blog/
RewriteRule ^read-blog/(.*)&index. php?
act=_blog/detail_blog&category=$1&news_date=$2&news_alias=$3
#RewriteRule ^read/(.*)&index. php?
act=_blog/_details/details&category=$1&news_date=$2&news_alias=$3

# -----
# PRESS
# -----
RewriteRule ^press-release/(.*)&index. php?act=_press/
RewriteRule ^press-release-video&index. php?act=_press/
RewriteRule ^press-release-view/(.*)&index. php?
act=_press/press_print&cat_news=$1&record=$2

# -----
# SERVICE
# -----
RewriteRule ^services/(.*)&index. php?act=_servi/
RewriteRule ^full-services-list&index. php?act=_servi

# -----
# ARTICLE
# -----
RewriteRule ^article&index. php?act=artic/
RewriteRule ^article-view/(.*)&index. php?act=artic/
RewriteRule ^article-read/(.*)&index. php?
act=article/_details/details&category=$1&news_date=$2&news_alias=$3

# -----
# RECIPES
# -----
RewriteRule ^recipes&index. php?act=pages/
RewriteRule ^recipes-view/(.*)&index. php?
```

```
act=pages/_recipes/_index&cat_news=$1&record=$2 index.php?
RewriteRule ^recipes-read/(.+)/(.+)/(.+)$ index.php?
act=recipes/_details/details&category=$1&news_date=$2&news_alias=$3 index.php?
RewriteRule ^ajax-add$ index.php?act=shop_/

# -----
# ORDER
# -----
RewriteRule ^bag$ index.php?act=order
# RewriteRule ^order-login$ index.php?act=order
RewriteRule ^checkout$ index.php?act=order
RewriteRule ^email-order-customer/(.+)$ index.php?
act=admin/emails/order/_customer/_order_placed&order_number=$1
RewriteRule ^email-order-admin/(.+)$ index.php?
act=admin/emails/order/_admin/_order_placed&order_number=$1
RewriteRule ^finish$ index.php?act=order
RewriteRule ^wishlist$ index.php?act=order

# -----
# ACCOUNT
# -----
RewriteRule ^my-account$ index.php?act=account
RewriteRule ^confirm$ index.php?act=confirm
RewriteRule ^confirm-notification-customer/(.+)$ index.php?
act=admin/emails/confirm/_customer/_index&order_number=$1
RewriteRule ^confirm-notification-admin/(.+)$ index.php?
act=admin/emails/confirm/_admin/_index&order_number=$1

RewriteRule ^order-history$ index.php?act=account
RewriteRule ^order-detail/(.+)/history_detail/_orderdetails&oid=$1 index.php?act=account

RewriteRule ^edit-shipping$ index.php?act=account
shipping_shippingdetails
RewriteRule ^edit-account$ index.php?act=account

RewriteRule ^reset-password/(.+)$ index.php?act=account
RewriteRule ^login$ index.php?act=account
RewriteRule ^register$ index.php?act=account
RewriteRule ^logout$ index.php?act=static
```

```
# -----
# PAGES
# -----
RewriteRule ^faqs$ index.php?act=_faq
RewriteRule ^story$ index.php?act=_stor
RewriteRule ^where-to-buy/(.*)& index.php?act=pages,
RewriteRule ^contact-us index.php?act=_book
RewriteRule ^terms-conditions$ index.php?act=pages
RewriteRule ^policy$ index.php?act=pages
RewriteRule ^help$ index.php?act=pages

# -----
# DUAL CURRENCY
# -----
RewriteRule ^change-currency/redirect-(.*)& index.php?act=static

# -----
# DUAL LANGUAGE
# -----
RewriteRule ^change-language/redirect-(.*)& index.php?act=static

# -----
# ADMIN
# -----
RewriteRule ^admin/login$ admin/index.php?act=login
RewriteRule ^admin/logout$ admin/index.php?act=logout
RewriteRule ^admin/forgot-password$ admin/index.php?act=forgot
RewriteRule ^admin/recover-password/(.*)& admin/index.php?act=recover

# -----
# LOGIN
# -----
RewriteRule ^admin/login$ admin/index.php?act=login
RewriteRule ^admin/logout$ admin/index.php?act=logout
RewriteRule ^admin/forgot-password$ admin/index.php?act=forgot
RewriteRule ^admin/recover-password/(.*)& admin/index.php?act=recover

# -----
# SETTINGS
# -----
RewriteRule ^admin/accounts$ admin/index.php?act=accounts
RewriteRule ^admin/general$ admin/index.php?act=general
RewriteRule ^admin/configuration$ admin/index.php?act=configuration
```

```
-----+
RewriteRule ^admin/notifications$ admin/index.php?act=notifications
RewriteRule ^admin/payments$ admin/index.php?act=payments
RewriteRule ^admin/payments-detail/(.*)&act=settings/payment/details/index&id admin/index.php?act=payments-detail
RewriteRule ^admin/server-info$ admin/index.php?act=server-info

# -----
# PAGES
# -----
# RewriteRule ^admin/home$ admin/index.php?act=home
RewriteRule ^admin/home admin/index.php?act=home
act=custom/inspiration/detail/index&ins_id=19 admin/index.php?act=inspiration
RewriteRule ^admin/about admin/index.php?act=about
act=custom/inspiration/detail/index&ins_id=33 admin/index.php?act=inspiration
RewriteRule ^admin/page-slider/(.*)&act=page-slider admin/index.php?act=page-slider
#RewriteRule ^admin/about$ admin/index.php?act=about
RewriteRule ^admin/page-(.*)&act=page admin/index.php?act=page
act=pages/about/about&param=$1&lang=$2 admin/index.php?act=page
RewriteRule ^admin/contact$ admin/index.php?act=contact

# -----
# PAYMENT: BANK
# -----
RewriteRule ^admin/add-payment-bank$ admin/index.php?act=custom/_payment/_bank/category/_add/index
RewriteRule ^admin/payment-bank-detail/(.*)&act=custom/_payment/_bank/category/_details/index&id=$1 admin/index.php?act=custom/_payment/_bank/category/_details
RewriteRule ^admin/payment-bank$ admin/index.php?act=custom/_payment/_bank/category/index
RewriteRule ^admin/payment-bank-view/(.*)&act=custom/_payment/_bank/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?act=custom/_payment/_bank/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/add-payment-bank-account$ admin/index.php?act=custom/_payment/_bank/details/edit&id=$1
RewriteRule ^admin/payment-bank-account-detail/(.*)&act=custom/_payment/_bank/details/edit&id=$1 admin/index.php?act=custom/_payment/_bank/details/edit&id=$1
RewriteRule ^admin/payment-bank-account$ admin/index.php?act=custom/_payment/_bank/details/edit
RewriteRule ^admin/payment-bank-account-view/(.*)&act=custom/_payment/_bank/details/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 admin/index.php?act=custom/_payment/_bank/details/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# NDNFD
# -----
```

# ORDER

# -----

```
RewriteRule ^admin/order$                               admin/index.php?act
RewriteRule ^admin/order-view/(.*)&act=orders/_all&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
RewriteRule ^admin/order-detail/(.*)&act=emails/paid/_customer/_index&order_number=$1 admin/index.php?act
RewriteRule ^admin/order-verified-customer/(.*)&act=emails/paid/_customer/_index&order_number=$1 admin/index.php?
RewriteRule ^admin/order-verified-warehouse/(.*)&act=emails/paid/_warehouse/_index&order_number=$1 admin/index.php?
RewriteRule ^admin/order-shipping/(.*)&act=emails/shipping/_index&order_number=$1 admin/index.php?
RewriteRule ^admin/order-open$                           admin/index.php?act
RewriteRule ^admin/order-open-view/(.*)&act=orders/_open&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
RewriteRule ^admin/order-expired$                      admin/index.php?act
RewriteRule ^admin/order-expired-view/(.*)&act=orders/_expired&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
RewriteRule ^admin/order-cancelled$                   admin/index.php?act
RewriteRule ^admin/order-cancelled-view/(.*)&act=orders/_cancel&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
RewriteRule ^admin/email-order-details-cancelled/(.*)&act=emails/order/_cancel&order_number=$1 admin/index.php?
RewriteRule ^admin/add-orders$                         admin/index.php?act
```

# -----

# PRODUCT

# -----

```
RewriteRule ^admin/product/(.*)&act=products/_all&active=$1&pg=$2&cat=$3&qpp=$4&srt=$5&src=$6&srcval=$7 [B] admin/index.php?act
RewriteRule ^admin/product-view/(.*)&act=products/_active/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B] admin/index.php?
RewriteRule ^admin/product-active$                   admin/index.php?act
RewriteRule ^admin/product-activeview/(.*)&act=products/_active/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B] admin/index.php?
RewriteRule ^admin/product-all$                     admin/index.php?act
RewriteRule ^admin/product-allview/(.*)&act=products/_inactive/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B] admin/index.php?
RewriteRule ^admin/product-inactive$                admin/index.php?act
RewriteRule ^admin/product-inactiveview/(.*)&act=products/_inactive/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B] admin/index.php?
```

# -----

```
RewriteRule admin/product-details(.*)$ admin/index.php?
act=products/details/edit&product_alias=$1
RewriteRule ^admin/add-product$ admin/index.php?act=
RewriteRule ^admin/products/add/index.php admin/add-product

#
# CATEGORY
#
RewriteRule ^admin/category$ admin/index.php?act=
RewriteRule ^admin/add-category$ admin/index.php?act=
RewriteRule ^admin/edit-category$ admin/index.php?act=
#RewriteRule ^admin/detail-category/(.*)/(.*)&act=products/_category/_detail/detail1&cid=$1&cname=$2 admin/index.php?
act=products/_category/_detail/detail1&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/category-view/(.*)&act=products/_category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
act=products/_category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

RewriteRule ^admin/child-category/(.*)&act=products/_category/child/index&cid=$1&cname=$2 admin/index.php?
RewriteRule ^admin/child-category-view/(.*)&act=products/_category/child/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7 admin/index.php?
act=products/_category/child/index&cid=$1&cname=$2&pg=$3&qpp=$4&srt=$5&src=$6&srcval=$7

#
# STOCK MANAGER
#
RewriteRule ^admin/stock-manager$ admin/index.php?act=
RewriteRule ^admin/stock-view/(.*)&act=products/stock/sizemanager&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]
act=products/stock/sizemanager&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6
RewriteRule ^admin/stock-grouped$ admin/index.php?act=
RewriteRule ^admin/stock-grouped-view/(.*)&act=products/stock/_grouped/grouped&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
act=products/stock/_grouped/grouped&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

#
# COLOR MANAGER
#
RewriteRule ^admin/color$ admin/index.php?act=
RewriteRule ^admin/add-color$ admin/index.php?act=
RewriteRule ^admin/color-detail/(.*)&act=products/color/edit/edit&color_id=$1&color_name=$2 admin/index.php?
act=products/color/edit/edit&color_id=$1&color_name=$2
RewriteRule ^admin/color-view/(.*)&act=products/color/view/color&id=$1 admin/index.php?
act=products/color/view/color&id=$1
```

```
act=products/color/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5

#
# -----#
# SIZE MANAGER
# -----#
RewriteRule ^admin/size$ admin/index.php?act=
RewriteRule ^admin/size-detail/(.*)>(.*)> admin/index.php?
act=products/size/_details/edit&size_id=$1&size_name=$2
RewriteRule ^admin/size-view/(.*)>(.*)>(.*)>(.*)>(.*)> admin/index.php?
act=products/size/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/add-size$ admin/index.php?act=
RewriteRule ^admin/edit-size$ admin/index.php?act=


#
# -----#
# CUSTOMER
# -----#
RewriteRule ^admin/customer$ admin/index.php?act=
RewriteRule ^admin/add-customer$ admin/index.php?act=
RewriteRule ^admin/customer/(.*)> admin/index.php?act=
RewriteRule ^admin/customer-details/(.*)>(.*)>(.*)>(.*)>(.*)>(.*)> admin/index.php?
act=customers/details/index&cid=$1&pg=$2&qpp=$3&srt=$4&src=$5&srcval=$6
RewriteRule ^admin/edit-customer/(.*)> admin/index.php?
act=customers/details/_edit/edit&cid=$1
RewriteRule ^admin/customer-view/(.*)>(.*)>(.*)>(.*)>(.*)>(.*)> admin/index.php?
act=customers/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/customer-details/(.*)>(.*)>(.*)>(.*)>(.*)>(.*)> admin/index.php?
act=customers/details/index&cid=$1&pg=$2&qpp=$3&srt=$4&src=$5&srcval=$6


#
# -----#
# SHIPPING
# -----#
RewriteRule ^admin/shipping$ admin/index.php?act=
RewriteRule ^admin/shipping-view/(.*)>(.*)>(.*)>(.*)>(.*)>(.*)> admin/index.php?
act=settings/shipping/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/add-shipping$ admin/index.php?act=
RewriteRule ^admin/shipping/(.*)> admin/index.php?
act=settings/shipping/detail/index&sid=$1
RewriteRule ^admin/edit-shipping/(.*)> admin/index.php?
act=settings/shipping/detail/edit&sid=$1


# -----#
```

```
#  
# CUSTOM  
#  
# -----  
RewriteRule ^admin/menu_bar$ admin/index.php?  
  
# -----  
# PRODUCT: GENDER  
# -----  
RewriteRule ^admin/gender$ admin/index.php?act=custom/products/_gender/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]  
RewriteRule ^admin/gender-view/(.+)/(.+)/(.+)/(.*)-(&.*)_($ act=custom/products/_gender/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]  
RewriteRule ^admin/add-gender$ admin/index.php?act=custom/products/_gender/edit/edit&collection_id=$1&collection_name=$2  
RewriteRule ^admin/detail-gender/(.+)/(.*)$ admin/index.php?  
act=custom/products/_gender/edit/edit&collection_id=$1&collection_name=$2  
  
# -----  
# PRODUCT: COLLECTION  
# -----  
RewriteRule ^admin/collections$ admin/index.php?act=custom/products/_collection/index [B]  
RewriteRule ^admin/collection-view/(.+)/(.+)/(.+)/(.*)-(&.*)_($ act=custom/products/_collection/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]  
RewriteRule ^admin/add-collection$ admin/index.php?  
act=custom/products/_collection/add/add  
RewriteRule ^admin/detail-collection/(.+)/(.*)$ admin/index.php?  
act=custom/products/_collection/edit/edit&collection_id=$1&collection_name=$2  
  
# -----  
# PROMOTION: NEW ARRIVAL  
# -----  
RewriteRule ^admin/new-arrivals$ admin/index.php?act=custom/promotions/new_arrival/index [B]  
RewriteRule ^admin/new-arrivals-view/(.+)/(.+)/(.+)/(.*)-(&.*)_($ act=custom/promotions/new_arrival/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]  
  
# -----  
# PROMOTION: SALE  
# -----  
RewriteRule ^admin/sale$ admin/index.php?act=custom/promotions/_sale/index [B]  
RewriteRule ^admin/sale-view/(.+)/(.+)/(.+)/(.*)-(&.*)_($ act=custom/promotions/_sale/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]
```

```
# -----
# PROMOTION: VOUCHER
# -----
RewriteRule ^admin/voucher$ admin/index.php?act=custom/promotions/vocher [L]
RewriteRule ^admin/voucher-view/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/promotions/_vocher/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
RewriteRule ^admin/add-vocher$ admin/index.php?act=custom/promotions/_vocher/add [L]
RewriteRule ^admin/voucher-details-(.+) admin/index.php?act=custom/promotions/_vocher/_details/details&vocher_id=$1 [L]
RewriteRule ^admin/voucher-detail/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/promotions/_vocher/_details/details&vocher_id=$1&pg=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]
# -----
# GALLERY
# -----
RewriteRule ^admin/project-category$ admin/index.php?act=custom/inspiration/category/index [L]
RewriteRule ^admin/project-category-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/inspiration/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
RewriteRule ^admin/add-project-category$ admin/index.php?act=custom/inspiration/category/add [L]
RewriteRule ^admin/project-category-detail/(.+) admin/index.php?act=custom/inspiration/category/details&ins_id=$1 [L]
RewriteRule ^admin/project$ admin/index.php?act=custom/inspiration/project [L]
RewriteRule ^admin/view-project/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/inspiration/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 [B]
RewriteRule ^admin/add-project$ admin/index.php?act=custom/inspiration/project/add [L]
RewriteRule ^admin/project-detail/(.+) admin/index.php?act=custom/inspiration/detail/index&ins_id=$1 [L]
RewriteRule ^admin/project-meta-tag$ admin/index.php?act=custom/inspiration/meta-tag [L]
# -----
# NEWS
# -----
RewriteRule ^admin/add-news-category$ admin/index.php?act=custom/news/category/_add/add [L]
#RewriteRule ^admin/lang-(.+)/add-news-category$ admin/index.php?act=custom/news/category/_add/add&lang=$1 [L]
RewriteRule ^admin/news-category$ admin/index.php?act=custom/news/category/index [L]
RewriteRule ^admin/news-category-detail/(.+)/(.+)/(.+)$ admin/index.php?act=custom/news/category/_details/details&lang=$1&cid=$2&cname=$3 [L]
RewriteRule ^admin/news-category-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/news/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 [B]
```

```
RewriteRule ^admin/news$ admin/index.php?act=
#RewriteRule ^admin/news-detail/(.*)/(.*)&act=custom/news/details/index&nid=$1&nn=$2 admin/index.php?
RewriteRule ^admin/news-detail/(.*)/(.*)/(.*)&act=custom/news/details/edit&lang=$1&nid=$2&nn=$3 admin/index.php?
RewriteRule ^admin/add-news$ admin/index.php?act=
RewriteRule ^admin/news-view/(.*)/(.*)/(.*)/(.*)&act=custom/news/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 admin/index.php?

# -----
# SERVICES (SPALOSOPHY)
# -----
RewriteRule ^admin/add-services-category$ admin/index.php?
act=custom/_services/category/_add/add
RewriteRule ^admin/services-category$ admin/index.php?act=
RewriteRule ^admin/services-category-detail/(.*)/(.*)&act=custom/_services/category/_details/details&lang=$1&cid=$2&cname=$3 admin/index.php?
RewriteRule ^admin/services-category-view/(.*)&act=custom/_services/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
RewriteRule ^admin/services$ admin/index.php?act=
RewriteRule ^admin/service-view/(.*)&act=custom/_services/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6 admin/index.php?
RewriteRule ^admin/service-detail/(.*)&act=custom/_services/details/edit&lang=$1&nid=$2&nn=$3 admin/index.php?
RewriteRule ^admin/add-services$ admin/index.php?act=

# -----
# PRESS
# -----
RewriteRule ^admin/add-press-category$ admin/index.php?
act=custom/_pressreallease/category/_add/add
#RewriteRule ^admin/lang-(.*)&act=custom/_pressreallease/category/_add/add&lang=$1 admin/index.php?
RewriteRule ^admin/press-category$ admin/index.php?
act=custom/_pressreallease/category/index
RewriteRule ^admin/press-category-detail/(.*)&act=custom/_pressreallease/category/_details/details&lang=$1&cid=$2&cname=$3 admin/index.php?
RewriteRule ^admin/press-category-view/(.*)&act=custom/_pressreallease/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5 admin/index.php?
RewriteRule ^admin/press$ admin/index.php?act=
RewriteRule ^admin/detail-press/(.*)&act= admin/index.php?
```

```
act=custom/_pressrealase/details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-press admin/index.php?act=custom/_pressrealase/add-press
RewriteRule ^admin/view-press/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/_pressrealase/view-press/$1/$2/$3/$4/$5-$6
act=custom/_pressrealase/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

#
# RECIPES
#
RewriteRule ^admin/add-recipes-category$ admin/index.php?act=custom/recipes/_category/add
#RewriteRule ^admin/lang-(.+)/add-recipes-category$ admin/index.php?act=custom/recipes/_category/add
RewriteRule ^admin/recipes-category$ admin/index.php?act=custom/recipes/_category
RewriteRule ^admin/recipes-category-detail/(.+)/(.+)/(.+)$ admin/index.php?act=custom/recipes/_category/detail/$1/$2/$3
act=custom/recipes/_category/_details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/recipes-category-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/recipes/_category/view/$1/$2/$3/$4/$5-$6
act=custom/recipes/_category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/recipes$ admin/index.php?act=custom/recipes/_index
#RewriteRule ^admin/recipes-detail/(.+)/(.+)$ admin/index.php?act=custom/recipes/_category/detail/$1/$2
RewriteRule ^admin/recipes-detail/(.+)/(.+)/(.+)$ admin/index.php?act=custom/recipes/_category/detail/$1/$2/$3
act=custom/recipes/_details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-recipes$ admin/index.php?act=custom/recipes/_add
RewriteRule ^admin/recipes-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/recipes/_category/view/$1/$2/$3/$4/$5-$6
act=custom/recipes/_index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

#
# ARTICLE
#
RewriteRule ^admin/add-article-category$ admin/index.php?act=custom/article/_category/add
#RewriteRule ^admin/lang-(.+)/add-article-category$ admin/index.php?act=custom/article/_category/add
RewriteRule ^admin/article-category$ admin/index.php?act=custom/article/_category
RewriteRule ^admin/article-category-detail/(.+)/(.+)/(.+)$ admin/index.php?act=custom/article/_category/detail/$1/$2/$3
act=custom/article/_category/_details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/article-category-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/article/_category/view/$1/$2/$3/$4/$5-$6
act=custom/article/_category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/article$ admin/index.php?act=custom/article/_index
#RewriteRule ^admin/article-detail/(.+)/(.+)$ admin/index.php?act=custom/article/_category/detail/$1/$2
RewriteRule ^admin/article-detail/(.+)/(.+)/(.+)$ admin/index.php?act=custom/article/_category/detail/$1/$2/$3
act=custom/article/_details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-article$ admin/index.php?act=custom/article/_add
RewriteRule ^admin/article-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?act=custom/article/_category/view/$1/$2/$3/$4/$5-$6
act=custom/article/_index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6
```

```
# -----
# LOCATIONS
# -----
RewriteRule ^admin/add-location-city$ admin/index.php?act=custom/_location/
RewriteRule ^admin/location-city$ admin/index.php?act=
RewriteRule ^admin/location-city-detail/(.+)/(.+)$ admin/index.php?
act=custom/_location/category/_details/details&cid=$1&cname=$2
RewriteRule ^admin/location-city-view/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?
act=custom/_location/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/location$ admin/index.php?act=
#RewriteRule ^admin/location-detail/(.+)/(.+)$ admin/index.php?
act=custom/_location/details/index&nid=$1&nn=$2
RewriteRule ^admin/location-detail/(.+)/(.+)$ admin/index.php?
act=custom/_location/details/edit&nid=$1&nn=$2
RewriteRule ^admin/add-location$ admin/index.php?act=
RewriteRule ^admin/location-view/(.+)/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?
act=custom/_location/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6

# -----
# BACK ORDER
# -----
RewriteRule ^admin/back-order$ admin/index.php?act=custom/order
RewriteRule ^admin/back-order-view/(.+)/(.+)/(.+)/(.+)-(.+)$ admin/index.php?
act=custom/orders/_backorder/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
#RewriteRule ^admin/back-order-detail/(.+) admin/index.php?act=custom/order
RewriteRule ^admin/back-order-detail/(.+) admin/index.php?
act=custom/orders/_backorder/details/index&oid=$1
RewriteRule ^admin/back-order-notification/(.+) admin/index.php?act=emails/b

# -----
# REPORT
# -----
RewriteRule ^admin/reporting$ admin/index.php?act=custom/reports/
RewriteRule ^admin/reporting/sales-by-category$ admin/index.php?
act=custom/reports/sales/items/categories/index
RewriteRule ^admin/reporting/sales-by-category/(.+)/(.+)$ admin/index.php?
act=custom/reports/sales/items/categories/index&date_start=$1&date_end=$2
RewriteRule ^admin/reporting/sales-by-order$ admin/index.php?act=custom/r
RewriteRule ^admin/reporting/sales-by-order/(.+)/(.+)$ admin/index.php?
act=custom/reports/sales/items/orders/index&date_start=$1&date_end=$2
RewriteRule ^admin/reporting/inventor$ admin/index.php?act=custom/re
```

```
-----+
RewriteRule ^admin/reporting/inventory/(.*)&act=custom$ admin/index.php?act=custom/r
RewriteRule ^admin/reporting-export/inventory$ admin/index.php?act=custom
RewriteRule ^admin/reporting-export/inventory/(.*)&act=custom/reports/inventory/export&root=$1 admin/index.php?

#
# LIST ADD MENU FUJIN
#
RewriteRule ^admin/add-menu-category$ admin/index.php?
act=custom/list_add_menu/category/_add/add
RewriteRule ^admin/menu-category$ admin/index.php?act=custom
RewriteRule ^admin/menu-category-detail/(.*)&lang=$1&cid=$2&cname=$3 admin/index.php?
act=custom/list_add_menu/category/_details/details&lang=$1&cid=$2&cname=$3
RewriteRule ^admin/menu-category-view/(.*)&lang=$1&cid=$2&cname=$3 admin/index.php?
act=custom/list_add_menu/category/index&pg=$1&qpp=$2&srt=$3&src=$4&srcval=$5
RewriteRule ^admin/menu$ admin/index.php?act=custom
RewriteRule ^admin/menu-view/(.*)&lang=$1&cid=$2&cname=$3 admin/index.php?
act=custom/list_add_menu/index&pg=$1&cat=$2&qpp=$3&srt=$4&src=$5&srcval=$6
RewriteRule ^admin/menu-detail/(.*)&lang=$1 admin/index.php?
act=custom/list_add_menu/details/edit&lang=$1&nid=$2&nn=$3
RewriteRule ^admin/add-menu admin/index.php?act=custom

#
# VERITRANS
#
RewriteRule ^admin/payment-veritrans$ admin/index.php?
act=custom/_payment/_veritrans/_antikode/admin/index
RewriteRule ^control-veritrans/(.*)&act=order/_payment/_veritrans/_antikode/control&order_number=$1 index.php?
act=order/_payment/_veritrans/_antikode/control&order_number=$1
RewriteRule ^payment-veritrans/(.*)&act=order/_payment/_veritrans/_antikode/web/checkout-process&order_number=$1 index.php?act=order/_payment/_veritrans/_antikode/web/checkout-process&order_number=$1
RewriteRule ^bag-veritrans$ index.php?act=order/_payment/_veritrans/_antikode/bag
RewriteRule ^finish-veritrans$ index.php?act=order/_payment/_veritrans/_antikode/finish

RewriteRule ^email-veritrans-customer-success/(.*)&act=admin/custom/_payment/_veritrans/emails/_success/_customer/_order_placed&order_number=$1 index.php?
act=admin/custom/_payment/_veritrans/emails/_success/_customer/_order_placed&order_number=$1
RewriteRule ^email-veritrans-warehouse-success/(.*)&act=admin/custom/_payment/_veritrans/emails/_success/_warehouse/_index&order_number=$1 index.php?
act=admin/custom/_payment/_veritrans/emails/_success/_warehouse/_index&order_number=$1
RewriteRule ^email-veritrans-admin-success/(.*)&act=admin/custom/_payment/_veritrans/emails/_success/_admin/_order_placed&order_number=$1 index.php?
act=admin/custom/_payment/_veritrans/emails/_success/_admin/_order_placed&order_number=$1
```

```
RewriteRule ^email-veritrans-customer-challange/(. *)$ index.php?
act=admin/custom/_payment/_veritrans/emails/_challenge/_customer/_order_placed&order_number=
RewriteRule ^email-veritrans-admin-challange/(. *)$ index.php?
act=admin/custom/_payment/_veritrans/emails/_challenge/_admin/_order_placed&order_number=$1

RewriteRule ^email-veritrans-customer-failed/(. *)$ index.php?
act=admin/custom/_payment/_veritrans/emails/_failed/_customer/_order_placed&order_number=$1
RewriteRule ^email-veritrans-admin-failed/(. *)$ index.php?
act=admin/custom/_payment/_veritrans/emails/_failed/_admin/_order_placed&order_number=$1

# -----
# PAYPAL
# -----

RewriteRule ^admin/payment-paypal$ admin/index.php?act=custom/_payr
RewriteRule ^control-paypal/(. *)$ index.php?act=order/_payment/_pa
checkout/process&order_number=$1
RewriteRule ^bag-paypal-(. *)/token-(. *)$ index.php?
act=order/_payment/_paypal/_antikode/_bag/control&order_number=$1&token=$2
RewriteRule ^finish-paypal$ index.php?act=order/_payment/_pa

#RewriteRule ^email-paypal-customer-success/(. *)$ index.php?
act=admin/custom/_payment/_paypal/emails/_success/_customer/_order_placed&order_number=$1
#RewriteRule ^email-paypal-warehouse-success/(. *)$ index.php?
act=admin/custom/_payment/_paypal/emails/_success/_warehouse/_index&order_number=$1
#RewriteRule ^email-paypal-admin-success/(. *)$ index.php?
act=admin/custom/_payment/_paypal/emails/_success/_admin/_order_placed&order_number=$1

RewriteRule ^email-paypal-customer-pending/(. *)$ index.php?
act=admin/custom/_payment/_paypal/emails/_challenge/_customer/_order_placed&order_number=$1
RewriteRule ^email-paypal-admin-pending/(. *)$ index.php?
act=admin/custom/_payment/_paypal/emails/_challenge/_admin/_order_placed&order_number=$1

RewriteRule ^email-paypal-customer-failed/(. *)$ index.php?
act=admin/custom/_payment/_paypal/emails/_failed/_customer/_order_placed&order_number=$1
RewriteRule ^email-paypal-admin-failed/(. *)$ index.php?
act=admin/custom/_payment/_paypal/emails/_failed/_admin/_order_placed&order_number=$1

# -----
# PAYPAL
# -----
```

```
RewriteRule ^admin/mailchimp$ admin/index.php?act=custom/email_notification/index&alias=$1

# FRONT END
RewriteRule ^news-category/(.*)&act=custom/email_notification/index$ index.php?act=(news)
RewriteRule ^details-news/(.*)&(.*).*$ index.php?act=(news)

# DUAL LANGUAGE
RewriteRule ^indonesia$ lang_id.php
RewriteRule ^english$ lang_en.php

#ABOUT
RewriteRule ^admin/(.*)&act=custom/language/pages/about/about&lang=$1&param=$2 admin/index.php?

# PRODUCTS
RewriteRule ^admin/(.*)&act=custom/language/products/edit&lang=$1&product_alias=$2 admin/index.php?

#NEWS
RewriteRule ^admin/(.*)&act=custom/language/pages/news/news&lang=$1&nid=$2&nn=$3 admin/index.php?
RewriteRule ^admin/(.*)&act=custom/language/pages/news/news_edit&lang=$1&nid=$2&nn=$3 admin/index.php?

php_value upload_max_filesize 100M
php_value post_max_size 100M

RewriteRule sitemap.xml sitemap.php [nocase]
```