

```
# Apache configuration file
# httpd.apache.org/docs/2.2/mod/quickreference.html

# Note .htaccess files are an overhead, this logic should be in your Apache config if
# possible
# httpd.apache.org/docs/2.2/howto/htaccess.html

# Techniques in here adapted from all over, including:
# Kroc Camen: camendesign.com/.htaccess
# perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
# Sample .htaccess file of CMS MODx: modx.com

###
### If you run a webserver other than apache, consider:
### github.com/paulirish/html5-boilerplate-server-configs
###

# -----
# Start rewrite engine
# -----

<IfModule mod_rewrite.c>
  RewriteEngine On
  RewriteBase /gircms/
</IfModule>

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    BrowserMatch MSIE ie
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
  </IfModule>
</IfModule>
```

```
<IfModule mod_headers.c>
# Because X-UA-Compatible isn't sent to non-IE (to save header bytes),
# We need to inform proxies that content changes based on UA
Header append Vary User-Agent
# Cache control is set only if mod_headers is enabled, so that's unnecessary to declare
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain ajax requests, disabled.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
# Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# Webfont access
# -----

# allow access from all domains for webfonts
# alternatively you could only whitelist
# your subdomains like "sub.domain.com"

<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</FilesMatch>

# -----
# Proper MIME type for all files
# -----

# audio
AddType audio/ogg oga ogg

.. ..
```

video

AddType video/ogg ogv
AddType video/mp4 mp4
AddType video/webm webm

Proper svg serving. Required for svg webfonts on iPad

twitter.com/FontSquirrel/status/14855840545

AddType image/svg+xml svg svgz
AddEncoding gzip svgz

webfonts

AddType application/vnd.ms-fontobject eot
AddType font/truetype ttf
AddType font/opentype otf
AddType application/x-font-woff woff

assorted types

AddType image/x-icon ico
AddType image/webp webp
AddType text/cache-manifest appcache manifest
AddType text/x-component htc
AddType application/x-chrome-extension crx
AddType application/x-xpinstall xpi
AddType application/octet-stream safariextz

-----

Allow concatenation from within specific js and css files

-----

e.g. Inside of script, combined.js you could have

<!--#include file="libs/jquery-1.5.0.min.js" -->

<!--#include file="plugins/jquery.idletimer.js" -->

and they would be included into this single file

this is not in use in the boilerplate as it stands, you may

choose to name your files in this way for this advantage

or concatenate and minify them manually.

Disabled by default.

<FilesMatch "\.combined\. (js|css)\$">

Options +Includes

```

# SetOutputFilter INCLUDES
# </FilesMatch>

# -----
# gzip compression
# -----

<IfModule mod_deflate.c>

# force deflate for mangled headers developer, yahoo.com/blogs/ydn/posts/2010/12/pushing-
beyond-gzipping/
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
    ^((gzip|deflate)\s,?\s(gzip|deflate)? X(4,13)|^(4,13)|-(4,13))$ HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>
# html, txt, css, js, json, xml, htc:
<IfModule filter_module>
  FilterDeclare COMPRESS
  FilterProvider COMPRESS DEFLATE resp=Content-Type
/text/(html|css|javascript|plain|x(ml|-component))/
  FilterProvider COMPRESS DEFLATE resp=Content-Type /application/(javascript|json|xml|x-
javascript)/
  FilterChain COMPRESS
  FilterProtocol COMPRESS change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
  # Legacy versions of Apache
  AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
  AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-
javascript
  AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
</IfModule>

# webfonts and svg:
<FilesMatch "\.(ttf|otf|eot|svg)$" >
  SetOutputFilter DEFLATE
</FilesMatch>

```

```
</IfModule>
```

```
# -----  
# Expires headers (for better cache control)  
# -----  
  
# these are pretty far-future expires headers  
# they assume you control versioning with cachebusting query params like  
# <script src="application.js?20100608">  
# additionally, consider that outdated proxies may miscache  
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/  
  
# if you don't use filenames to version, lower the css and js to something like  
# "access plus 1 week" or so
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

```
# Perhaps better to whitelist expires rules? Perhaps.
```

```
ExpiresDefault "access plus 1 month"
```

```
# cache, apcache needs re-requests in FF 3.6 (thx Remy "Introducing HTML5")
```

```
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

```
# your document html
```

```
ExpiresByType text/html "access plus 0 seconds"
```

```
# data
```

```
ExpiresByType text/xml "access plus 0 seconds"
```

```
ExpiresByType application/xml "access plus 0 seconds"
```

```
ExpiresByType application/json "access plus 0 seconds"
```

```
# rss feed
```

```
ExpiresByType application/rss+xml "access plus 1 hour"
```

```
# favicon (cannot be renamed)
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

```
# media: images, video, audio
```

```
ExpiresByType image/gif "access plus 1 month"
```

```
ExpiresByType image/png "access plus 1 month"
```

```
ExpiresByType image/jpg "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# htc files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# webfonts
ExpiresByType font/truetype "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# css and javascript
ExpiresByType text/css "access plus 2 months"
ExpiresByType application/javascript "access plus 2 months"
ExpiresByType text/javascript "access plus 2 months"

<IfModule mod_headers.c>
  Header append Cache-Control "public"
</IfModule>

</IfModule>

# -----
# ETag removal
# -----

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----
```

```
# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above). If
# needed, un-comment the following rules.

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, uncomment and specify a path or regex in the Location directive

# <IfModule mod_headers.c>
#   <Location />
#     Header set P3P "policyref=\"/w3c/p3p.xml\", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD
IVAI IVDi CONi HIS OUR IND CNT\""
#   </Location>
# </IfModule>

# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs - especially not
with and
# without "www." at the beginning, since this can cause SEO problems (duplicate content).
# That's why you should choose one of the alternatives and redirect the other one.

# By default option 1 (no "www.") is activated. Remember: Shorter URLs are sexier.
# no-www.org/faq.php?q=class_b

# If you rather want to use option 2, just comment out all option 1 lines
# and uncomment option 2.
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----
```

```
# Option 1:
# Rewrite "www.domain.com -> domain.com"

<IfModule mod_rewrite.c>
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
  RewriteRule ^(.*)$ http://%1/$1 [R=301,L]
</IfModule>

# -----

# Option 2:
# To rewrite "domain.com -> www.domain.com" uncomment the following lines.
# Be aware that the following rule might not be a good idea if you
# use "real" subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\..+$ [NC]
#   RewriteCond %{HTTP_HOST} (.+$) [NC]
#   RewriteRule ^(.*)$ http://www.%1/$1 [R=301,L]
# </IfModule>

# -----
# Add/remove trailing slash to (non-file) URLs
# -----

# Google treats URLs with and without trailing slashes separately.
# Forcing a trailing slash is usually preferred, but all that's really
# important is that one correctly redirects to the other.

# By default option 1 (force trailing slash) is activated.
# http://googlewebmastercentral.blogspot.com/2010/04/to-slash-or-not-to-slash.html
# http://www.alistapart.com/articles/slashforward/
# http://httpd.apache.org/docs/2.0/misc/rewriteguide.html#url Trailing Slash Problem

# -----

# Option 1:
# Rewrite "domain.com/foo -> domain.com/foo/"
```

```
#<IfModule mod_rewrite.c>
# RewriteCond %{REQUEST_FILENAME} !-f
# RewriteCond %{REQUEST_URI} !(\. [a-zA-Z0-9]{1,5}|/| #(.*)$)
# RewriteRule ^(.*)$ /$1/ [R=301,L]
#</IfModule>

# -----

# Option 2:
# Rewrite "domain.com/foo/ -> domain.com/food"

#<IfModule mod_rewrite.c>
# RewriteRule ^(.*)/$ /$1 [R=301,L]
#</IfModule>

# -----

# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version revving,
# you might want to consider enabling this, which will route requests for
# /css/style.20110203.css to /css/style.css

# To understand why this is important and a better idea than all.css?v1231,
# read: github.com/paulirish/html5-boilerplate/wiki/Version-Control-with-Cachebusting

# Uncomment to enable.
# <IfModule mod_rewrite.c>
# RewriteCond %{REQUEST_FILENAME} !-f
# RewriteCond %{REQUEST_FILENAME} !-d
# RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1.$3 [L]
# </IfModule>

# -----

# Prevent SSL cert warnings
# -----

# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent
# https://www.domain.com when your cert only allows https://secure.domain.com
# Uncomment the following lines to use this feature
```

```
# UNCOMMENT THE FOLLOWING LINES TO USE THE FEATURES
```

```
# <IfModule mod_rewrite.c>  
# RewriteCond %{SERVER_PORT} !^443  
# RewriteRule (.*) https://example-domain-please-change-me.com/$1 [R=301,L]  
# </IfModule>
```

```
# -----  
# Prevent 404 errors for non-existing redirected folders  
# -----
```

```
# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name  
does not exist
```

```
# e.g. /blog/hello : webmasterworld.com/apache/3888792.htm
```

Options -MultiViews

```
# -----  
# custom 404 page  
# -----
```

```
# You can add custom pages to handle 500 or 403 pretty easily, if you like.
```

```
ErrorDocument 403 /files/index?url=403
```

```
ErrorDocument 404 files/index?url=404
```

```
ErrorDocument 500 files/index?url=500
```

```
# -----  
# UTF-8 encoding  
# -----
```

```
# use utf-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

```
# force utf-8 for a number of file formats
```

```
AddCharset utf-8 .html .css .js .xml .json .rss
```

```
# -----  
# A little more security  
# -----
```

```
# Do we want to advertise the exact version number of Apache we're running?
```

```
# DefineEnvVar
```

```
# Probably not.
## This can only be enabled if used in httpd.conf - It will not work in .htaccess
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a default document
# Usually you should leave this activated, because you shouldn't allow everybody to surf
through
# every folder on your server (which includes rather private places like CMS system
folders).
Options -Indexes

# Block access to "hidden" directories whose names begin with a period. This
# includes directories used by version control systems such as Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteRule "(^/)\." - [F]
</IfModule>

# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS :
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Pages
<IfModule mod_rewrite.c>
    RewriteEngine on

    RewriteCond %{REQUEST_URI} (/robots\.txt|/favicon\.ico|/crossdomain\.xml|/apple-touch-
icon\.png)$
    RewriteRule    (.*) files/extras/$1    [QSA,L]
```

```
#RewriteRule ^style/(. #\. css) lib/combine. php?type=css&files=$1  
#RewriteRule ^scripts/(. #\. js) lib/combine. php?type=javascript&files=$1
```

```
RewriteCond %(REQUEST_FILENAME) !-d
```

```
RewriteCond %(REQUEST_FILENAME) !-f
```

```
RewriteCond %(REQUEST_URI)
```

```
!^(/robots\. txt|/favicon\. icol 403|/docs/license\. txt| combine\. php)
```

```
RewriteRule (. *) files/$1 [QSA, L]
```

```
RewriteRule ^$ files/ [QSA, L]
```

```
</IfModule>
```