

```
###
### Regole inserite da me
###

RewriteEngine on

RewriteCond %{HTTP_HOST} ^(\.+)$ [NC]
RewriteRule ^http-bind http://%1:5280/http-bind [P]

# Devio tutte le richieste a "script.js" e "style.css" a PHP minify
RewriteRule ^js/script.js$ /min/?g=js [L]
RewriteRule ^css/style.css$ /min/?g=css [L]

###
### Regole da html5-boilerplate
###

# Apache configuration file
# httpd.apache.org/docs/2.2/mod/quickreference.html

# Note .htaccess files are an overhead, this logic should be in your Apache config if possible
# httpd.apache.org/docs/2.2/howto/htaccess.html

# Techniques in here adapted from all over, including:
#   Kroc Camen: camendesign.com/.htaccess
#   perishablepress.com/press/2006/01/10/stupid-htaccess-tricks/
#   Sample .htaccess file of CMS MODx: modxcms.com

###
### If you run a webserver other than apache, consider:
### github.com/paulirish/html5-boilerplate-server-configs
###

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk
```

```

<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=Edge,chrome=1"
    # mod_headers can't match by content-type, but we don't want to send this header on *ev
    <FilesMatch "\.(js|css|gif|png|jpe?
gl|pdf|xml|ogal|ogg|m4a|ogv|mp4|m4v|webm|svg|svgz|eot|ttf|otf|woff|ico|webp|appcache|manifest|
>
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# -----
# Cross-domain AJAX requests
# -----

# Serve cross-domain ajax requests, disabled.
# enable-cors.org
# code.google.com/p/html5security/wiki/CrossOriginRequestSecurity

# <IfModule mod_headers.c>
#   Header set Access-Control-Allow-Origin "*"
# </IfModule>

# -----
# Webfont access
# -----

# Allow access from all domains for webfonts.
# Alternatively you could only whitelist your
# subdomains like "subdomain.example.com".

<FilesMatch "\.(ttf|ttc|otf|eot|woff|font. css)$">
    <IfModule mod_headers.c>
        Header set Access-Control-Allow-Origin "*"
    </IfModule>
</FilesMatch>

# -----
# Proper MIME type for all files
# -----

" - - - - -

```

```
# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/javascript js
```

```
# Audio
```

```
AddType audio/ogg oga ogg
```

```
AddType audio/mp4 m4a
```

```
# Video
```

```
AddType video/ogg ogv
```

```
AddType video/mp4 mp4 m4v
```

```
AddType video/webm webm
```

```
# SVG
```

```
# Required for svg webfonts on iPad
```

```
# twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml svg svgz
```

```
AddEncoding gzip svgz
```

```
# Webfonts
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType application/x-font-ttf ttf ttc
```

```
AddType font/opentype otf
```

```
AddType application/x-font-woff woff
```

```
# Assorted types
```

```
AddType image/x-icon ico
```

```
AddType image/webp webp
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/x-component htc
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/octet-stream safariextz
```

```
AddType text/x-vcard vcf
```

```
# -----
```

```
# Allow concatenation from within specific js and css files
```

```
# -----
```

```
# e.g. Inside of script.combined.js you could have
```

```
<script src="script.combined.js" type="text/javascript">
```

```

# <!--#include file="libs/jquery-1.5.0.min.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# This is not in use in the boilerplate as it stands. You may
# choose to name your files in this way for this advantage or
# concatenate and minify them manually.
# Disabled by default.

#<FilesMatch "\.combined\.js$"
# Options +Includes
# AddOutputFilterByType INCLUDES application/javascript application/json
# SetOutputFilter INCLUDES
#</FilesMatch>
#<FilesMatch "\.combined\.css$"
# Options +Includes
# AddOutputFilterByType INCLUDES text/css
# SetOutputFilter INCLUDES
#</FilesMatch>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

# Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-bey
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$ ^((gzip|deflate)\s)
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>

# HTML, TXT, CSS, JavaScript, JSON, XML, HTC:
<IfModule filter_module>
  FilterDeclare COMPRESS
  FilterProvider COMPRESS DEFLATE resp=Content-Type $text/html
  FilterProvider COMPRESS DEFLATE resp=Content-Type $text/css
  FilterProvider COMPRESS DEFLATE resp=Content-Type $text/plain

```

```

FilterProvider COMPRESS DEFLATE resp=Content-Type $text/xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $text/x-component
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/javascript
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/json
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/xhtml+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/rss+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/atom+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/vnd.ms-fontobject
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/svg+xml
FilterProvider COMPRESS DEFLATE resp=Content-Type $image/x-icon
FilterProvider COMPRESS DEFLATE resp=Content-Type $application/x-font-ttf
FilterProvider COMPRESS DEFLATE resp=Content-Type $font/opentype
FilterChain COMPRESS
FilterProtocol COMPRESS DEFLATE change=yes;byteranges=no
</IfModule>

<IfModule !mod_filter.c>
  # Legacy versions of Apache
  AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
  AddOutputFilterByType DEFLATE application/javascript
  AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
  AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml application/atom+
  AddOutputFilterByType DEFLATE image/x-icon image/svg+xml application/vnd.ms-fontobject app
font/opentype
</IfModule>
</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with cachebusting query params like
# <script src="application.js?20100608">
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week" or so.

```

```
<IfModule mod_expires.c>
    ExpiresActive on

    # Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault          "access plus 1 month"

    # cache, apache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
    ExpiresByType text/cache-manifest "access plus 0 seconds"

    # Your document html
    ExpiresByType text/html          "access plus 0 seconds"

    # Data
    ExpiresByType text/xml           "access plus 0 seconds"
    ExpiresByType application/xml    "access plus 0 seconds"
    ExpiresByType application/json   "access plus 0 seconds"

    # Feed
    ExpiresByType application/rss+xml "access plus 1 hour"
    ExpiresByType application/atom+xml "access plus 1 hour"

    # Favicon (cannot be renamed)
    ExpiresByType image/x-icon       "access plus 1 week"

    # Media: images, video, audio
    ExpiresByType image/gif          "access plus 1 month"
    ExpiresByType image/png          "access plus 1 month"
    ExpiresByType image/jpg         "access plus 1 month"
    ExpiresByType image/jpeg        "access plus 1 month"
    ExpiresByType video/ogg          "access plus 1 month"
    ExpiresByType audio/ogg          "access plus 1 month"
    ExpiresByType video/mp4         "access plus 1 month"
    ExpiresByType video/webm        "access plus 1 month"

    # HTC files (css3pie)
    ExpiresByType text/x-component   "access plus 1 month"

    # Webfonts
    ExpiresByType font/truetype      "access plus 1 month"
    ExpiresByType font/opentype      "access plus 1 month"
    ExpiresByType application/x-font-woff "access plus 1 month"
```

```
ExpiresByType image/svg+xml          "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css                "access plus 1 year"
ExpiresByType application/javascript  "access plus 1 year"

<IfModule mod_headers.c>
    Header append Cache-Control "public"
</IfModule>

</IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Stop screen flicker in IE on CSS rollovers
# -----

# The following directives stop screen flicker in IE on CSS rollovers - in
# combination with the "ExpiresByType" rules for images (see above). If
# needed, un-comment the following rules.

# BrowserMatch "MSIE" brokenvary=1
# BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
# BrowserMatch "Opera" !brokenvary
# SetEnvIf brokenvary 1 force-no-vary

# -----
```

```
# Cookie setting from iframes
# -----

# Allow cookies to be set from iframes (for IE only)
# If needed, uncomment and specify a path or regex in the Location directive

# <IfModule mod_headers.c>
#   <Location />
#     Header set P3P "policyref=\"/w3c/p3p.xml\"", CP=\"IDC DSP COR ADM DEVI TAIi PSA PSD IW
CNT\"""
#   </Location>
# </IfModule>

# -----
# Start rewrite engine
# -----

# Turning on the rewrite engine is necessary for the following rules and features.
# FollowSymLinks must be enabled for this to work.

<IfModule mod_rewrite.c>
  Options +FollowSymlinks
  RewriteEngine On
</IfModule>

# -----
# Suppress or force the "www." at the beginning of URLs
# -----

# The same content should never be available under two different URLs - especially not with
# without "www." at the beginning, since this can cause SEO problems (duplicate content).
# That's why you should choose one of the alternatives and redirect the other one.

# By default option 1 (no "www.") is activated. Remember: Shorter URLs are sexier.
# no-www.org/faq.php?q=class_b

# If you rather want to use option 2, just comment out all option 1 lines
# and uncomment option 2.
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!

# -----
```



```

..

# Option 1:
# Rewrite "www.example.com -> example.com"

<IfModule mod_rewrite.c>
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----

# Option 2:
# To rewrite "example.com -> www.example.com" uncomment the following lines.
# Be aware that the following rule might not be a good idea if you
# use "real" subdomains for certain parts of your website.

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\..+$ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----

# Built-in filename-based cache busting
# -----

# If you're not using the build script to manage your filename version revving,
# you might want to consider enabling this, which will route requests for
# /css/style.20110203.css to /css/style.css

# To understand why this is important and a better idea than all.css?v1231,
# read: github.com/paulirish/html5-boilerplate/wiki/Version-Control-with-Cachebusting

# Uncomment to enable.
<IfModule mod_rewrite.c>
  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteCond %{REQUEST_FILENAME} !-d
  RewriteRule ^(.+)\.(\d+)\. (js|css|png|jpg|gif)$ $1.$3 [L]
</IfModule>

```

```
# -----  
# Prevent SSL cert warnings  
# -----  
  
# Rewrite secure requests properly to prevent SSL cert warnings, e.g. prevent  
# https://www.example.com when your cert only allows https://secure.example.com  
# Uncomment the following lines to use this feature.  
  
# <IfModule mod_rewrite.c>  
# RewriteCond %{SERVER_PORT} !^443  
# RewriteRule ^ https://example-domain-please-change-me.com%{REQUEST_URI} [R=301,L]  
# </IfModule>  
  
# -----  
# Prevent 404 errors for non-existing redirected folders  
# -----  
  
# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name does  
# e.g. /blog/hello : webmasterworld.com/apache/3808792.htm
```

Options -MultiViews

```
# -----  
# Custom 404 page  
# -----  
  
# You can add custom pages to handle 500 or 403 pretty easily, if you like.  
ErrorDocument 404 /404.html  
  
# -----  
# UTF-8 encoding  
# -----  
  
# Use UTF-8 encoding for anything served text/plain or text/html  
AddDefaultCharset utf-8  
  
# Force UTF-8 for a number of file formats  
AddCharset utf-8 .html .css .js .xml .json .rss .atom  
  
# -----  
# Don't allow the server to handle 404s
```

```
# A little more security
# -----

# Do we want to advertise the exact version number of Apache we're running?
# Probably not.
## This can only be enabled if used in httpd.conf - It will not work in .htaccess
# ServerTokens Prod

# "-Indexes" will have Apache block users from browsing folders without a default document
# Usually you should leave this activated, because you shouldn't allow everybody to surf thi
# every folder on your server (which includes rather private places like CMS system folders.
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# Block access to "hidden" directories whose names begin with a period. This
# includes directories used by version control systems such as Subversion or Git.
<IfModule mod_rewrite.c>
    RewriteRule "(^/)\." - [F]
</IfModule>

# If your server is not already configured as such, the following directive
# should be uncommented in order to set PHP's register_globals option to OFF.
# This closes a major security hole that is abused by most XSS (cross-site
# scripting) attacks. For more information: http://php.net/register\_globals
#
# IF REGISTER_GLOBALS DIRECTIVE CAUSES 500 INTERNAL SERVER ERRORS :
#
# Your server does not allow PHP directives to be set via .htaccess. In that
# case you must make this change in your php.ini file instead. If you are
# using a commercial web host, contact the administrators for assistance in
# doing this. Not all servers allow local php.ini files, and they should
# include all PHP configurations (not just this one), or you will effectively
# reset everything to PHP defaults. Consult www.php.net for more detailed
# information about setting PHP directives.

# php_flag register_globals Off

# Rename session cookie to something else, than PHPSESSID
# php_value session.name sid

# -----
```

```
# Do not show you are using PHP
# Note: Move this line to php.ini since it won't work in .htaccess
# php_flag expose_php Off

# Level of log detail - log all errors
# php_value error_reporting -1

# Write errors to log file
# php_flag log_errors On

# Do not display errors in browser (production - Off, development - On)
# php_flag display_errors Off

# Do not display startup errors (production - Off, development - On)
# php_flag display_startup_errors Off

# Format errors in plain text
# Note: Leave this setting 'On' for xdebug's var_dump() output
# php_flag html_errors Off

# Show multiple occurrence of error
# php_flag ignore_repeated_errors Off

# Show same errors from different sources
# php_flag ignore_repeated_source Off

# Size limit for error messages
# php_value log_errors_max_len 1024

# Don't precede error with string (doesn't accept empty string, use whitespace if you need)
# php_value error_prepend_string " "

# Don't prepend to error (doesn't accept empty string, use whitespace if you need)
# php_value error_append_string " "

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

# -----
```

```

# Mobile specific server config
# -----

# blackberry types - http://goo.gl/A696I
AddType application/x-bb-appworld      bbaw
AddType text/vnd.rim.location.xloc     xloc
AddType text/x-vcard                   vcf

# nokia types - http://goo.gl/LU1bM
# http://wiki.forum.nokia.com/index.php/How_to_enable_DTA_(Over_The_Air)_SIS_install_from_y
AddType application/octet-stream      six
AddType application/vnd.symbian.install sis

# prevent mobile transcoding -
# <FilesMatch "\.(php|cgi|pl)$">
#   <IfModule mod_headers.c>
#     Header append Cache-Control "no-transform"
#     Header append Vary "User-Agent, Accept"
#   </IfModule>
# </FilesMatch>

# Mobile Redirection Script is used to detect if user is viewing the site
# from mobile device. If the script detects the user is viewing from
# mobile phone, they will be redirected to the mobile version of the site.
# One thing to note is that if you want to allow the user on the mobile version
# of your site to have the option to switch to desktop version, you may consider
# using other methods like JavaScript or PHP at http://detectmobilebrowser.com/
#
# To use the script, first, uncomment the lines below,
# second, change 'http://www.example.com/mobile' to the URL of your mobile site.

#RewriteEngine On
#RewriteBase /
#RewriteCond %{HTTP_USER_AGENT}
android|avantgo|blackberry|blazer|compal|elaine|fennec|hiptop|iemobile|ip(hone|od)|iris|kin
|maemo|mipd|mmp|opera\ m(ob|in)i|palm(\ os)?|phone|p(ixi|re)\|plucker|pocket|psp|symbian|t
(browser|link)|vodafone|wap|windows\ (cel|phone)|xda|xiino [NC,OR]
#RewriteCond %{HTTP_USER_AGENT} ^(1207|6310|6590|3gso|4thp|50[1-6]i|770s|802s|a\ wal|aba|ac
)|ai(kol|rn)|al(av|cal|co)|amoi|an(ex|nyl|yu)|aptul|ar(ch|go)|as(tel|us)|attw|au(di|l\ -m|r\ l|s
)|avan|be(ckl|ll|nq)|bi(1bl|rd)|bl(ack|az)|br(el|v)\w|bumbl|bu\-(n|u)|c55\|cap|ccwa|cdm\ -l|celll
|co(mpl|nd)|crawl|da(it|ll|ng)|dbtel|dc\ -s|devil|di|cal|dmobl|do(cl|p)|ds(12l|\ -d)|el(49l|ai)|em(12l|

```

7J0l osl wal ze)l fetcl fly(\-l_)l g1\ ul g560l genel gf\ -5l g\ -mol go(\. ul od)l gr(adl un)l hai el hci tl hd\ -
il ip)l hs\ -cl ht(c(\-l \ l_l al gl pl sl t)l tp)l hu(awl tc)l i\ -(20l gol ma)l i230l iac(\ l \ -
l \)l librol ideal ig0l ikoml im1kl innol ipaq l iris l ja(tl v)al jbr ol jemul jigs l kddil keji l kgt(\ l \)l ku
l kyo(cl k)l le(nol xi)l lg(\ gl \/(kl ll u)l 50l 54l e\ -l e\ /l \-[a-u])l libul lynxl ml \ -ul m3gal m50\ /l ma(t
crl me(dil rcl ri)l mi(o8l oal ts)l mmefl mo(01l 02l bil del dol t(\-l \ l ol v)l zz)l mt(50l pl v\)l mubpl myuk
3Jl n30(0l 2)l n50(0l 2l 5)l n7(0(0l 1)l 10)l ne((cl m)\ -
l onl tfl wfl wgl ut)l nok(6l i)l nzphl o2iml op(til uv)l oranl owg1l p800l pan(al dl t)l pdxgl pg(13l \-(11-
8Jl c))l phil l pirel pl(ayl uc)l pn\ -2l po(ckl rtl se)l proxl psi ol pt\ -gl qa\ -al qc(07l 12l 21l 32l 60l \-[2-
)l qtekl r380l r600l raksl rim9l ro(vel zo)l s55\ /l sa(gel mal mml msl nyl va)l sc(01l h\ -l ool p\ -)l sdk\ /l sei
l sharl sie(\-l m)l sk\ -0l sl(45l id)l sm(al l arl b3l itl t5)l so(ftl ny)l sp(01l h\ -l v\ -l v\
)l sy(01l mb)l t2(18l 50)l t6(00l 10l 18)l ta(gt l lk)l tc l \ -l tdg\ -l tel(il m)l tim\ -l t\ -mol to(pl l sh)l ts(
l m3l m5)l tx\ -9l up(\. bl gl l si)l utstl v400l v750l veril vi(rgl te)l vk(40l 5[0-3]l \ -
v)l vm40l vodal vul cl vx(52l 53l 60l 61l 70l 80l 81l 83l 85l 98)l w3c(\-l \)l webcl whi tl wi(g\ l ncl nw)l uml bl
l yourl zetol zte\ -) [NC]

#RewriteRule ^\$ http://www.example.com/mobile [R,L]