

#禁止下载

```
<FilesMatch "\.  
(engine|incl|info|install|lang|module|profile|test|pol|sh|. *sql|theme|tpl(\. php)?|xhtml|svn-  
base)$|^(\code-style|. pl|Entries. *| Repository| Root| Tag| Template| all-  
wcprops| entries| format)$">  
    Order allow,deny  
</FilesMatch>
```

PHP 设置

```
<IfModule mod_php5.c>  
    php_flag magic_quotes_gpc                off  
    php_flag magic_quotes_sybase            off  
    php_flag register_globals                off  
    php_flag session.auto_start             off  
    php_value mbstring.http_input           pass  
    php_value mbstring.http_output          pass  
    php_value mbstring.internal_encoding    utf-8  
    php_flag mbstring.encoding_translation  off  
</IfModule>
```

#重写规则

```
Options +FollowSymLinks
```

#默认404页面

```
ErrorDocument 404 /index.php
```

#默认首页

```
DirectoryIndex index.php
```

#设置 header 缓存过期时间

```
<IfModule mod_expires.c>  
    ExpiresActive On  
    ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
    # php 文件例外
```

```
    ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

返回压缩

```
<IfModule mod_deflate.c>
    AddOutputFilterByType DEFLATE text/html text/plain text/xml application/x-httpd-php
    AddOutputFilter DEFLATE js css
</IfModule>
```

伪静态化

```
<IfModule mod_rewrite.c>
    RewriteEngine on
```

以下两种方式不能同时启用

使用 www 访问，未加 www 前缀的访问将跳转

RewriteCond %{HTTP_HOST} !^www\. [NC]

RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [L,R=301]

#

不使用 www 前缀，以 www 前缀的访问将跳转

RewriteCond %{HTTP_HOST} ^www\. (.+)\$ [NC]

RewriteRule ^ http://%1%{REQUEST_URI} [L,R=301]

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !=/favicon.ico
```

```
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
```

```
</IfModule>
```